



Find more information on Conveyor Stand selection on Grainger.com.



Roller Material Support and Transfer Tables

- 500-lb. load capacity

Portable roller tables provide stability to feed material into or out of machinery in machine shops, woodshops, and fabrication facilities. Table height can be adjusted to keep material aligned for the intended tool or process.

Roller Width	Overall Width	Overall Length	Min. Height	Max. Height	Item No.
13 in	26 1/2 in	1 ft 5 in	26 1/2 in	43 1/2 in	2YE11
22 in	15 in	5 ft 6 in	26 1/2 in	43 1/2 in	4FE14
23 3/4 in	24 in	5 ft 6 in	26 1/2 in	43 1/2 in	2YE12



Material Support and Transfer Stands

Portable flat roller stands each have a single roller to support flat-bottomed sheets, planks, and bars. Portable V-roller stands each have two rollers in a V-shape to cradle cylindrical materials.

Overall Width	For Between Frame Width	Min. Height	Max. Height	Stand Load Capacity	Color	Item No.
Flat Roller						
15 3/4 in	14 in	23 in	38 1/2 in	1,760 lb	Gray	33VE10
	14 in	27 in	42 in	1,760 lb	Gray	33VE11
16 3/4 in	16 1/2 in	22 1/2 in	35 1/2 in	500 lb	White	33VE08
	16 1/2 in	28 1/2 in	47 1/2 in	500 lb	White	33VE09
V-Roller						
12 3/4 in	8 3/4 in	23 in	38 1/2 in	1,760 lb	Gray	33VE16
	8 3/4 in	27 in	42 in	1,760 lb	Gray	33VE17
16 3/4 in	8 3/4 in	28 in	45 in	500 lb	White	33VE13



Temporary Tripod Conveyor Support Stands

- 400-lb. capacity

Stands can temporarily support straight or curved sections of gravity-flow skate wheel or light-duty roller conveyors. Height adjusts to create a level or sloped conveying surface.

For Between Frame Width	Min. Height	Max. Height	Overall Width	Item No.	For Between Frame Width	Min. Height	Max. Height	Overall Width	Item No.
10 in	16 in	27 in	12 in	2WJL5	16 in	16 in	27 in	18 in	2WJN1
	25 in	43 in	12 in	3W432		25 in	43 in	18 in	3W433
	42 in	60 in	12 in	2WJL6	22 in	42 in	60 in	18 in	2WJN2
	16 in	27 in	15 in	2WJL7		16 in	27 in	24 in	2WJN3
13 in	25 in	43 in	15 in	2WJL8		25 in	43 in	24 in	3MY71
	42 in	60 in	15 in	2WJL9		42 in	60 in	24 in	2WJN4



Low-Profile Permanent Mount Conveyor Support Stands

- 2500-lb. load capacity per pair

Stands permanently mount light to extra-heavy duty conveyor sections close to the floor. Suitable for items that are too tall or too heavy to be lifted far off the ground.

Min. Height	Max. Height	Item No.
1 1/4 in	3 in	38AP28
2 1/4 in	4 3/4 in	38AP29
4 3/4 in	5 in	38AP30
4 1/4 in	5 3/4 in	38AP31
5 3/4 in	6 3/4 in	38AP32



Stationary Multitier

Portable Single-Tier




ASHLAND CONVEYOR PRODUCTS

H-Style Conveyor Support Stands

Stands support conveyor sections and can be adjusted to create a level or sloped conveying surface. Pivoting mounting brackets allow sloped installations. Choose an H-stand based on between-frame (BF) dimension and duty rating.

Note: Range of adjusted height is to top of H-stand.

Note: For a stand-alone conveyor, a min. of two supports is required. For two sections of conveyor, a min. of three supports is required (the middle stand supports both sections).



PERMANENT H-STAND

Stands bolt to the floor to provide permanent support for powered or unpowered (gravity-flow) conveyors.

PERMANENT MULTI-TIER

Stands each have two tiers for gravity-flow skate wheel or roller conveyors. Can help create multi-level flow racks. Each level has adjustable height.

PORTABLE SINGLE-TIER

Stands have casters that make skate wheel and roller conveyor sections portable. Brakes prevent the stands from rolling when locked.

For Between Frame Width	Overall Width	Min. Height	Max. Height	Brand	Item No.	For Between Frame Width	Overall Width	Min. Height	Max. Height	Brand	Item No.
Portable Single-Tier											
Light- to Medium-Duty — 1,800 lb Load Cap.											
13 in	13 in	22 1/2 in	32 3/4 in	—	2WJK3	27 in	19 1/2 in	31 in	—	—	2WJJ7
16 in	16 in	22 1/2 in	32 3/4 in	—	1PDP3	27 in	31 in	43 in	—	—	2WJK1
22 in	22 in	22 1/2 in	32 3/4 in	—	1PDP4	27 in	43 in	55 in	—	—	42X896
27 in	27 in	22 1/2 in	32 3/4 in	—	2WJK4	27 in	55 in	67 in	—	—	42X904
—	36 in	22 1/2 in	32 3/4 in	—	1PDP5	27 in	67 in	79 in	—	—	42X911
						27 in	79 in	109 in	—	—	42X918
						31 in	19 1/2 in	31 in	—	—	2WJJ8
						31 in	31 in	43 in	—	—	2WJK2
Permanent Mounted Multi-Tier H-Stand											
Light- to Extra Heavy-Duty — 2,500 lb Load Cap.											
10 in	10 in	3 3/4 in	46 in	—	6GKK3	31 in	31 in	43 in	—	—	42X897
	10 in	3 3/4 in	82 in	—	6GKL0	31 in	55 in	67 in	—	—	42X905
	13 in	3 3/4 in	46 in	—	6GKK4	31 in	67 in	79 in	—	—	42X912
	13 in	3 3/4 in	82 in	—	6GKL1	31 in	79 in	109 in	—	—	42X919
	16 in	3 3/4 in	46 in	—	6GKK5	36 in	19 1/2 in	31 in	—	—	5W818
	16 in	3 3/4 in	82 in	—	6DKX7	36 in	31 in	43 in	—	—	5W819
	22 in	3 3/4 in	46 in	—	6DKX8	36 in	43 in	55 in	—	—	42X898
	22 in	3 3/4 in	82 in	—	6GKK6	36 in	55 in	67 in	—	—	42X906
	27 in	3 3/4 in	46 in	—	6DKX9	36 in	67 in	79 in	—	—	42X913
	27 in	3 3/4 in	82 in	—	6GKK7	36 in	79 in	109 in	—	—	42X920
	31 in	3 3/4 in	46 in	—	6DKX8	Heavy-Duty — 3,000 lb Load Cap.					
	31 in	3 3/4 in	82 in	—	6DKY0	13 in	13 in	25 3/4 in	36 3/4 in	—	2WJL2
	36 in	3 3/4 in	46 in	—	6GKK9	21 in	21 in	16 1/2 in	26 1/4 in	—	2WJK9
Permanent Mounted H-Stand											
Light- to Medium-Duty — 1,500 lb Load Cap.											
10 in	10 in	19 1/2 in	31 in	—	5W812	27 in	27 in	25 3/4 in	36 3/4 in	—	1PDR1
	10 in	31 in	43 in	—	5W813	39 in	39 in	25 3/4 in	36 3/4 in	—	2WJL4
	10 in	43 in	55 in	—	42X892	51 in	51 in	12 1/4 in	17 in	—	1PDP7
	10 in	55 in	67 in	—	42X899	54 in	54 in	25 3/4 in	36 3/4 in	—	1PDR2
	10 in	67 in	79 in	—	42X907	Extra Heavy-Duty — 5,000 lb Load Cap.					
	10 in	79 in	109 in	—	42X914	27 in	27 in	17 in	27 1/4 in	—	42X979
	13 in	19 1/2 in	31 in	—	2WJJ6	27 in	27 in	25 in	41 1/2 in	—	42X982
	13 in	31 in	43 in	—	2WJJ9	27 in	39 in	17 in	27 1/4 in	—	42X980
	13 in	43 in	55 in	—	42X893	39 in	39 in	25 in	41 1/2 in	—	42X983
	13 in	55 in	67 in	—	42X901	51 in	51 in	17 in	27 1/4 in	—	42X981
	13 in	67 in	79 in	—	42X908	51 in	51 in	25 in	41 1/2 in	—	42X984
	13 in	79 in	109 in	—	42X915	For Between Frame Width					
	17 in	19 1/2 in	31 in	—	5W814	Brand					
	16 in	31 in	43 in	—	5W815	Item No.					
	16 in	43 in	55 in	—	42X894	Tier Addition Kits for Light- to Extra Heavy-Duty Conveyors					
	16 in	55 in	67 in	—	42X902	13 in	—	—	—	—	6DKY3
	16 in	67 in	79 in	—	42X909	16 in	—	—	—	—	6DKY4
	16 in	79 in	109 in	—	42X916	27 in	—	—	—	—	6DKY6
	22 in	31 in	43 in	—	5W817	31 in	—	—	—	—	6DKY7
	22 in	43 in	55 in	—	42X895	36 in	—	—	—	—	6DKY8
	22 in	55 in	67 in	—	42X903						
	22 in	67 in	79 in	—	42X910						
	22 in	79 in	109 in	—	42X917						