



2VKH9



### Wire Rope Clips

- Sizes 1/8" to 7/8" will develop 80% of cable breakage strength
- 1" size will develop 90% of cable breakage strength

Secure end of wire rope when turning back to form a loop. Galvanized finish.

For Wire Rope Dia.	Rope Turn Back	DAYTON MALEABLE IRON		DAYTON FORGED STEEL		CROSBY® FORGED STEEL		DAYTON 304 STAINLESS STEEL	
		Min. No. of Clips	Item No.	Min. No. of Clips	Item No.	Min. No. of Clips	Item No.	Min. No. of Clips	Item No.
1/8 in	3 1/4 in	3	2VKH9	2	4DV33	2	29WP16	3	2VKG6
3/16 in	3 3/4 in	3	2VKJ1	2	4DV34	2	29WP17	3	2VKH1
1/4 in	4 3/4 in	—	—	2	4DV35	2	29WP18	3	2VKH3
5/16 in	5 1/4 in	3	2VKJ3	2	4DV36	2	29WP19	3	2VKH5
3/8 in	6 1/2 in	3	2VKJ4	2	4DV37	2	29WP20	3	2VKH7
7/16 in	7 in	3	2VKJ5	2	4DV38	—	—	—	—
1/2 in	11 1/2 in	—	—	—	—	3	29WP22	—	—
5/8 in	12 in	4	2VKJ6	3	4DV39	—	—	—	—
3/4 in	12 in	—	—	3	4DV40	—	—	—	—
7/8 in	12 in	—	—	—	—	3	29WP24	—	—
1 in	12 in	4	2VKJ8	3	4DV41	—	—	—	—
1 1/8 in	18 in	5	2VKJ9	4	4DV42	4	29WP25	—	—
1 1/4 in	20 in	5	2VKK1	4	4DV43	4	29WP26	—	—
1 3/8 in	26 in	6	2VKK2	5	4DV44	5	29WP27	—	—
1 1/2 in	34 in	—	—	—	—	6	29WP28	—	—
1 3/4 in	44 in	—	—	—	—	7	29WP29	—	—
1 7/8 in	44 in	—	—	—	—	7	29WP30	—	—
2 in	54 in	—	—	—	—	8	29WP31	—	—



1DKK4



### Clip and Thimble Sets

Each set includes 1 thimble and 2 U-bolt type wire rope clips, except 2VKK6 which includes 1 thimble and 3 U-bolt-type clips.

For Wire Rope Dia.	GALVANIZED STEEL		STAINLESS STEEL	
	Item No.	Item No.	Item No.	Item No.
1/8 in	1DKK4	1DKK9	—	—
3/16 in	1DKK5	1DKL1	—	—
1/4 in	—	1DKL2	—	—
5/16 in	—	1DKL3	—	—
3/8 in	1DKK8	1DKL4	—	—
7/16 in	2VKK3	—	—	—
1/2 in	2VKK4	2VKK6	—	—



4FRY5



### 316 Stainless Steel Wire Rope Clip and Thimble Sets

Each set includes 1 thimble and the appropriate number of U-bolt type clips. Made with 316 stainless steel.

For Wire Rope Dia.	Min. No. of Clips	Item No.
5/16 in to 3/2 in	2	4FRY5
1/8 in	2	4FRY6
3/16 in	2	4FRY7
1/4 in	2	4FRY8
5/16 in	2	4FRY9
3/8 in	3	4FRZ1
1/2 in	3	4FRZ2
5/8 in	3	4FRZ3
3/4 in	3	4FRZ4
7/8 in	4	4FRZ5



29WP32

### Crosby Fist Grip Clips

Double saddle allows for quick installation. Steel construction with galvanized finish. Include heavy hex nuts. Meet FF-C-450 Standards.

For Wire Rope Dia.	Min. No. of Clips	Rope Turn Back	Min. Torque	Item No.
3/16 in to 1/4 in	2	4 in	30 ft-lb	29WP32
5/16 in	2	5 in	30 ft-lb	29WP33
3/8 in	2	5 1/4 in	45 ft-lb	29WP34
7/16 in to 1/2 in	3	11 in	65 ft-lb	29WP35
5/8 in to 3/8 in	3	13 1/2 in	130 ft-lb	29WP36
3/4 in	3	16 in	225 ft-lb	29WP37
7/8 in	4	26 in	225 ft-lb	29WP38
1 in	5	37 in	225 ft-lb	29WP39
1 1/8 in	5	41 in	360 ft-lb	29WP40
1 1/4 in	6	55 in	360 ft-lb	29WP41



1DLG1



### Wire Rope Thimbles

Thimbles extend usable life of cable by protecting against everyday wear. Compatible with sleeves or wire rope clips.

For Wire Rope Dia.	DAYTON ZINC-PLATED		DAYTON GALVANIZED		CROSBY GALVANIZED		DAYTON STAINLESS STEEL	
	Item No.	Pkg. Qty.	Item No.	Pkg. Qty.	Item No.	Pkg. Qty.	Item No.	Pkg. Qty.
1/8 in	—	—	—	—	—	—	1DLG6	25
1/16 in	1DLG1	25	2VKK7	25	48FR63	1	1DLG8	25
3/16 in	1DLG2	25	2VKK8	25	48FR64	1	1DLG9	25
1/4 in	1DLG3	25	2VKL1	25	48FR68	1	1DLH1	25
5/16 in	1DLG4	25	2VKL2	25	48FR69	1	1DLH2	25
3/8 in	1DLG5	25	2VKL3	25	48FR66	1	1DLH3	25
7/16 in	—	—	2VKL4	25	—	—	—	—
1/2 in	—	—	2VKL5	25	—	—	—	—
5/8 in	—	—	—	—	48FR67	1	—	—



1DKJ3



### Sleeve and Thimble Sets

Allow 100% cable strength. Use with cable swaging tools, sold separately.

**Galvanized Steel**—Include 2 zinc-plated thimbles and 2 aluminum alloy sleeves.

**Stainless Steel**—Include 2 stainless steel thimbles and 2 tin-plated copper sleeves.

For Wire Rope Dia.	GALVANIZED STEEL Item No.	STAINLESS STEEL Item No.
1/8 in	—	1DKJ6
1/16 in	1DKJ3	1DKJ8
3/16 in	1DKJ4	1DKJ9
1/4 in	1DKJ5	1DKK1
5/16 in	—	1DKK2
3/8 in	—	1DKK3

### Crosby Steel Tapered Sleeves

Standard steel sleeve terminations have an efficiency rating of 96% with IWRC or 93% with FC based on strength of wire rope. These sleeves are used for wire rope constructions: 6 x 19, 6 x 37, RRL, FC, and IWRC.



For Wire Rope Dia.	Steel Item No.
3/8 in	48FR72
1/2 in	48FR73
5/8 in	48FR74
1 1/4 in	48FR75