



Disposable Tank Liner

Straight-sided insert designed to fit a 2.8 gallon spray paint pressure feed tank 2TKN8. Lip snaps over the tank to prevent leakage between the insert and tank.



Description	Item No.
2.8 gal. Disposable Pressure Tank Liner, Pkg. of 10 Linear High Density Polyethylene, 9½"L, 10½"W, Thickness 0.01 Mil	5PB40



39AM04

Airless Paint Sprayers

Spray a wide range of coatings. ProConnect Pump Removal System allows for fast, on-the-job pump swap-out. Compatible with 1- and 5-gal. containers. Includes contractor-grade metal gun, RAC X reversible spray tip, and 50 ft. of BlueMax II hose.

390 PC Stand—Lightweight, reliable stand features variable pressure adjustment and an offset handle.

FinishPro GX19 Stand—Features the ProXChange Pump, the fast and easy on-the-job pump replacement, no tools required.

FinishPro II 395 PC Cart—Sprays in both airless and air-assisted airless modes for ultimate versatility. Includes contractor-grade metal air-assist gun, 2 RAC X reversible spray tips (210 and 517), flat tip (309), and 50-ft. of fluid and air hose.

Description	HP	Flow Rate	Operating Pressure	Mfr. Model	Item No.
390 PC Stand	¾ hp	0.47 gpm	3,300 psi	17C310	39AM04
FinishPro GX19 Stand	½ hp	0.38 gpm	3,000 psi	17F924	48YD46
Finish Pro II 395 PC Cart	¾ hp	0.43 gpm	3,300 psi	17C417	39AM07

Description	Tip Size	Pattern Size	Item No.
Tips			
Airless Tip LTX 413	0.013 in	8 in to 10 in	2WCW8
Airless Tip LTX 415	0.015 in	8 in to 10 in	2WCW9
Airless Tip LTX 515	0.015 in	10 in to 12 in	2WCX1
Airless Tip LTX 517	0.017 in	10 in to 12 in	2WCX2
Airless Tip LTX 521	0.021 in	10 in to 12 in	2WCX3
Airless Tip LTX 631	0.031 in	12 in to 14 in	2WCX4
Airless Tip FFLP210	0.01 in	4 in to 6 in	53JT75
Airless Tip FFLP310	0.01 in	6 in to 8 in	53JT76
Airless Tip FFLP410	0.01 in	8 in to 10 in	53JT77
Airless Tip FFLP212	0.012 in	4 in to 6 in	53JT80
Airless Tip FFLP616	0.016 in	12 in to 14 in	53JT88
Airless Tip Guard, ⅞" Thread	—	—	2WCX9
Airless Tip Guard, ⅜" Thread	—	—	2WCY1

Description	Max. Pressure	Nozzle Size	Item No.
Accessories			
Contractor Ftx Airless Spray Gun	3,600 psi	0.015 in	2WCW3
Contractor Airless Spray Gun	3,600 psi	0.017 in	2WCW4
Airless In-Line Valve	3,600 psi	—	2WCY3
Airless Spray Gun & Hose Kit	3,600 psi	0.017 in	2WCW5
Airless Hose ¼" x 50 ft.	—	—	2WCY2
Pump Armor Fluid, 1 qt.	—	—	2WCW6
TSL Seal Liquid, 1 qt.	—	—	2WCW7
Endurance Lower Pump	—	—	39CT94
Pump Replacement Kit, ProXChange	—	—	43LD26
Express Pump, 2004 to 2014 Models	—	—	43LD30
Express Pump, 2015 and Newer Models	—	—	43LD31
Endurance Pump, 2004 to 2014 Models	—	—	43LD32



53JT67



48YD42



Airless Line Strippers

■ See striping paints on page 1548

LineLazer 3400—This 1-gun, airless stripper is perfect for small parking lots, schools, park and recreation departments, factory safety lines, and re-stripe jobs.

LineLazer 3900—This 2-gun airless stripper is ideal for parking lots, roadways, athletic fields, and factory safety lines.

LineLazer 5900—Designed for larger striping jobs such as large parking facilities, roadways, athletic fields, and factory lines.

Description	Flow Rate	Second Gun Outlet	Waterborne Compatible	Max. Pressure	Max. Tip Size	Body Material	Mfr. Model	Item No.
LineLazer 3400, 1-Gun	0.75 gpm	No	Yes	3,300 psi	0.027 in	Steel	25M224	53JT67
LineLazer V 3900 Standard - 2 Manual Guns	1.2 gpm	Yes	Yes	3,300 psi	0.036 in	Metal	17H450	48YD42
LineLazer V 3900 Standard - 2 Automatic Guns	1.2 gpm	Yes	Yes	3,300 psi	0.036 in	Metal	17H453	48YD43
LineLazer V 5900 Standard - 2 Manual Guns	1.6 gpm	Yes	Yes	3,300 psi	0.043 in	Metal	17H455	48YD44
LineLazer V 5900 Standard - 2 Automatic Guns	1.6 gpm	Yes	Yes	3,300 psi	0.043 in	Metal	17H458	48YD45

Description	For Use With Grainger Item Number	Item No.
Accessories		
LineLazer Tip Medium Film	48YD42, 48YD43, 48YD44, 48YD45, 53JT67	2WCW1
LineLazer Tip Heavy Film	48YD42, 48YD43, 48YD44, 48YD45, 53JT67	2WCW2
Inlet Strainer	48YD42, 48YD43, 48YD44, 48YD45	2LVU8
Manifold Filter	48YD42, 48YD43, 48YD44, 48YD45, 53JT67	2LVX1
Pump Repair Kit	48YD42, 48YD43	2LVU3
Pump Repair Kit	48YD44, 48YD45	2LVU4