



F8634



**Body Belts**

- Tongue buckle
- Available in multiple sizes

Have D-rings that connect to positioning and restraint lanyards that are attached to an anchor point on a building or structure. Allow workers to freely use both hands while positioning themselves correctly in a work area and remaining in place while working. They also prevent workers from getting too close to a fall hazard.

Number of D-Rings	D-Ring Locations	Includes Padding	Webbing Material	Hardware Material	Brand	Item No.
1	Back	Yes	Polyester	Stainless Steel	3M Dbi-Sala	K8295
1	Back	Yes	Nylon	Stainless Steel	Honeywell Miller	E1709
1	Back	No	Nylon	Stainless Steel	Honeywell Miller	F8634
2	Hips	Yes	Polyester	Stainless Steel	3M Dbi-Sala	K8296
2	Hips	Yes	Polyester	Steel	3M Protecta	H6704
2	Hips	Yes	Polyester	Steel	Condor	H7937
2	Hips	Yes	Nylon	Stainless Steel	Honeywell Miller	F8635



3NGH9



**Bosun's Chairs**

- Steel D-Rings
- Plywood seats

Allow workers to sit and work while suspended. Keep suspended workers comfortable by relieving pressure on the legs and hips and taking some of the weight of their equipment off the body. Chairs attach to full-body safety harnesses as part of a fall arrest system and do not provide fall protection on their own.

Weight Cap.	Seat Padding	Body Belt Included	Seat Depth	Seat Width	Brand	Item No.
310 lb	No	No	12 in	24 in	3M Dbi-Sala	3NGH9
310 lb	Yes	No	12 in	24 in	3M Dbi-Sala	3NGJ1
425 lb	No	No	11 1/2 in	23 1/2 in	Falltech	55ML27
425 lb	Yes	Small	11 1/2 in	23 1/2 in	Falltech	55ML23
425 lb	Yes	Medium	11 1/2 in	23 1/2 in	Falltech	55ML24
425 lb	Yes	Large	11 1/2 in	23 1/2 in	Falltech	55ML25
425 lb	Yes	X-Large	11 1/2 in	23 1/2 in	Falltech	55ML26



**Personal Fall Limiter**

- Meets ANSI standards
- Capacity: 310 lb.

Helps reduce total fall and deceleration distance. Steel frame with PVC cover. 2"W webbing with snap hook and swiveling carabiner. Features internal braking system.



SRL Length	Item No.
8 ft.	19F393



1XET6



1XET5



5RP70



2KUA6



49U970



**Personal Fall Limiters and Cab-Mount Bracket**

- Meet ANSI and CSA standards

**PERSONAL FALL LIMITERS (PFLs)**

Self-retracting lanyards with polyester webbing and quick-activating brake systems eliminate the need for extended fall distance clearance. 6-ft. working length is suitable for most applications; 9-ft. length is great for scaffolding and order picker applications; 11-ft. length offers maximum mobility.

Harness connectors have 3600-lb. gate strength unless noted as 5K (5000 lb.). Connectors are made of steel unless noted as aluminum.

**MiniLite®**

Lightweight stainless steel interior components with high-impact thermoplastic housing.

**Scorpion™**

Can be attached directly to the harness D-ring for use as a personal fall limiter or as a traditional lifeline.

**Turbo T-BAK™ Retractable Tie-Back**

All-in-1 design with anchorage connector reduces the amount of equipment required on a jobsite.

**TurboLite™**

Impact-resistant nylon housing is compact and lightweight. Unit attaches directly to harness back D-ring for increased mobility.

**Twin Turbo™ Systems**

Allow 2 TurboLite or Turbo T-BAK tie-back retractable PFLs to be connected to a single harness for 100% tie-off fall protection. Systems with D-ring connector easily attach to noncoated metallic back D-rings. Systems with lightweight G2 connector attach to harness webbing below the D-ring, leaving it open for other equipment. G2 Connector Kit and components are available separately.

SRL Length	No. of Legs	Anchorage Hook Type	Harness Hook Type	Weight Cap.	Mfr. Model	Item No.
<b>Personal Fall Limiters (PFLs)</b>						
<b>MiniLite®</b>						
11 ft.	1	—	Steel Snap Hook	310 lb	FL11-Z7/11FT	45JJ97
11 ft.	1	Carabiner, Swivel Shackles	Steel Snap Hook	310 lb	FL11-3-Z7/11FT	1XET6
<b>Scorpion™</b>						
9 ft.	1	Steel Snap Hook	Steel Carabiner	310 lb	PFL-4-Z7/9FT	1XET5
9 ft.	1	Steel Snap Hook	Steel Carabiner	310 lb	PFL-5/9FT	3AE97
<b>Turbo T-BAK™ Retractable Tie-Back</b>						
7 ft. 6"	1	5K® Snap Hook	—	400 lb	MFLT-1/7.5FT	19D179
7 ft. 6"	1	5K® Snap Hook	Steel Carabiner	400 lb	MFLT-2/7.5FT	5RP89
7 ft. 6"	1	5K® Snap Hook	Aluminum Carabiner	400 lb	MFLT-3/7.5FT	5RP70
7 ft. 6"	1	5K® Snap Hook	Snap Hook	400 lb	MFLT-5/7.5FT	19D181
<b>TurboLite™</b>						
6 ft.	1	Steel Snap Hook	Steel Carabiner	400 lb	MFL-1-Z7/6FT	2KUA6
6 ft.	1	Steel Rebar Hook	Steel Carabiner	400 lb	MFL-2-Z7/6FT	3RCC5
6 ft.	1	Aluminum Snap Hook	Aluminum Carabiner	310 lb	MFL-11-Z7/6FT	36WA13
6 ft.	1	Aluminum Rebar Hook	Aluminum Carabiner	400 lb	MFL-12-Z7/6FT	36WA12
9 ft.	1	Steel Snap Hook	—	400 lb	MFL-3-Z7/9FT	49U960
9 ft.	1	Aluminum Snap Hook	—	400 lb	MFL-16-Z7/9FT	49U954
9 ft.	1	Steel Snap Hook	Steel Carabiner	400 lb	MFL-1-Z7/9FT	49U957
9 ft.	1	Aluminum Snap Hook	Aluminum Carabiner	400 lb	MFL-11-Z7/9FT	49U949
9 ft.	1	Steel Snap Hook	Steel Snap Hook	400 lb	MFL-9-Z7/9FT	49U946
9 ft.	1	Aluminum Rebar Hook	Aluminum Carabiner	400 lb	MFL-12-Z7/9FT	49U951
<b>Twin Turbo™ System with D-Ring Connector</b>						
6 ft.	2	Steel Snap Hook	Snap Hook	400 lb	MFLB-3-Z7/6FT	5RP85
6 ft.	2	Steel Rebar Hook	Snap Hook	400 lb	MFLB-4-Z7/6FT	5RP86
7 ft. 6"	2	5K® Snap Hook	Aluminum Snap Hook	400 lb	MFLTB-1/7.5FT	5RP72
<b>Twin Turbo™ System with G2 Connector</b>						
6 ft.	2	Steel Snap Hook	Snap Hook	400 lb	MFLC-3-Z7/6FT	49U963
6 ft.	2	Steel Rebar Hook	Snap Hook	400 lb	MFLC-4-Z7/6FT	49U965
6 ft.	2	Aluminum Snap Hook	Snap Hook	400 lb	MFLC-11-Z7/6FT	49U968
6 ft.	2	Aluminum Rebar Hook	Snap Hook	400 lb	MFLC-12-Z7/6FT	49U970
9 ft.	2	Steel Snap Hook	Snap Hook	400 lb	MFLC-3-Z7/9FT	49U972
9 ft.	2	Aluminum Rebar Hook	Snap Hook	400 lb	MFLC-12-Z7/9FT	49U978
7 ft. 6"	2	5K® Snap Hook	Steel Swivel Snap Hook	400 lb	MFLTC-1/7.5FT	49U979
<b>Turbolite™ Extreme</b>						
6 ft.	1	Steel Snap Hook	Aluminum Carabiner	420 lb	MFLC-3/6FT	53CV22
9 ft.	1	Steel Snap Hook	Steel Snap Hook	420 lb	MFLC-3/9FT	53CV23
9 ft.	2	Steel Rebar Hook	Aluminum Carabiner	420 lb	MFLC2-4/9FT	53CV26
<b>Turbolite™ Max</b>						
9 ft.	1	Steel Snap Hook	Aluminum Carabiner	420 lb	MFLW-3/9FT	53CV31
6 ft.	2	Aluminum Rebar Hook	Steel Swivel Snap Hook	420 lb	MFLW2-12/6FT	53CV36
9 ft.	2	Aluminum Rebar Hook	Steel Swivel Snap Hook	420 lb	MFLW2-12/9FT	53CV37