





Hardwired 45TT72

Hardwired 2FTP5



10 Year Sealed Battery 1RK40





10 Year Sealed **Battery** 48TD27



**Battery** 5TR37

## BRK Kidde FIREX

# Combination Carbon Monoxide Detectors

■ Volume Level: 85 dB @ 10 ft

Carbon monoxide (CO) and smoke detectors sound an alarm when high concentrations of CO or smoke are detected in the air. Combination units require less space to install and reduce the number of units that need to be installed, maintained, and tested.

Carbon monoxide (CO) and gas detectors sound an alarm when CO or explosive gases such as methane and propane are detected in the air. Units are installed near the floor as explosive gases are heavier than air and settle at floor level.

Battery Backup	Interconnectivity	Sensor Type	Tamper Proof	Features	Brand	Item No.
	Sealed Battery					
Smoke/C	O Detector					
No	None	Electrochemical, Photoelectric	Yes	Test Button; Hush Button	First Alert	45TT70
Removab	le Battery					
No	Up to 18 Units	Photoelectric	Yes	Voice Alert; Test Button; Hust Button	First Alert	48Z670
Hardwire	d					
Explosive	Gas/CO Detector					
Yes	None	Electrochemical	No	LCD Display; Front Loading Battery; Test Button; H	First Alert	402G02
Smoke/C	O Detector					
Yes	None	Photoelectric	Yes	Voice Alert	First Alert	45TT83
Yes	Up to 18 Units	Electrochemical, Ionization	Yes	Side Loading Battery; Hush Button; Test Button	First Alert	45TT72
Yes	Up to 18 Units	Photoelectric	Yes	Voice Alert; Side Loading Battery; Hush Button; Te	BRK	2FTP5
Yes	Up to 24 Units	Electrochemical, Photoelectric	No	Voice Alert; Test Button; Hust Button	Kidde	446G62
10 Year S	Sealed Battery					
Explosive	Gas/CO Detector					
No	None	Electrochemical	No	LCD Display; Test Button; Hush Button	Kidde	1RK40
Smoke/C	O Detector					
No	None	Electrochemical, Ionization	No	Voice Alert; Test Button; Hust Button	Kidde	48TD27
No	None	Electrochemical, Photoelectric	Yes	Slim Profile; Test Button; Hush Button	First Alert	402G03
Removab	le Battery					
No	None	Electrochemical, Ionization	Yes		Kidde	5TR37
No	None	Electrochemical, Ionization	No	Front Loading Battery; Test Button; Hush Button	Kidde	20JK15
No	None	Electrochemical, Ionization	No		Kidde	48TD32
No	None	Electrochemical, Photoelectric	Yes	Slim Profile; Test Button; Hush Button	First Alert	45TT79
No	None	Electrochemical, Photoelectric	Yes	Front Loading Battery; Hush Button; Test Button	Firex	5MPL0
No	Up to 12 Units	Photoelectric	Yes	Side Loading Battery; Hush Button; Test Button	First Alert	45TT76
No	Up to 18 Units	Photoelectric	Yes	Voice Alert; Front Loading Battery	First Alert	45TT82



#### **Heat Detectors**

■ Volume Level: 85 dB @ 10 ft

Detectors sound a warning when high heat or fast increases in air temperature have been detected. They're often used in kitchens, attics, and boiler rooms where the presence of smoke can cause false alarms in normal operation.



20JK13

Battery Backup Hardwired	Interconnectivity	Sensor Type	Tamper Proof	Features	Brand	Item No.
Yes	Up to 18 Units	Thermistor	Yes	Side Loading Battery; Hush Button; Test Button	BRK	2FTN6
Removable Battery						
No	Up to 18 Units	Thermistor	Yes	Test Button	Kidde	20JK13









1762

### **Smoke Detector Testing Equipment**

Equipment includes items required to test smoke or carbon monoxide detectors to ensure they're in good working order. Local fire codes often require units to be tested on a regular basis.

Product Type	No.
CO Detector Test	36JG34
Smoke Detector Aerosol Tester Equipment	36JG31
Smoke Detector Tester	36JG35
Smoke Detector Tester	36JG36
Starter Kit	36JG32



#### First Alert

#### **Strobe Light for Smoke & Carbon Monoxide Detectors**

Strobe light works with carbon monoxide (CO) and smoke detectors to alert workers who are hearing impaired or are working in loud areas where an audible signal might not be heard.

Power Source	Backup	Interconnectivity	No.
Hardwired	No	Up to 18 Units	429J53







### **Interconnection Relays**

Relays automate tasks such as activating strobe lights, closing doors, or switching off HVAC systems when a detector is triggered.

D.
J39
N7
155