



Antislip Tape and Treads Definitions

Heavy—Has a very coarse (8-49 Grit) mineral-coated abrasive backing that is designed to handle heavy foot and equipment traffic. This durable, high-friction tape is used in muddy, greasy, and oily conditions such as on construction and farm equipment.

Medium—Tape offers a coarse (50-60 Grit) mineral-coated abrasive backing for general purpose use in medium traffic areas. This tape is recommended for flat surfaces, steps, and ramps where the traffic is less rigorous.

Light—Includes a fine (61-80 Grit) mineral-coated abrasive backing for use in light traffic areas. This tape is recommended for flat surfaces and ramps, such as entrances and exits, where some degree of friction is needed.

Wet & Barefoot—Tape has a non-abrasive (No Grit) textured surface designed for barefoot traffic in wet environments. It provides extra protection from slips and falls in areas where footwear is not worn such as around swimming pools, in showers, locker rooms, and on boat surfaces.



Antislip Tape



Continuous rolls of antislip tape prevent slips, trips, and falls, and allow for customization in cutting tape lengths to fit the surface area needed. The level of traffic determines the tape durability and grit level needed on the tape's abrasive backing. All tape is for use in both indoor and outdoor applications.



Wet & Barefoot, Solid 21YT67

Imperial Tape WxL	Tape Thickness	Grit Size	Adhesive Material	Performance Temp. Range	Brand	Item No.
Heavy Traffic, Very Coarse Abrasive						
Solid, Black						
1 in x 60 ft	41 mil		Rubber	-20°F to 175°F	Condor	1AJF5
2 in x 60 ft	41 mil		Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D73
2 in x 30 ft	41 mil	46	Rubber	-20°F to 175°F	Condor	1AJF6
4 in x 60 ft	41 mil		Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D74
4 in x 30 ft	41 mil		Rubber	-20°F to 175°F	Condor	1AJF7
4 in x 30 ft	42 mil		Acrylic	-40°F to 220°F	Wooster Flex-Tred	12E916
6 in x 60 ft	6.7 mil	24	Rubber	40°F to 175°F	3M Safety Walk	21C25
6 in x 60 ft	41 mil	46	Rubber	-20°F to 175°F	Condor	12E852
6 in x 60 ft	41 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	12E913
6 in x 30 ft	6.7 mil	24	Rubber	40°F to 175°F	3M Safety Walk	21DA5
12 in x 60 ft	41 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D70
12 in x 30 ft	53 mil	36	Acrylic	-40°F to 220°F	Wooster Flex-Tred	12E877
24 in x 30 ft	42 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D72
Striped, Black/Yellow						
3 in x 60 ft	36 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D83
Message—Caution Watch Your Step, Black/Yellow						
3 in x 60 ft	36 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D67
Medium Traffic, Coarse Abrasive						
Solid, Black						
1 in x 60 ft	30 mil		Rubber			6BV13
2 in x 60 ft	30 mil		Rubber			5AN34
2 in x 60 ft	36 mil		Rubber			6BV21
4 in x 60 ft	30 mil		Rubber			6AD55
4 in x 60 ft	36 mil	60	Rubber	40°F to 175°F	3M Safety Walk	6BV22
6 in x 60 ft	28 mil		Rubber			3AH44
6 in x 60 ft	36 mil		Rubber			6BV23
12 in x 60 ft	30 mil		Rubber			6BV14
18 in x 60 ft	28 mil		Rubber			21YT73
Solid, Clear						
4 in x 60 ft	33 mil	60	Acrylic	-20°F to 150°F	—	12E792
Solid, Yellow						
1 in x 60 ft	29 mil		Rubber	40°F to 150°F	3M Safety Walk	35XN36
1 in x 60 ft	32 mil		Rubber	-40°F to 150°F	—	6BV15
2 in x 60 ft	33 mil	60	Acrylic	-20°F to 150°F	—	448K75
2 in x 60 ft	36 mil		Rubber	40°F to 175°F	—	21YT79
4 in x 60 ft	30 mil		Rubber	-40°F to 150°F	3M Safety Walk	6BV16
4 in x 60 ft	36 mil		Rubber	40°F to 175°F	—	35XN38
Striped, Black/Yellow						
1 in x 60 ft	32 mil		Acrylic			32G31
1 in x 60 ft	32 mil		Acrylic			32G32
3 in x 60 ft	32 mil	60	Acrylic	-20°F to 150°F	Condor	32G33
4 in x 60 ft	32 mil		Acrylic			12E797
6 in x 60 ft	32 mil		Acrylic			12E813
12 in x 60 ft	32 mil		Acrylic			12E838
Light Traffic, Fine Abrasive						
Solid, Black						
3 in x 60 ft	28 mil		Rubber			12E782
4 in x 60 ft	28 mil		Rubber			12E850
6 in x 60 ft	28 mil		Rubber		Condor	6U953
8 in x 60 ft	28 mil		Rubber	-20°F to 175°F	—	12E830
12 in x 60 ft	28 mil		Rubber		—	448K76
24 in x 60 ft	28 mil		Rubber		Condor	12E842
Wet and Barefoot Traffic, Non-Abrasive						
Solid, Black						
1 in x 60 ft	45 mil		Rubber			21YT69
2 in x 60 ft	45 mil		Rubber	40°F to 175°F	3M Safety Walk	6BV25
4 in x 60 ft	45 mil		Rubber			6BV26
6 in x 60 ft	45 mil		Rubber			6BV27
12 in x 60 ft	29 mil		Acrylic	-20°F to 220°F	—	12E869
Solid, Gray						
1 in x 60 ft	45 mil		Rubber			21YT67
2 in x 60 ft	45 mil		Proprietary	40°F to 175°F	3M Safety Walk	6BV30
4 in x 60 ft	45 mil		Rubber			6BV29



Antislip Tape Treads

Tape treads prevent slips, trips, and falls and allow for uniform placement on surfaces. The level of traffic determines the tape durability and grit level needed on the tread's abrasive backing. 12E817 glows in the dark. All treads are for use in both indoor and outdoor applications, except 3EYK4 and 3EYK7 are for indoor use only.

Imperial Tape WxL	Tape Thickness	Grit Size	Adhesive Material	Performance Temp. Range	Brand	Item No.	Pkg. Qty.
Heavy Traffic, Very Coarse Abrasive							
Solid, Black							
3 in x 24 in	42 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	12E940	50
3 in x 24 in	46.9 mil	20 to 40	Rubber		Sure-Foot Master Stop	31AP77	12
3 in x 24 in	109.4 mil	10 to 20	Rubber		3M Safety Walk	31AP62	24
6 in x 24 in	6.7 mil	24	Rubber	40°F to 175°F	3M Safety Walk	21DA9	25
6 in x 24 in	41 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D76	10
6 in x 24 in	41 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D75	50
6 in x 24 in	41 mil	46	Rubber	-20°F to 175°F	—	12E854	25
6 in x 24 in	41 mil	46	Rubber	-20°F to 175°F	—	12E853	50
6 in x 24 in	52 mil	46	Acrylic	-20°F to 150°F	—	12E827	10
6 in x 24 in	54 mil	20	Acrylic	-10°F to 210°F	Military Grade Flex-Tred	53XX14	50
6 in x 24 in	46.9 mil	10 to 20	Rubber	-40°F to 220°F	Sure-Foot Master Stop	31AP66	24
12 in x 48 in	34 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D81	1
Solid, Clear							
3 in x 24 in	44 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D88	10
Solid, Gray							
3 in x 24 in	38 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D68	50
Solid, White							
3/4 in x 12 in	37 mil	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	452D77	400
Striped, Black/Yellow							
6 in x 24 in	—	46	Acrylic	-40°F to 220°F	Wooster Flex-Tred	1AJZ1	10
Medium Traffic, Coarse Abrasive							
Solid, Black							
3/4 in x 24 in	28 mil	60	Rubber		3M Safety Walk	2JFK6	50
3/4 in x 24 in	28 mil	60	Rubber		Ability One SKILCRAFT	52CA61	50
5 1/2 in x 5 1/2 in	28 mil	60	Rubber		3M Safety Walk	2JCZ8	50
6 in x 24 in	28 mil	60	Rubber	40°F to 175°F	Ability One SKILCRAFT	52CA63	50
6 in x 24 in	30 mil	60	Rubber		3M Safety Walk	5AN41	50
6 in x 24 in	36 mil	60	Rubber		Ability One SKILCRAFT	52CA80	50
6 in x 24 in	36 mil	60	Rubber		3M Safety Walk	6BV20	50
6 in x 24 in	42 mil	60	Acrylic	-20°F to 220°F	—	3EYH1	10
6 in x 24 in	80 mil	60	Rubber	40°F to 175°F	Ability One SKILCRAFT	5MM74	1
Solid, Clear							
6 in x 24 in	35 mil	60	Rubber	40°F to 150°F	3M Safety Walk	54DF21	50
Solid, White							
6 in x 24 in	28 mil	50	Acrylic	-20°F to 150°F	Condor	4HY92	10
Solid, Yellow							
6 in x 24 in	33 mil	60	Acrylic	-20°F to 150°F	Condor	12F876	10
6 in x 24 in	33 mil	60	Acrylic	-20°F to 150°F	—	12E821	50
Striped, Black/Yellow							
6 in x 24 in	32 mil	60	Acrylic	-20°F to 150°F	Condor	12E824	10
6 in x 24 in	36 mil	60	Rubber	40°F to 150°F	3M Safety Walk	54DF11	50
Message—Caution, Black/Yellow							
6 in x 24 in	32 mil	60	Acrylic	-20°F to 150°F	—	448K62	10
6 in x 24 in	32 mil	60	Acrylic	-20°F to 150°F	—	12E825	24
Message—Watch Your Step, Black/Yellow							
6 in x 24 in	32 mil	60	Acrylic	-20°F to 150°F	Condor	12E826	24
Light Traffic, Fine Abrasive							
Solid, Black							
6 in x 24 in	28 mil	80	Rubber	-20°F to 175°F	Condor	4T628	50
2 in x 24 in	28 mil	80	Rubber	-20°F to 200°F	—	12E773	50
Striped, Black							
6 in x 24 in	28 mil	80	Rubber	-20°F to 175°F	—	12E817	24
Wet and Barefoot Traffic, Non-Abrasive							
Solid, Black							
6 in x 24 in	45 mil	Proprietary	Rubber	40°F to 175°F	3M Safety Walk	2JDC5	50
4 in x 16 5/8 in	12.7 mil	20	Rubber	Not Rated	—	448K72	1
Solid, White							
3/4 in x 7 1/2 in	27 mil	Proprietary	Acrylic	-20°F to 220°F	Condor	3EYK7	12
3/4 in x 17 in	23 mil	Proprietary	Acrylic	50°F to 175°F	3M Safety Walk	6BT82	50
16 in x 33 1/2 in	27 mil	Proprietary	Acrylic	-20°F to 220°F	Condor	3EYK4	1