



**Self-Powered
6NVN9**



**Battery-Powered
2ZU99**

Keying	D (in.)	W (in.)	Mfr. Model	Item No.
PowerPlex Self-Powered				
Schlage C	3 3/16	3 3/16	P2031XSSL62641	6NVN9
Best & Equivalents	3 3/16	3 3/16	P2031BLL62641	6NVPO
Battery-Powered				
Schlage C	2 13/16	3 3/16	E2031XSSL62641	2ZU99
Best & Equivalents	2 13/16	3 3/16	E2031BLL62641	1NEZ7

2000 Series, Grade 1 Electronic Push-Button Locks

- 100 individual user codes
- For 1 3/8" - to 2 1/2" - thick doors; 2 3/4" backset

No battery to install. Nonhanded, field-reversible locks have a vandal-resistant, all-metal keypad and a solid cast exterior housing and lever. Classroom/storeroom function; no code required for egress. Come with a standard core or are prepped for a SFIC cylinder (not included). Include lock assembly, installation manual, template, reference guide, operations manual, and hardware. Retrofit standard ASA 161 door preps.

PowerPlex Self-Powered—Efficient and innovative electronic locks generate power with each turn of the lever; no batteries required and virtually no maintenance costs. 6NVN9 includes Schlage C keyway, 2 keys. 6NVPO is for use with Best SFIC 6- or 7-pin length, not included.

Battery-Powered—Feature audible low battery alert, timed relock, codes for 1-time use, antitamper function (invalid entry), and total user lockout codes. Include 3 AA batteries.

E-PLEX
BY KABA



**5000 Series
Key-In Lever,
Grade 1,
Chrome**



**L1000
Series Lever,
Standard,
Chrome**



**1000 Series
Knob,
Standard,
Chrome**

Protective keypad covers available, see page 1907.

Description	Keying	Hand	SATIN CHROME		ANTIQUE BRASS	
			Mfr. Model	Item No.	Mfr. Model	Item No.
Programmable Locks, Push-Button, Grade 1 (5000 Series)						
Lever	KIL	Reversible	5021-XS-WL-26D-41	2ZU95	—	—
Lever	SFIC	Reversible	5021-B-WL-26D-41	5BB73 *	—	—
Exit Trim, Lever	KIL	Reversible	5010-XS-WL-26D-41	2ZV18	—	—
Programmable Locks, Push-Button (L1000 Series)						
Lever	Standard	Left	LL-1011-26D-41	5U740	LL-1011-05-41	5U739
Lever	Standard	Right	LR-1011-26D-41	5U742	LR-1011-05-41	5U741
Lever	SFIC	Left	LL-1021-B-26D-41	4YF90 *	LL-1021-B-05-41	4YF89 *
Lever	SFIC	Right	LR-1021-B-26D-41	4YF92 *	LR-1021-B-05-41	4YF91 *
Knob	Standard	Reversible	1011-26D-41	1U140	1011-05-41	1U092
Lever	KIL	Reversible	5021XKWL26D41	9LDD6	—	—
Knob	SFIC	Reversible	1021-B-26D-41	4YF88 *	1021-B-05-41	4YF87 *
Knob, Passage	Standard	Reversible	1031-26D-41	1U141	1031-05-41	1U083
Mechanical Push Button Lockset						
Knob	Combination Access	Reversible	EE11/1126D41	31NG48	—	—
Lever	R/C Schlage	Left	LL1021S26D41	31NG77	—	—
Lever	R/C Schlage	Right	LR1021S26D41	31NG80	—	—

* Cylinders not included.

SIMPLEX
BY KABA

Mechanical Access Control Push-Button Locks

- 1 user code
- For 1 3/8" - to 2 1/4" - thick doors; 2 3/4" backset, 1/2" latch bolt
- Include ASA standard strikes

Provide an alternative to traditional keyed locksets. Classroom/storeroom function, no code required for egress. Retrofit standard ASA 161 door preps.

PROGRAMMABLE LOCKS, PUSH-BUTTON, GRADE 1 (5000 SERIES)

Standard KIL core included. Simple 4-screw installation. Compatible with most rim exit devices.

PROGRAMMABLE LOCKS, PUSH-BUTTON (L1000 SERIES)

Measure 9"L (inside) x 3 1/8"W x 3 3/16"D.



**Lever
Lockset**



**Knob
Lockset**

Mechanical Access Control Locks

SIMPLEX
BY KABA

- 1 user code
- For 1 3/8" - to 2 1/2" - thick doors
- 2 cover plates included with each lock
- Satin Stainless Finish

Vandal-resistant, all-metal keypad. Nonhanded, field reversible. Lever locksets are 7 1/16"L x 2 1/4"W x 3"D. Breakaway lever helps keep vandals from damaging drive components. Knob locksets are 6 1/16"L x 2 3/16"W x 3"D. No batteries required.

Description	CHOOSE: Backset	Item No.
Lever Lockset	2 3/8 in, 2 3/4 in	D0001
Knob Lockset	2 3/8 in, 2 3/4 in	D0002



With Deadlocking Latch

900 Mechanical Access Control

SIMPLEX
BY KABA

- 1 user code
- 2 1/2" backset

Classroom/storeroom function, no code required for exit. Nonhanded, field reversible. No batteries required. Can be used alone or with an existing lockset. Require a 1 3/8"-dia. mounting hole. Measure 4"W x 5"H.

Note: All locks include a sheet metal strike for outswung doors and a cast box strike for inswing wood frame installation.

With Deadbolt—Deadbolt extends 1" from edge of door. Lock remains open and must be manually relocked. Egress by thumbturn.

With Deadlocking Latch and Holdback

Helps secure latch against prying. Automatically relocks after egress, except when latch hold-back is activated. No code is required for entry. Exit by thumbturn.

With Deadlocking Latch, No Hold-Back

Helps secure latch against prying. Automatically relocks after egress.

Metal Frame Adapter Kit—Includes surface-mounted strike with shims to adjust strike box. With 1/4" x 3/8" reversible riser plate for aligning inside housing to strike.

CHOOSE: Door Thickness	CHOOSE: Finish	Item No.
With Deadbolt		
1 3/8 to 1 1/2, 1 3/4 to 2 1/8	Satin Brass, Satin Chrome	D0003
With Deadlocking Latch and Holdback		
1 3/8 to 1 1/2, 1 3/4 to 2 1/8	Satin Brass, Satin Chrome	D0004
With Deadlocking Latch, No Hold-Back		
1 3/8 to 1 1/2, 1 3/4 to 2 1/8	Satin Brass, Satin Chrome	D0005
Metal Frame Adapter Kit	Satin Brass, Satin Chrome	D0006