Surface-Mount Hinges without Holes

Have at least 270° range of motion

Reversible hinges are mounted by welding or drilling holes for fasteners. Nonremovable pin provides increased security.

Door Leaf Height	Door Leaf Width	Door Leaf Thickness	Pin Dia.	ltem No.	Door Leaf Height	Door Leaf Width	Door Leaf Thickness	Pin Dia.
	d Steel, Non	-Removable	Pin		Zinc Stee	I, Non-Remo	vable Brass	Pin
1 in	³¹ /32 in	0.047 in	7⁄64 in	3HTE3	4 in	4 in	0.18 in	5∕16 in
2 in	1 ½ in	0.06 in	1⁄8 in	3HTE6	4 in	4 in	0.25 in	1⁄2 in
2 in	2 in	0.099 in	—	4PA65		Steel, Nonre		
2 1/2 in	2 ½ in	0.11 in	%16 in	4PA66	1 ½ in	1 ½ in	0.05 in	¹∕₀ in
3 in	2 ½ in	0.12 in	1⁄4 in	3HTF2	2 in	1 ½ in	0.06 in	¹∕≋ in
3 in	3 in	0.11 in	—	4PA67	2 1/2 in	2 1/2 in	0.075 in	3∕16 in
4 in	3 ½ in	0.165 in	5∕16 in	3HTF4	3 in	1 in	0.09 in	3∕16 in
4 in	4 in	0.139 in	—	4PA69	3 in	3 in	0.12 in	1⁄4 in
4 in	4 in	0.25 in	5∕s in	3HTF6	3 ½ in	3 in	0.09 in	3⁄16 in
5 in	5 in	0.165 in	—	4PA71	3 ½ in	3 ½ in	0.09 in	³∕16 in
6 in	5 in	0.18 in	3⁄8 in	3HTG3	4 in	4 in	0.25 in	5∕s in
6 in	6 in	0.187 in	—	4PA72	5 in	5 in	0.12 in	1⁄4 in
8 in	6 in	0.18 in	3% in	3HTG7	5 in	5 in	0.18 in	⅔ in
	d Steel, Ren				Stainless Steel, Removable Pin			
2 1/2 in	2 1/2 in	0.12 in		3HTH3	2 ½ in	2 1/2 in	0.075 in	3⁄16 in
6 in	3 in	0.18 in	3% in	3HTK1	4 in	3 in	0.12 in	1⁄4 in
6 in	6 in	0.18 in	3∕s in	3HTK3				
	nel Steel, No							
2 in	2 in	0.105 in	³∕16 in	3HTP1				
3 ½ in	3 ½ in	0.165 in	5∕16 in	3HTP4				

Nontemplate Mortise-Mount Hinges

= 270° range of motion.

Reversible nontemplate hinges have nonstandard hole patterns, providing flexibility as older/stripped holes can be ignored when mounting new hinges. Hinges mount into recessed cutouts, attaching hollow metal or wood doors to frames. Holes are predrilled and countersunk for easy installation and better corrosion resistance.

Door Leaf Height	Door Leaf Width	Door Leaf Thickness	Pin Dia.	Holes	ltem No.			
			Dia.	per Leaf	NU.			
	Gray Enamel Steel, Non-Removable Pin Square Corners, 3 Knuckle							
1 ½ in	1 % in	0.05 in	1/8 in	2	3HTU4			
Square Corners, 5 Knuckle								
2 in	1 %16 in	0.05 in	1/8 in	2	3HTU6			
2 in	2 in	0.08 in	3/16 in	2	3HTU7			
3 in	2 in	0.062 in	5⁄32 in	3	3HTV1			
3 in	3 in	0.09 in	17/64 in	3	3HTV2			
4 in	4 in	0.11 in	17/64 in	4	3HTV4			
6 in	6 in	0.16 in	3/8 in	5	3HTV5			
Gray Enamel Steel	Removable Pin							
Square Corners, 5 Knuckle								
2 1/2 in	2 1/2 in	0.09 in	7⁄32 in	3	3HTW7			
3 in	2 in	0.062 in	5⁄32 in	3	3HTW8			
3 in	3 in	0.09 in	17/64 in	3	3HTW9			
3 1/2 in	3 1/2 in	0.11 in	17/64 in	3	3HTX1			
Zinc-Plated Steel. Removable Pin								
Square Corners, 5	Knuckle							
3 1/2 in	3 1/2 in	0.11 in	17/64 in	3	3HTY1			
3 in	3 in	0.09 in	17⁄64 in	3	3HTX9			

Spring Hinges

Hardware included Ensure doors close automatically.

Door Leaf Height	Door Leaf Width	Finish	Door Leaf Thickness	Holes per Leaf	Brand	ltem No.	
Adjustable-1		Vood Storm Door Sp		eel. Plated	Finish, Fu		
4 ½ in	2 in	Gray Enamel	0.098 in	4		1CAC4	
Adjustable E	Ball Bearings Do	ouble-Acting Floor	Spring Hinge Se	t. Steel. P	ated Finis	1	
1 in	9 13/16 in	Satin Bronze	0.099 in	4	_	4PB50	
Adjustable-	Cension Heavy	Vood Storm Door Sp	ring Hinges, St	eel. Plated	Finish. Fu	II Mortise	
2 55/64 in	1 ¹⁵ / ₃₂ in	Bright Zinc	0.08 in	3	_	4PA75	
Adjustable-1	Tension Wood S	torm Door Spring Hi	inges, Steel, Pl	ated Finish	1		
2 ¾ in	1 ¹⁵ / ₃₂ in	Black Enamel	0.045 in	3	_	1RBU7 *	
2 3⁄4 in	1 ¹⁵ / ₃₂ in	Steel	0.08 in	3	_	1RBV1	
2 3⁄4 in	1 15/32 in	Bright Zinc	0.048 in	3	_	4PA74	
Full Mortise		ing Residential Hin	ges, ¼" Radius				
3 ½ in	1 3⁄4 in	Satin Brass	0.099 in	3	_	4PA90	
3 ½ in	1 ¾ in	Satin Chrome	0.099 in	3	_	4PA91	
4 in	2 in	Satin Brass	0.099 in	4	_	4PA92	
4 in	2 in	Satin Chrome	0.099 in	4	_	4PA93	
	Adjustable Spr	ing Residential Hin					
3 ½ in	1 ³ ⁄ ₄ in	Satin Brass	0.099 in	3	_	4PA94	
4 in	2 in	Satin Brass	0.099 in	4	_	4PA95	
		ing Residential Hin					
3 ½ in	1 ³ ⁄ ₄ in	Satin Brass	0.099 in	3	_	4PA76	
3 1⁄2 in	1 ¾ in	Satin Chrome	0.099 in	3	_	4PA77	
4 1/2 in	2 in	Satin Brass	0.134 in	4	_	1RBV3	
4 ½ in	2 in	White Enamel	0.134 in	4	_	4PA81	
4 1⁄2 in	2 in	Satin Chrome	0.134 in	4	_	4PA82	
4 1/2 in	2 1/4 in	Satin Brass	0.134 in	4	_	4PA84	
4 ½ in	2 ¼ in	Bronze	0.134 in	4	_	4PA85	
4 1⁄2 in	2 1/4 in	Satin Chrome	0.134 in	4	_	4PA86	
4 1/2 in	2 1/4 in	Bright Brass	0.134 in	4	_	4PA87	
4 ½ in	2 ¼ in	Satin Bronze	0.134 in	4	_	4PA88	
4 in	2 in	Satin Brass	0.099 in	4	_	4PA78	
4 in	2 in	Satin Chrome	0.099 in	4	_	4PA79	
4 in	2 in	Stainless Steel	0.099 in	4		4PA80	
TRU CLOSE® Heavy Duty Self-Closing Adjustable Spring Hinge							
4 ¾ in	1 3/8 in	Black Matte	0.39 in	2	TruClose	38G646	
	Self-Closing A	djustable Spring Hi	nge		-		
3 ¾ in	1 1/8 in	Black Matte	0.35 in	2	TruClose	38G643	
* Pkn of 2							



Item No. 3HTP7 3HTP8 3HTK5

3HTK5 3HTK6 3HTL1 3HTL2 3HTL5

3HTL6 3HTL7 3AGC3 3AGC4 3AGC5 3HTN2 3HTN6





3HTN2

3AGC3



3HTU4

3HTV1



знтхэ



1CAC4



4**P**A75

4PA74



4**PA**94





4PA86



38G643

Pkg. of 2.

Sign in to Grainger.com® to see YOUR Pricing and MORE

D TRUCIOSE

SECURITY Hinges