



Flat Head



Hex Nut



Acorn Nut



Round Head



Sleeve Anchors

Filler sleeve eliminates galling between sleeve and tapered bolt head. For concrete, hollow or shallow masonry, or grout-filled blocks. Include nut and washer. Red Head Meet U.S. Government A-A-1922A standard.

Anchor Dia.	Anchor Length	Min. Embedment	Max. Work Thickness	Ultimate Shear in 4000 psi Concrete (lb.)	Ultimate Tension in 4000 psi Concrete (lb.)	Anchor Material	Brand	Item No.	Pkg. Qty.
Flat Head Phillips									
3/8 in	2 1/4 in	1 1/4 in	1 1/2 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK56	25
	4 in	1 1/2 in	2 1/2 in	3,040 lb	3,100 lb	Steel	Red Head	3A489	50
	4 in	1 1/4 in	2 3/4 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK57	25
	5 in	1 1/2 in	3 1/2 in	3,040 lb	3,100 lb	Steel	Red Head	3A490	50
	5 in	1 1/4 in	3 3/4 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK58	10
	6 in	1 1/4 in	4 3/4 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK59	10
Flat Head Slotted									
1/4 in	1 1/2 in	1 in	1/2 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK53	50
	2 in	1 in	1 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK54	50
	3 in	1 in	2 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK55	50
3/8 in	4 in	1 1/4 in	2 3/4 in	2,020 lb	2,960 lb	SS	MKT Fastening	30PK74	5
Hex Nut									
5/16 in	1 1/2 in	1 1/4 in	1/2 in	2,400 lb	2,600 lb	Steel	Red Head	3A472	100
	1 1/2 in	1 3/8 in	3/8 in	1,600 lb	1,900 lb	Steel	MKT Fastening	30PK38	50
	1 1/2 in	1 1/8 in	3/8 in	1,600 lb	1,900 lb	SS	MKT Fastening	30PK65	10
	2 1/2 in	1 3/8 in	1 3/8 in	1,600 lb	1,900 lb	Steel	MKT Fastening	30PK39	50
	2 1/2 in	1 1/8 in	1 3/8 in	1,600 lb	1,900 lb	SS	MKT Fastening	30PK66	10
	1 1/8 in	1 1/2 in	3/8 in	3,040 lb	3,100 lb	Steel	Red Head	3A474	50
3/8 in	1 1/8 in	1 1/4 in	3/8 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK40	25
	1 1/8 in	1 1/4 in	3/8 in	2,020 lb	2,960 lb	SS	MKT Fastening	30PK67	5
	3 in	1 1/2 in	1 1/2 in	3,040 lb	3,100 lb	Steel	Red Head	3A475	50
	3 in	1 1/4 in	1 3/4 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK41	25
	3 in	1 1/4 in	1 3/4 in	2,020 lb	2,960 lb	SS	MKT Fastening	30PK68	5
	2 1/4 in	1 1/8 in	3/8 in	5,000 lb	4,400 lb	Steel	Red Head	3A476	25
1/2 in	2 1/4 in	1 1/2 in	3/4 in	5,760 lb	4,860 lb	Steel	MKT Fastening	30PK42	10
	2 1/4 in	1 1/2 in	3/4 in	5,760 lb	4,860 lb	SS	MKT Fastening	30PK69	5
	3 in	1 1/8 in	1 1/8 in	5,000 lb	4,400 lb	Steel	Red Head	3A477	25
	3 in	1 1/2 in	1 1/2 in	5,760 lb	4,860 lb	Steel	MKT Fastening	30PK43	10
	3 in	1 1/2 in	—	—	—	SS	DeWalt	30RZ75	25
	4 in	1 1/8 in	2 1/8 in	5,000 lb	4,400 lb	Steel	Red Head	3A478	25
5/8 in	4 in	1 1/2 in	2 1/2 in	5,760 lb	4,860 lb	Steel	MKT Fastening	30PK44	10
	4 in	1 1/2 in	2 1/2 in	5,760 lb	4,860 lb	SS	MKT Fastening	30PK70	5
	4 in	1 1/2 in	—	—	—	SS	—	31KL90	10
	6 in	1 1/2 in	4 1/2 in	5,760 lb	4,860 lb	Steel	MKT Fastening	30PK45	5
	3 in	2 in	1 in	7,880 lb	5,970 lb	Steel	MKT Fastening	30PK47	5
	4 1/4 in	2 in	2 1/4 in	8,080 lb	6,120 lb	Steel	Red Head	3A481	10
3/4 in	4 1/4 in	2 in	2 1/4 in	7,880 lb	5,970 lb	Steel	MKT Fastening	30PK48	5
	6 in	2 in	4 in	7,880 lb	5,970 lb	Steel	MKT Fastening	30PK49	5
	2 1/2 in	2 in	1/2 in	11,620 lb	8,780 lb	Steel	MKT Fastening	30PK50	5
	2 1/2 in	2 in	1/2 in	11,620 lb	8,780 lb	SS	MKT Fastening	30PK72	5
	4 1/4 in	2 in	2 1/4 in	11,620 lb	8,780 lb	Steel	MKT Fastening	30PK51	5
	6 1/4 in	2 in	4 1/4 in	11,620 lb	8,780 lb	Steel	MKT Fastening	30PK52	5
Acorn Nut									
5/8 in	—	1/8 in	—	—	—	Steel	MKT Fastening	30PK35	100
1/4 in	1 3/8 in	1 in	3/8 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK36	50
	1 3/8 in	1 in	3/8 in	920 lb	1,400 lb	SS	MKT Fastening	30PK63	10
	2 1/4 in	1 in	1 1/4 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK37	50
	2 1/4 in	1 in	1 1/4 in	920 lb	1,400 lb	SS	MKT Fastening	30PK64	10
Round Head Slotted									
1/4 in	1 1/4 in	1 in	1/4 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK60	50
	2 in	1 in	1 in	920 lb	1,400 lb	Steel	MKT Fastening	30PK61	50
3/8 in	2 1/2 in	1 1/4 in	1 1/2 in	2,020 lb	2,960 lb	Steel	MKT Fastening	30PK62	25



Taper Bolt with Expansion Nut



Taper Bolt Expansion Anchors with Nuts

Removable, reusable bolts include a finished, low-profile hex head. High tensile strength allows users to substitute smaller bolts, for reduced cost. Uniform expansion provides greater strength and holding power.



Expansion Nut

Screw Size	Item No.	Pkg. Qty.
3/8 in	4KH8	100
1/2 in	4KH9	50
3/4 in	4KH2	50
1 in	4KH3	10

Anchor Dia.	Length	Ultimate Tension	Ultimate Shear	Min. Embedment	Item No.	Pkg. Qty.
MKT Fastening, Taper Bolt Anchor with Nut						
3/8 in	2 1/4 in	4,030 lb	7,177 lb	1 1/8 in	4KH9	50
3/8 in	3 in	4,030 lb	7,177 lb	1 1/8 in	4KH2	50
3/8 in	4 in	4,030 lb	7,177 lb	1 1/8 in	4KH3	50
1/2 in	2 in	8,165 lb	12,177 lb	2 3/8 in	4KH4	25
1/2 in	4 in	8,165 lb	12,177 lb	2 3/8 in	4KH5	25
1/2 in	5 in	8,165 lb	12,177 lb	2 3/8 in	4KH6	20
5/8 in	3 1/2 in	9,990 lb	17,030 lb	2 7/8 in	4KH7	20
5/8 in	4 1/2 in	9,990 lb	17,030 lb	2 7/8 in	4KH8	25
3/4 in	4 1/8 in	11,906 lb	27,916 lb	3 3/8 in	4KH2	20
3/4 in	5 1/2 in	11,906 lb	27,916 lb	3 3/8 in	4KH3	20
3/4 in	7 in	11,906 lb	27,916 lb	3 3/8 in	4KH4	15
3/4 in	8 in	11,906 lb	27,916 lb	3 3/8 in	4KH5	15
1 in	7 1/4 in	28,263 lb	36,257 lb	4 3/8 in	4KH7	10



Toggle Bolt Anchors with Pull Ring

• Grip range 3/8 to 3 3/8"

Thread Size	Drill Bit Size	UOM Qty	
		10 Item No.	100 Item No.
Steel			
#10-24	1/2 in	40P467	40P468
1/4"-20	3/8 in	40P469	40P470
5/16"-18	3/8 in	40P471	40P472
3/8"-16	3/4 in	40P473	40P474
1/2"-13	3/4 in	40P475	—
Stainless Steel			
3/8"-16	3/4 in	40P477	—
1/2"-13	3/4 in	40P479	—

DOWNLOAD the Grainger Mobile App!

- Easy Checkout
- Track Orders
- Create Location-Based Lists
- Search by Image

> To download the app, visit grainger.com/mobile



Apple, the Apple logo and iPhone are trademarks of Apple Inc. App Store is a service mark of Apple Inc. Google Play is a trademark of Google Inc.