



## Hammer-Drive Anchors and Pins

**Standard**—Easy-to-install, tamperproof anchors can be used in concrete, block, brick, or stone. Include hex nut and washer.

**Security Anchors**—Set flush in recessed washer to help prevent tampering and removal.

Anchor Dia.	Anchor Length	Min. Embedment	Max. Fixture Thickness	Item No.	Pkg. Qty.
<b>Standard, Zamac</b>					
3/16 in	3/8 in	3/8 in	1/4 in	11K340	100
	3/4 in	3/8 in	3/8 in	11K341	100
	1 in	3/4 in	3/4 in	11K342	100
1/4 in	1 1/4 in	3/4 in	1/2 in	11K343	100
	1 1/2 in	3/4 in	3/4 in	11K344	100
	2 in	3/4 in	1 1/4 in	11K345	100
<b>Standard, Steel</b>					
1/4 in	1 3/4 in	1 1/2 in	3/8 in	11K324	50
	2 3/8 in	1 1/2 in	1 in	11K325	50
3/8 in	2 in	1 3/8 in	3/8 in	11K326	25
	2 3/4 in	1 3/8 in	1 in	11K327	25
3/8 in	3 1/2 in	1 1/2 in	1 in	11K329	25
	4 3/4 in	1 3/4 in	2 5/8 in	11K330	25
1/2 in	2 3/4 in	2 in	1/4 in	11K331	10
	3 1/2 in	2 1/4 in	3/4 in	11K332	10
3/8 in	4 in	2 3/4 in	1 5/8 in	11K335	5
	6 in	2 3/4 in	2 in	11K336	5
3/4 in	5 in	3 1/2 in	2 in	11K337	4
	7 1/2 in	3 1/2 in	2 in	11K338	4
<b>Standard, Carbon Steel</b>					
3/8 in	2 3/8 in	1 3/8 in	3/8 in	11K328	25
	4 3/4 in	2 1/4 in	2 in	11K333	10
1/2 in	6 in	2 1/4 in	3 1/4 in	11K334	10
<b>Security Anchors, Carbon Steel Body (Hardened Pin)</b>					
1/4 in	1 3/4 in	1 in	1/2 in	15W081	10
	2 3/8 in	1 in	3/8 in	15W082	10
3/16 in	2 3/4 in	1 1/4 in	1 1/4 in	15W083	10
	2 3/8 in	1 1/2 in	3/8 in	15W084	10
3/8 in	3 1/2 in	1 1/2 in	1 3/4 in	15W085	5
	5 in	1 1/2 in	3 1/4 in	15W086	5
1/2 in	2 3/4 in	2 in	3/4 in	15W087	5
	3 1/2 in	2 in	1 1/2 in	15W088	5
3/4 in	4 3/4 in	2 in	2 3/4 in	15W089	5
	6 in	2 in	4 in	15W090	2
3/8 in	4 in	2 1/2 in	1 1/2 in	15W091	2
	6 in	2 1/2 in	3 1/2 in	15W092	2
3/4 in	5 in	3 in	2 1/4 in	15W093	2
	6 in	3 in	3 1/4 in	15W094	2



## Steel Toggle Bolts

Spring-type wing with combo head screw is easy-to-install. Use for light-duty applications such as block, drywall, hollow walls, ceiling, and steel construction.

Thread Size	Drill Size	Wing Span	Pkg. Qty.	2 in LENGTH Item No.	3 in LENGTH Item No.	4 in LENGTH Item No.	5 in LENGTH Item No.	6 in LENGTH Item No.
#6-32	1/2 in	1.5 in	50	11K301	11K302	11K303	—	—
#10-24	9/16 in	2 in	50	11K304	11K305	11K306	11K307	11K308
1/4"-20	1 1/8 in	2 in	50	—	11K309	11K310	11K311	11K312
3/8"-16	1 in	2.875 in	25	—	11K313	11K314	11K315	11K316



## Powder-Actuated Tool

For fast, secure fastening into steel, concrete, and masonry. Ergonomically designed for operator comfort and safety. Trigger-operated tool uses 10-load powder strips for efficient operation and has automatic powder load ejection and steel construction.

Description	Caliber	Tool Length (In)	Tool Weight (lb.)	Mfr. Model	Item No.
<b>Power-Actuated Tools</b>					
<b>Capacity 2 -1/2 in Pins and 3 in Pin with Washer</b>					
Semi-Automatic, 10 Load Strip	0.27	13 1/4 in	4.5 lb	COBRA	2HNW6
<b>Knurled Pins</b>					
1/2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
<b>Straight Pins</b>					
3/4 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 1/4 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 1/2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
2 1/2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
<b>Fastening Pins With 1" Washer</b>					
3/4 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 1/4 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
1 1/2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
2 1/2 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
3 in Length, 0.3 in Head Dia./0.145 in Shank Diameter					
<b>Powder Loads</b>					
0.27, Green, Fastening				3RS27	2HPA1 100
0.27, Yellow, Fastening				4RS27	2HPA2 100
0.27, Red, Fastening				5RS27	2HPA3 100

\* All pins are 1060-1065 steel with core hardness of 52-56 Rc.



**WINGITS**  
The Solutions Company

## Shower and Grab Bar Anchors

**Shower Rod Anchor**—Use with crescent and oval curved shower rods when there is insufficient structural blocking. Installs quickly into any hollow wall substrate up to 1 1/4" thick. Made of fire-retardant plastic material. Includes 4 stainless steel screws, 4 wings, and waterproof adhesive tape.

**Grab Bar Anchors**—Watertight installation eliminates blocking, even over grout lines in drywall with tile. 6UTC8 is rated up to 600 lb. and 6UTC7 is rated up to 800 lb. Each includes stainless steel screws. Meet ADA guidelines and commercial building codes. Installation into bare 1/2" drywall is not compliant with commercial building codes.

**Wall and Tile Drill Bits and Sets**—Precision bits cut fast, clean holes to install anchors in ceramic wall tile, wallboard, glass, steel, marble, and plaster. Made of industrial carbide.



Material	Item No.	Pkg. Qty.
<b>Shower Rod Anchor</b>		
Plastic	6UTD3	2
<b>Grab Bar Anchors</b>		
Stainless Steel	6UTC7	2
Plastic	6UTC8	2
<b>Wall and Tile Drill Bits and Sets</b>		
1/4 in, 3/8 in, 1 1/4 in	6UTD1	1
1/4 in, 1/2 in, 3/4 in, 1 in, 1 1/4 in	6UTD2	1
1 1/2 in	6UTD0	1
<b>Straight Shank</b>		
3/4 in	6UTC9	1