



## Kitchen and Bathroom Sealants and Caulks

Note: See corresponding caulk guns on page 2129.

### DAP

#### 100% Silicone Sealant

One-component, acetoxycure material. Provides a durable, watertight seal that won't crack or shrink. It offers long-lasting flexibility and is safe for incidental food contact. Cured sealant is mildew resistant.

#### Kitchen, Bath, and Plumbing High-Performance Sealant

Kwik Dry formula is paintable and water-resistant in 1/2 hr. Waterproof seal with Microban protects against mold and mildew up to 10 yr.

#### Kitchen and Bath Sealant with Microban

Antimicrobial protection fights mold, mildew, odors, and stains. Kwik Seal Plus formula provides a watertight seal with maximum adhesion and flexibility.

#### KWIK SEAL Kitchen and Bath Adhesive Caulk

Acrylic formula is mold- and mildew-resistant. Dries tack-free in 15 min. Resists cracking, crumbling, and shrinking.

#### Phenoseal Adhesive Caulk

Mildew-resistant and watertight seal. Water cleanup.

#### Premium Kitchen and Bath Sealant

Low-odor silicone formula is water-resistant in 1/2 hr. Forms a flexible, waterproof seal with excellent adhesion.

### DOW CORNING

DOWSIL Silicone Base Clear Cartridge Sealant is for use on concrete, glass, masonry, metal, plastic, and wood. DOWSIL 786 RTV Sealant is designed to seal nonporous surfaces around showers, tubs, sinks, and plumbing fixtures.

### GE

#### Silicone II Sealant

D0278 and D0279 are low odor and mildew resistant. Sealant remains permanently flexible.

#### Silicone II Supreme Sealant

Sealant is permanently flexible, won't corrode metals, is water-ready in 1/2 hr., and resists mold up to 10 yr. Mildew- and UV-resistant. D9106 features low VOC.

#### Silicone I Sealant

Flexible formula is mold and mildew resistant. Accommodates 25% movement in extension and compression with excellent recovery when joints shift. Applies to horizontal or vertical overhead surfaces. For use on laminate, porcelain, glass, metal, plastic, granite, wood, and most ceramic tile.

### HOMAX

Extra-wide caulk strip is a preshaped, flexible, peel-and-stick strip that seals out moisture that can damage walls by eliminating the gap where dirt can accumulate.

#### Kitchen, Bath & Plumbing 29RV15



Silicone II  
22N770



Caulking Strip  
444D75

Description	Begins to Harden	Performance Temp. Range	Size	Sealant Container	► CHOOSE: Color	Item No.
<b>DAP</b>						
100% Silicone Sealant	10 min	-40° to 400°F	9.8 oz	Cartridge	Clear	D0277 *
Kitchen, Bath and Plumbing High Performance Sealant	20 min	-65° to 200°F	9 oz	Cartridge	White	29RV14
	20 min	-65° to 200°F	9 oz	Cartridge	Clear	29RV15
Kitchen & Bath Sealant with Microban	10 min	40° to 100°F	10.1 oz	Cartridge	White, Clear, Biscuit	K4260
	10 min	40° to 100°F	5.5 oz	Tube	White, Biscuit	K4259
	10 min	-30° to 180°F	5.5 oz	Tube	Clear	29RV10
KWIK SEAL Kitchen & Bath Adhesive Caulk	10 min	-20° to 180°F	10.1 oz	Cartridge	Clear	25F525
	10 min	-20° to 150°F	10.1 oz	Cartridge	White	4MY71 *
	10 min	-20° to 150°F	5.5 oz	Tube	White, Almond	D9107 *
	10 min	-20° to 180°F	5.5 oz	Tube	Clear	5UFP2 *
Phenoseal Latex Adhesive Caulk	10 min	-20° to 100°F	10 oz	Cartridge	Almond, Metallic Gray, Black	D0281 *
	10 min	-20° to 180°F	10 oz	Cartridge	White	4MY75 *
	10 min	-20° to 180°F	10 oz	Cartridge	Clear	4MY76 *
Premium Kitchen and Bath Sealant	15 min	-65° to 350°F	10.1 oz	Cartridge	Clear	29RV06 *
	15 min	-65° to 350°F	10.1 oz	Cartridge	Almond	29RV07
<b>Dow Corning</b>						
DOWSIL 786, RTV Sealant	20 min	-75° to 350°F	10.1 oz	Cartridge	Clear, Translucent White	K4257
DOWSIL Glazing Sealant	45 min	-75° to 350°F	10.3 oz	Cartridge	Aluminum Gray, Black, Bronze, Clear, Transparent White, White	K4214
DOWSIL Hi-Temp Sealant Red	25 min	-75° to 350°F	10.3 oz	Cartridge	Red	53DD20
DOWSIL HVAC/R Sealant	25 min	-75° to 350°F	10.3 oz	Cartridge	Aluminum Gray	53DD18
	25 min	-75° to 350°F	10.3 oz	Cartridge	Clear	53DD19
DOWSIL Tub/Tile/Ceramic Sealant	25 min	-75° to 350°F	10.3 oz	Cartridge	Almond, Clear, Transparent White, White	K4720
<b>GE</b>						
Silicone II Caulk	30 min	-60° to 400°F	2.8 oz	Tube	Almond	446G71
	30 min	-60° to 400°F	10.1 oz	Cartridge	Clear, White	D0279
Silicone II Silicone Sealant	10 min	-60° to 400°F	10.1 oz	Cartridge	Almond	11N099
	30 min	-60° to 400°F	2.8 oz	Tube	Clear, White	D0278
	30 min	-60° to 400°F	2.8 oz	Tube	Clear	22N770
Silicone II Supreme Silicone Sealant	30 min	-60° to 400°F	10.1 oz	Cartridge	Clear, White, Almond	D9106
Silicone I Sealant Supreme Paintable Silicone Sealant	30 min	-60° to 400°F	10.1 oz	Cartridge	Clear, White	K4258
	20 min	-30° to 150°F	10.1 oz	Cartridge	White	11N101 *
<b>Homax</b>						
Bathroom Tub, Wall Surrounds Hybrid Caulking Strip Strip	30 min	Not Rated	1 1/2 in x 11 ft	Roll	White	444D75

\* Paintable.

## Fireplace and Stove Sealers

- Sealant container: 10.1 oz. cartridge

**Silicate Cement**—High-heat mortar for use on masonry and wood. Ideal for patching firebrick and mortar in fireplaces, and sealing wood-burning stoves. Cleans up with water.

**Blockade Intumescent Acrylic Sealant**—Single-component water-based firestop sealant for use on concrete, fiberglass, plastic, and wood. Meets ASTM E8141 and UL 1479 standards.



Silicate Cement  
2KVH9



## Food-Grade Sealant

Silicone formula for commercial kitchens and food processing for use on ceramic, fiberglass, glass, metal, and plastic. Provides a durable, waterproof seal with minimal shrinkage, long-lasting flexibility, and excellent adhesion. NSF Standard 51 certified.

Sealant Container	Size	Begins to Harden	Full Cure	Application Temp. Range	Sealant Properties	Brand	Item No.
<b>Almond</b>							
Cartridge	10.1 oz	10 min	24 hr/ Expose to water 3 hr	40° to 100°F	Flexible	GE	11N099
<b>Clear</b>							
Cartridge	9.8 oz	10 min	1 day	-35° to 140°F	Flexible, Food Grade	DAP	20HA77
Cartridge	10.1 oz	30 min	1 day	40° to 100°F	Flexible	GE	3LA48
Tube	2.8 oz	30 min	1 day	40° to 100°F	Flexible	GE	3LA50
<b>Stainless Steel</b>							
Cartridge	9.8 oz	10 min	1 day	-35° to 140°F	Flexible, Food Grade	DAP	20HA78
<b>White</b>							
Cartridge	9.8 oz	10 min	1 day	-35° to 140°F	Flexible	DAP	20HA76
Cartridge	10.1 oz	30 min	1 day	40° to 100°F	Flexible	GE	3LA49
Tube	2.8 oz	30 min	1 day	40° to 100°F	Flexible	GE	4UH01



20HA76