



Heavy-Duty Industrial Hydraulic Press Sets and Accessories

ENERPAC. 2

Arbor Presses—Foot mounting holes allow vertical or horizontal positioning. Slotted back simplifies loading and unloading of longer parts. Order pump and cylinder separately.

C-Clamp Presses—18Y517 and 18Y518 are operational in all positions and include foot mounting holes for vertical or horizontal positioning.

Bench Press-Use where there is limited space, for quick press access, or for smaller parts. Includes 6-ft. thermoplastic hose. Cylinder mounting adapter allows lateral positioning along rails. Ships with predrilled mounting holes.

H-Frame Presses—Feature welded H-frame for longer life. Each includes heavy-duty steel pump mounting bracket, 10,000-psi pump, cylinder, hose, gauge, and gauge adapter. 3KD82 and 3KD81 feature 10-ft. control pendant; roller head design allows side-to-side movement and cylinder locking. Presses with over 10-ton capacity are equipped with an exclusive Hydra-Lift bed for adjustment.

| Frame Cap. (tons) | | Total Height (in.) | Working Height (in.) | | Total Width (in.) | | Working Width | | Mtr. Model | | ltem No. |
|-------------------|----------------|--------------------------------|----------------------|--------------------|-------------------|-------------------|------------------|--------------------------------|------------------|---------------|-------------|
| Arbor Pres | sses (Pump & I | Cylinder sold separately) | | | | | | | | | |
| | 10 tons | 165/16 | 8.94 | | 5.31 | | 2.0 | 0 in | F | A310 | 4YDT3 |
| 30 tons | | 2115/16 | 10.25 | | 7.00 | | 2.00 in | | A330 | | 4YDT4 |
| Frame Capacity | | Total Height | Working Height | | Total Width | | Working Width | | Mfr. Model | | Item No. |
| C-Clamp F | resses (Pump | & Cylinder sold separately) | | | | | | | | | |
| 5 ton | | 1129/64 | 61/2 | | 8 | | 2.00 in | | A205 | | 14A076 |
| 10 ton | | 16 | 9 | | 31/4 | | 3 1/4 in | | A210 | | 18Y517 |
| 20 ton | | 211/4 | 1111/8 | | _ | | 3 ¾ in | | A220 | | 18Y518 |
| Frame Capacity | Pump Type | Pump | Cylinder | Cylinder Stroke | Cylinder Type | Overall Height | Overall Width | Max. Ram-to- Table Distance | Working Width | Mfr. Model | Item No. |
| Bench Pre | | · | • | | | | | | | | |
| 10 ton | Hand Pump | Mfr. No. P142 | _ | _ | Single Acting | 29 39/64 in | 9 29/64 in | 16 47/64 in | 2.00 in | VLP106P142U | 60UN31 |
| H-Frame F | resses | | | | | | | | | | |
| 10 ton | Air | Mfr. No. XA-11 | Mfr. No. RC-1010 | _ | Single Acting | 52 in | 241/8 in | 40 in | 2.00 in | IPA1220 | 3KD79 |
| 10 ton | Manual | Mfr. No. P-392 | Mfr. No. RC-1010 | _ | Single Acting | 52 in | 24% in | 40 in | 2.00 in | IPH1240 | 3KD83 |
| 10 ton | Electric | Mfr. No. PEM-1201B | Mfr. No. RC-1010 | 10 1/4 in | Single Acting | 52 in | 24% in | 40 in | 30 in | IPE1215 | 25TU61 |
| 25 ton | Air | Mfr. No. XA-12 | Mfr. No. RC-2514 | _ | Single Acting | 76 in | 40½ in | 54½ in | 2.00 in | IPA2520 | 3KD80 |
| 25 ton | Manual | Mfr. No. P-80 | Mfr. No. RC-2514 | | Single Acting | 76 in | 40½ in | 54½ in | 2.00 in | IPH2531 | 3KD84 |
| 50 ton | Electric | Mfr. No. ZE4420SB-N/ZE4420SG-N | Mfr. No. RR-5013 | | Double Acting | 76 in | 42¾ in | 48.56 in | 2.00 in | IPE5060 | 3KD82 |
| 100 ton | Electric | Mfr. No. ZE4420SB-N | Mfr. No. RR-10013 | _ | Double Acting | 76 in | 51 in | 421/2 in | 2.00 in | IPE10060 | 3KD81 |
| 150 ton | Electric | Mfr. No. ZE5420SG-N | Mfr. No. RR-15013 | 13 1/4 in | Double Acting | 90 in | 247/s in | 48½ in | 67 8/47 in | IPE15065 | 25TU62 |

2352