

Hose and Crimpable Fittings with JIC Connection

- Hose fittings are specific to the hose brand
- 4:1 safety factor
- Temp. range: -40° to 212°F

Lightweight and easy-to-route hose is made of nylon tube with polyurethane cover and braided synthetic fiber reinforcement. Fittings are steel.

	Hose I.D.		Hose ength	Max. Working Pressure @ 70°F	Bend Radius	Mfr. Model	Item No.
Hydraulic Hose	47.1	47.1	==				
	1/4 in	1/2 in	50 ft	3,000 psi	1 1/4 in	3TR7-04-50	
	5∕16 in	%16 in	50 ft	3,000 psi	1 ½ in	3TR7-05-50	61KJ55
	3⁄8 in	41/64 in	50 ft	3,000 psi	2 in	3TR7-06-50	61KJ56
	½ in	¹³ ⁄16 in	50 ft	3,000 psi	2 ¾ in	3TR7-08-50	61KJ57
	For Hose Dash Size	Fitting Size	Fitt Move	ing ment	Thread Size	Mfr. Model	Item No.
Female x Femal			- 0	1	7/ 00	4744514	CALVIED
	-4 -4 -4	7/16 in x 1/4 in 1/2 in x 1/4 in 9/16 in x 1/4 in	. Sw	ivel	7/16"-20 1/2"-20 9/16"-18	4TA4FJ4 4TA5FJ4 4TA6FJ4	61KJ58 61KJ59 61KJ60
	-5 -5	1/2 in x 5/16 ir 9/16 in x 5/16 i	n Sw	ivel	½"-20 %16"-18	4TA5FJ5 4TA6FJ5	61KJ61 61KJ62
	-6 -8	% in x % in % in x ½ in			9/16"-18 3/4"-16	4TA6FJ6 4TA8FJ8	61KJ63 61KJ64
	For Hose Dash Size	Fitting Size	Fitt Move	ing ment	Thread Size	Mfr. Model	Item No.
Female x Femal	e, ORS x Crii	mp					
	-4	%16 in x 1/4 in	n Sw	ivel	9/16"-18	4TA4FR4	61KJ65
100	-5	11/16 in x 5/16	in Sw	ivel 1	1/16"-16	4TA6FR5	61KJ66
	-6	11/16 in x 3/8 i	n Sw	ivel 1	1/16"-16	4TA6FR6	61KJ67
	-8	13/16 in x 1/2 i	n Sw	ivel	¹³ ⁄16"-16	4TA8FR8	61KJ68
	For Hose Dash Size	Fitting Size	Fitt Move	ing ment	Thread Size	Mfr. Model	Item No.
Male x Female,							
	-4	1/4 in x 1/4 in			1/4"-18	4TA4MP4	61KJ69
	-5	1/4 in x 5/16 it			1/4"-18	4TA4MP5	61KJ70
The state of the s	-6	1/4 in x 3/8 in	ı Ri	gid	1/4"-18	4TA4MP6	61KJ71
	-6 -8	% in x % in ½ in x ½ in		, .	3/8"-18 1/2"-14	4TA6MP6 4TA8MP8	61KJ72 61KJ73

FAT•N | Aeroquip **Hydraulic Crimping Machines**

These lightweight, portable crimping devices are also compatible with MatchMate and Synflex hose and fittings (see above ads).

Note: Machine 54ZY27 requires 10,000 psi pumps, available on page 2348.

Note: For Collet and additional Die Kits, see Grainger.com

Hydraulic

Hose



Crimpii Max.	Min.	Hose Type Compatibility	Voltage	Operating Pressure		Crimping Force	Mfr. Model	Item No.
Bench I	Mount	•						
1 1/4 in	1 1/4 in	4 Spirai	115V	22,000 ps	si Electric Pump	10 ton	FT1380- 115-8	10C379
1 1/4 in	1 ¼ in	1 to 2 Wire, 4 Spiral	_	10,000 ps	External (No Pump Included	10 ton	ET1187- 001	54ZY27
1 1/4 in	1 ¼ in	1 to 2 Wire, 4 Spiral	_	10,000 ps	External (No Pump Included	35.3 ton	ET1000- 001	4YNW9
Floor								
2 in	2 in	1 to 2 Wire, 4 and 6 Spiral	115V	10,000 ps	si Electric Pump	10 ton	FT1390- 115-12	35Z762
Hose Cr Capa Max.	city	Hydraulic Hose Type Compatibility	Conne Color (Compatible Mfr. Model No.	Include	es	Item No.
Eaton A	eroquij	p Dies & Die Se	ts					
1 1/4 in	1⁄4 in	2 Wire	lack, Blue Red, Ye		ET1000	(3) Spac Rings, (8) Dies, Ada Ring, Pus	Split pter	54ZY34
1 1/4 in	1⁄4 in	1 Wire, 2 Wire 1 Wire,	Gol	d E	T1187, FT1380	(9) Crimpe	r Dies	54ZY33

Max.

MatchMate 4-Wire Hose and Crimpable Fittings

FAT•N

- Hose fittings are specific to the hose brand
- 4:1 safety factor
- Synthetic rubber hose with
- 4-wire spiral reinforcement
- Temp. range: -40° to 250°F

For hydraulic system service with petroleum and waterbased fluids and general industrial use.

Dia. (in.) Bulk Hose	Hose Outside Dia. (in.)	Hose Length (ft.)	Operating Pressure (ps	Min. B i) Radius	end Mfr. (in.) Model	Item No.
1/2	.92	50	6000	3.5		10C23
3/4	1.2	50	5500	4	GH493-12	10C23
1 11/4	1.48 1.83	50 50	5100 4500	6 8.2	GH493-16 GH493-20	10C23 10C23
174	Hydraulic	Hydraulic		L	Mfr.	Item
emale JIC	Hose I.D.	Thread S	Size (in.)	Model	No.
Ciliaic Jio						
Con and and and and and and and and and an	½ in	3/4"-16	5 2	2.63	4SA8FJ8	471Z43
R.	½ in	3/4"-16	S (3.30	4SA8FJA8	471Z55
7	½ in	3/4"-16	5 2	2.87	4SA8FJB8	471Z61
Q.	3⁄4 in	11/16"-1	2 3	3.23	4SA12FJ12	471Z49
2	3⁄4 in	1½6"-12		1.42	4SA12FJA12	
7	3⁄4 in	11⁄16"-12		3.99	4SA12FJB12	
Q.	1 in	15/16"-12		3.51	4SA16FJ16	
2	1 in	15/16"-12		5.07	4SA16FJA16	
7	1 in	1 5⁄16"-1	2 4	1.45	4SA16FJB16	471Z66
Female JIC Swi	1 ¼ in	15/8"-1	2	4	4SA20FJ20	46AC9
6	1 ¼ in	15⁄8"-1	2 :	3.20	4SA20FJA20	46AC90
-	1 ¼ in	15⁄8"-1	2 5	5.20	4SA20FJB20	46AC9
Male NPTF	14 :	141.4		75	40,40,400	47470
	1/2 in 3/4 in	1/2"-14 3/4"-14	1 :	2.75 3.38	4SA8MP8 4SA12MP12	471Z3
	1 in	1"-11-1	/2 :	3.70	4SA16MP16	471Z39
Male Universal	1 ½ in	11/4"-11-	1/2 4	1.71	4SA20MP20	471Z4
	½ in	0.511"-27		2.87	4S8FLB8	
	½ in	_		3.13	4S8FLA8	
	3⁄4 in	0.511"-27		1.27	4S12FLB12	
	3⁄4 in	_		3.57	4S12FL12	
	1 in	_		1.96	4S16FLB16	
	1 in — 3.67 1 in — 5.16		4S16FL16 4S16FLA16	471Z78		
1	1 in			J. 1U	HOTOTLATO	₩11L00
	1 ½ in			3.44	4S24FLA24	471Z91