





Slimline 2VB70

2W836

2VB69

304 Stainless Steel 4KP15

HUBBELL

WIEGMANN

30mm JIC and NEMA 12 and 13 Oiltight Push-Button Enclosures

- JIC Standard EL-1-71
- 14-ga. carbon steel
- ANSI 61 gray polyester powder-coated finish, except stainless steel

 Seam welded and ground smooth

Neoprene gasket and mounting flange ensure oiltight seal. Captive cover screws are threaded into deep-well hubs. Grounding stud included. UL Listed and CSA Certified.

| uuu | | 10103 | Jui | WIEGMANN | | | |
|----------|--------------|----------|---------|----------|---------------|-------------|--|
| | Columns | н | w | D | Mfr. Model | ltem No. | |
| Slimline | | | | | | | |
| 1 | 1 | 4 in | 2.5 in | 2.5 in | PSL1 | 2VB70 | |
| 2 | 1 | 6.25 in | 2.5 in | 2.5 in | PSL2 | 2VB72 | |
| 3 | 1 | 8.5 in | 2.5 in | 2.5 in | PSL3 | 2VB74 | |
| 4 | 1 | 10.75 in | 2.5 in | 2.5 in | PSL4 | 2VB76 | |
| Standard | | | | | | | |
| 1 | 1 | 3.5 in | 3.25 in | 2.81 in | PB1 | 2W834 | |
| 2 | 1 | 5.75 in | 3.25 in | 2.81 in | PB2 | 2W835 | |
| 3 | 1 | 8 in | 3.25 in | 2.81 in | PB3 | 2W836 | |
| 4 | 1 | 10.25 in | 3.25 in | 2.81 in | PB4 | 3A934 | |
| 6 | 2 | 9.5 in | 6.25 in | 3.09 in | PB6 | 2W837 | |
| 9 | 3 | 9.5 in | 8.5 in | 3.09 in | PB9 | 3A935 | |
| 12 | 3 | 11.75 in | 8.5 in | 3.09 in | PB12 | 3A936 | |
| Extra | Deep | | | | | | |
| 1 | 1 | 4 in | 4 in | 4.81 in | PBXD1 | 2VB65 | |
| 2 | 1 | 6 in | 4 in | 4.81 in | PBXD2 | 2VB66 | |
| 3 | 1 | 8 in | 4 in | 4.81 in | PBXD3 | 2VB67 | |
| 4 | 1 | 10 in | 4 in | 4.81 in | PBXD4 | 2VB68 | |
| 6 | 2 | 9.5 in | 8.5 in | 4.81 in | PBXD6 | 2VB69 | |
| 304 S | tainless Ste | | | | | | |
| 1 | 1 | 3.5 in | 3.25 in | 2.81 in | PBSS1 | 4KP15 | |
| 4 | 1 | 10.25 in | 3.25 in | 2.81 in | PBSS4 | 4KP18 | |
| | | | | | | | |



30mm Push-Button Enclosures

 ¾" NPT conduit entry legend plates will not fit on these enclosures.

| No. of | | NEMA | | | | Mfr. | Item | |
|---|--------------------------------|-----------------|----------|---------|---------|-----------|-------|--|
| Holes | Color | Rating | Н | W | D | Model | No. | |
| Metal Enclosures | | | | | | | | |
| 1 | Gray | 1, 13, 3 | 5.24 in | 4.18 in | 3.63 in | 9001KYAF1 | 2NMA9 | |
| 2 | Gray | 1, 13, 3 | 7.74 in | 4.18 in | 3.63 in | 9001KYAF2 | 2EP71 | |
| 3 | Gray | 1, 13, 3 | 10.24 in | 4.18 in | 3.63 in | 9001KYAF3 | 2NMC1 | |
| 4 | Gray | 1, 13, 3 | 12.74 in | 4.18 in | 3.63 in | 9001KYAF4 | 2NMC2 | |
| Die-Cast Aluminum Enclosures with Guard | | | | | | | | |
| 1 | Gray | 4 | 3.63 in | 5.5 in | 4 in | 9001KYG1 | 5GCD8 | |
| 1 | Gray and Yellow | 4 | 3.63 in | 5.5 in | 4 in | 9001KYG1Y | 5GCD9 | |
| Die-Cas | st Aluminum Enclo | osures | | | | | | |
| 1 | Gray | 1, 13, 3, 4 | 4 in | 3.63 in | 3.53 in | 9001KY1 | 5B478 | |
| 2 | Gray | 1, 13, 3, 4 | 5.75 in | 3.63 in | 3.53 in | 9001KY2 | 5B477 | |
| 3 | Gray | 1, 13, 3, 4 | 7.5 in | 3.63 in | 3.53 in | 9001KY3 | 5B476 | |
| 4 | Gray | 1, 13, 3, 4 | 9.25 in | 3.63 in | 3.53 in | 9001KY4 | 5B475 | |
| Metal I | Metal Enclosures | | | | | | | |
| 1 | _ | 1, 13, 3, 4, 4X | 5.24 in | 4.18 in | 3.63 in | 9001KYSS1 | 2EP86 | |
| 304 Sta | 304 Stainless Steel Enclosures | | | | | | | |
| 2 | — | 1, 13, 3, 4, 4X | 7.74 in | 4.18 in | 3.63 in | 9001KYSS2 | 2NME1 | |
| Plastic Enclosures | | | | | | | | |
| 1 | Gray | 1, 13, 3, 4, 4X | 6.63 in | 3.81 in | 3.88 in | 9001SKY1 | 2ER70 | |
| 2 | Gray | 1, 13, 3, 4, 4X | 6.63 in | 3.81 in | 3.88 in | 9001SKY2 | 2NMR3 | |
| 3 | Gray | 1, 13, 3, 4, 4X | 8.88 in | 3.81 in | 3.88 in | 9001SKY3 | 2NMR4 | |
| Blankir | Blanking Plugs | | | | | | | |
| _ | Gray | — | — | _ | _ | 9001K51 | 5B543 | |
| _ | Black | _ | _ | _ | _ | 9001K52 | 5B542 | |

Enclosure 2AAR9



Push-Button Enclosure 2VB54



WIEGMANN

JIC and NEMA 12 and 13 Sloped Enclosures

- Carbon steel
- ANSI 61 gray polyester powder-coated finish
 Seam welded and ground smooth
- Seam weided and ground sr UL Listed, CSA Certified.

Angled face ensures all installed devices face operator. Enclosures have grounding provision. Captive cover screws are threaded into deep-well hubs.

Sloped Top

Enclosure can be mounted to create either a 30° or 60° angle for the control surface. Continuously hinged cover along bottom edge.

Push-Button

Accept all standard 30mm 4-way push buttons, switches, and pilot lights. Top and bottom mounting plate.

Column

2VE11

PEDESTAL COLUMNS AND BASES

Support sloped-top enclosures.

Columns

Pedestal columns provide passageway for wiring. Flanged at both ends with a gasketed cover plate. Include access plate, gaskets, screws, and box connective fittings. Angled pedestal has a 45° angle at top.

Bases

Floor mounted with a square pattern of holes to fit a wiring column or other flanged device. Include leveling screws.

| Description | н | w | D | ltem No. |
|--|---------|---------|---------|-------------|
| Sloped Top Enclosure | 8 in | 8 in | 7 in | 2VB90 |
| Sloped Top Enclosure | 8 in | 12 in | 7 in | 2VB91 |
| Sloped Top Enclosure | 8 in | 16 in | 7 in | 2VB92 |
| Sloped Top Enclosure | 8 in | 20 in | 7 in | 2AAR9 |
| Sloped Top Enclosure | 12 in | 12 in | 9 in | 2VB93 |
| Sloped Top Enclosure | 12 in | 16 in | 9 in | 2VB94 |
| Sloped Top Enclosure | 12 in | 20 in | 9 in | 2VB95 |
| Sloped Top Enclosure | 12 in | 24 in | 9 in | 2AAT1 |
| Sloped Top Enclosure | 16 in | 16 in | 11 in | 2VB96 |
| Sloped Top Enclosure | 16 in | 20 in | 11 in | 2VB97 |
| Sloped Top Enclosure | 16 in | 24 in | 11 in | 2AAT2 |
| Sloped Top Enclosure | 16 in | 30 in | 11 in | 2AAT3 |
| Sloped Top Enclosure | 20 in | 20 in | 13 in | 2VB98 |
| Sloped Top Enclosure | 20 in | 24 in | 13 in | 2ACB7 |
| Sloped Top Enclosure | 20 in | 30 in | 13 in | 2AUB4 |
| Sloping Front Pushbutton Enclosure, 1 Column, 1 Hole | 3.5 in | 3.25 in | 4.78 in | 2VB54 |
| Sloping Front Pushbutton Enclosure, 1 Column, 2 Hole | 3.5 in | 5.5 in | 4.78 in | 2VB55 |
| Sloping Front Pushbutton Enclosure, 1 Column, 3 Hole | 3.5 in | 7.75 in | 4.78 in | 2VB56 |
| Sloping Front Pushbutton Enclosure, 1 Column, 4 Hole | 3.5 in | 10 in | 4.78 in | 2VB57 |
| Sloping Front Pushbutton Enclosure, 3 Column, 6 Hole | 7.25 in | 8.5 in | 6.66 in | 2VB58 |
| Straight Pedestal Column | 35 in | 4 in | 4.00" | 2VE11 |
| Angled Pedestal Column | 41 in | 4 in | 4.00" | 2VE12 |
| Straight Pedestal Column | 35 in | 6 in | 6.00" | 2VE13 |
| Pedestal Base | 1 in | 18 in | 18.00" | 2VB99 |
| Pedestal Base | 1 in | 24 in | 24.00" | 2VE10 |

Sign in to Grainger.com® to see YOUR Pricing and MORE