

1-800-GRAINGER (472-4643)



Little **GIANT**

Flexible Impeller Utility Pedestal Pumps

■ Buna-N impeller

FLEXIBLE IMPELLER UTILITY PEDESTAL PUMPS

Ideal for transferring liquids and emptying bowls, sinks, tanks, bilges, and have a dual inlet and outlet. Intermittent duty.

5UXL8 to 5UXN6—Feature stainless steel shaft and ball bearings, except 5UXN4 to 5UXN6 have sleeve bearings. Each includes 2 impellers and gasket. 5UXL7 and 5UXL9 have thermally protected motors.

Cast Aluminum 32JA72



Nickel-Plated Brass 5UXL8



Nickel-Plated Brass 5UXN4



Stainless Steel 5UXL9



| HP | Voltage | Amps AC | Motor Type | Motor Encl. | GPM of Water @ Total Ft. of Head (gpm) | | | | Inlet/Outlet (in.) | Max. Head (ft.) | Max. Suction Lift (ft.) | Max. Liquid Temp. (°F) | Max. Pressure (psi) | Cord | Brand | Mfr. Model | Item No. |
|---|---------|-----------|-----------------|--------------------------------|--|------|------|------|--|-----------------|-------------------------|------------------------|---------------------|---------------------------|-----------------|------------|----------|
| | | | | | 5 | 10 | 20 | 40 | | | | | | | | | |
| Flexible Impeller Utility Pedestal Pumps | | | | | | | | | | | | | | | | | |
| Cast Aluminum | | | | | | | | | | | | | | | | | |
| 1/2 | 12 V DC | 6 to 8 | DC | Open | 3.55 | 3.1 | 2.12 | 0.23 | 3/4 in OD, 3/8 in ID | 41.2 ft | 15 ft | 140 °F | 17.8 psi | 11 ft | Flint & Walling | 024481 | 32JA73 |
| | 115 V | 2.3 | Universal AC/DC | Open | 3.15 | 2.8 | 2.12 | 0.72 | 3/4 in OD, 3/8 in ID | 48 ft | 3 ft | 140 °F | 20.7 psi | 6 ft | Flint & Walling | 023817 | 32JA72 |
| Nickel-Plated Brass | | | | | | | | | | | | | | | | | |
| 1/4 | 12 V DC | 6.5 to 10 | DC | Open | 3.72 | 3.32 | 2.31 | — | 3/8 ID; 3/4 OD Garden Hose | 36.7 ft | 7 ft | 140 °F | 19.9 psi | 7 ft | Dayton | 5UXL8 | 5UXL8 |
| | 12 V DC | 7.0 | DC Brush | Totally Enclosed Nonventilated | — | — | — | — | 3/4 in Male GHT / 3/8 in FNPT | 46 ft | 7 ft | 120 °F | — | 12 in Leads | Little Giant | 555602 | 5UXN5 |
| | 115 V | 1.6 | AC Brush | Open Fan Cooled | — | — | — | — | 3/4 in male garden hose thread and 3/8 in FNPT | 48 ft | 7 ft | 120 °F | — | 6 ft | Little Giant | 555112 | 5UXN4 |
| | 115 V | 1.6 | Universal AC/DC | Open | 5.2 | 4.43 | 3.05 | — | 3/8 ID; 3/4 OD Garden Hose | 37.3 ft | 7 ft | 140 °F | — | 6 ft | Dayton | 5UXL7 | 5UXL7 |
| Stainless Steel | | | | | | | | | | | | | | | | | |
| 1/4 | 12 V DC | 6.5 to 10 | DC | Open | 3.72 | 3.32 | 2.31 | — | 3/8 ID; 3/4 OD Garden Hose | 36.7 ft | 7 ft | 140 °F | 19.9 psi | 7 ft | Dayton | 5UXN0 | 5UXN0 |
| | 115 V | 1.6 | AC Brush | Open Fan Cooled | — | — | — | 130 | 3/4 in Male GHT / 3/8 in FNPT | 48 ft | 7 ft | 120 °F | — | 6 ft with NEMA 5-15P Plug | Little Giant | 555110 | 5UXN6 |
| | 115 V | 1.6 | Universal AC/DC | Open | 5.2 | 4.43 | 4.5 | — | 3/8 ID; 3/4 OD Garden Hose | 37.3 ft | 7 ft | 140 °F | 20.9 psi | 6 ft | Dayton | 5UXL9 | 5UXL9 |
| Pump Repair Kits | | | | | | | | | | | | | | | | | |
| For Use With | | | | | Includes | | | | | Brand | | | | | Item No. | | |
| 5UXL7, 5UXL8, 5UXL9, 5UXN0 | | | | | Cam, 2 Gaskets, 2 Impellers | | | | | Dayton | | | | | 5UXN1 | | |
| 5UXL7, 5UXL8, 5UXL9, 5UXN0 | | | | | 2 Gaskets, 2 Impellers | | | | | Dayton | | | | | 5UXN2 | | |
| 360S, 555909, Mfr. No. 360 | | | | | (2) Gaskets, (2) Impellers | | | | | Little Giant | | | | | 6EDW3 | | |
| 360S, 555909, Mfr. No. 360 | | | | | (1) Felt Washer, (1) Retainer Ring, (1) Viton U-Cup Seal, (2) Gaskets, (2) Impellers | | | | | Little Giant | | | | | 6EDW4 | | |



Self Priming, Corded Utility Pumps

■ 115V AC

Use an air-water mixture to reach a fully-primed pumping condition. Self-priming and draw liquids from a source located below the pump, and must be primed before first use to ensure a proper seal. Use to water lawns, pump out flooded basements, bail out boats, and boost water pressure. Pumps feature lubricated, shielded ball bearings and external brush holders.



Dayton 33RW83



Liberty Pumps 5YU12



Zoeller 4HEX4

| HP | Pump Housing Material | Flow Rate @ 10 ft of Head (Maximum) | Flow Rate @ 20 ft of Head (Maximum) | Flow Rate @ 30 ft of Head (Maximum) | Maximum Feet of Head | Best Efficiency Head | Shut Off Pressure (Maximum) | Cord Length | Intake and Discharge Intake Type | Motor Encl. | Includes | Mfr. Model | Item No. |
|----------------------|-----------------------|-------------------------------------|-------------------------------------|-------------------------------------|----------------------|----------------------|-----------------------------|-------------|----------------------------------|---------------------------|--|------------|----------|
| Dayton | | | | | | | | | | | | | |
| 1/12 | Plastic | 5 gpm | 4 gpm | 2.4 gpm | 43 ft | 20 ft | 18.6 psi | — | 3/4 in, 3/4 in GHT | Open Dripproof | 6 ft Length of Garden Hose, Cam Ring and O-Ring, Extra Impeller, Ports with 3/4 in OD Fittings, Suction Strainer | 3YU61 | 3YU61 |
| 1/2 | Cast Iron | 21.7 gpm | 19.5 gpm | 17.7 gpm | 118 ft | 39 to 66 ft | 51 psi | — | 3/4 in, 3/4 in NPT | Open Dripproof | Suction Strainer, (2) 3/4 in Garden Hose Adapters, (2) Replacement Brushes | 33RW83 | 33RW83 |
| | Plastic | 9.9 gpm | 9.6 gpm | 6.8 gpm | 134 ft | 10 ft | 58 psi | 10 ft | 1 in, 1 in NPT | Open Dripproof | 1 in FNPT x 3/4 in Garden Hose Adapters | 3YU60 | 3YU60 |
| | Stainless Steel | 15.7 gpm | 15.4 gpm | 15.3 gpm | 145 ft | 46 to 81 ft | 64 psi | — | 1 in, 1 in NPT | Open Dripproof | (2) Garden Hose Adaptors | 4CUK6 | 4CUK6 |
| Liberty Pumps | | | | | | | | | | | | | |
| 1/2 | Aluminum | 22 gpm | 20 gpm | 17 gpm | 105 ft | 65 ft | 45 psi | 20 ft | 3/4 in, 3/4 in GHT | Open Dripproof | 3/4 in OD Brass Garden Hose Connectors, Plastic Suction Screen | 331 | 5YU12 |
| Zoeller | | | | | | | | | | | | | |
| 1/2 | Cast Iron | 22.5 gpm | 21.5 gpm | 20 gpm | 115 ft | 110 ft | 50 psi | 20 ft | 3/4 in, 3/4 in NPT | Totally Enclosed Air Over | 3/4 in NPT Brass, Lead Free Garden Hose Adapters, Suction Screen and Extra Set of Brushes | 314-0002 | 4HEX4 |