

**1-800-GRAINGER (472-4643)**

**Mop Sinks, Waste Disposers & Grease Interceptors**

For Sink Material and Bowl Size, see page 2606.

**Mop Sinks**

*American Standard*



■ 3" drain

Sinks allow personnel to rinse mops and empty bucket contents with minimal lifting or strain. They are typically mounted on or near the floor in janitorial closets or maintenance rooms. **Corner Mop Sinks** install in corners to maximize space. **Mop Sinks with Drop Front** have a shorter or notched side for easy pouring. **Mop Sink Bowls** have higher sides to contain water splashes inside the sink.



1RLN4



11U264

Brand	Sink Material	L	W	H	Bowl Size L x W	Bowl Depth	Color	Mfr. Model	Item No.
<b>Corner Mop Sinks with Drop Front</b>									
American Standard	Enameled Cast Iron	28 in	28 in	13 in	25 in x 13 in	8 in	White	7741000.020	41H856
<b>Mop Sink Bowls</b>									
Mustee	SMC Fiberglass	24 in	24 in	10 in	24 in x 24 in	10 in	White	63M	1RLN4
Mustee	SMC Fiberglass	36 in	24 in	10 in	24 in x 36 in	10 in	White	65M	11U263
<b>Mop Sink Bowls with Faucets, Lever Handle, Angled Straight Spout</b>									
Mustee	SMC Fiberglass	24 in	24 in	10 in	24 in x 24 in	10 in	White	63CM	11U264
<b>Mop Sinks with Drop Front</b>									
Terrazzo-Ware	Terrazzo	24 in	24 in	12 in	20 in x 20 in	4 in	Tan	TDF-24-SSC	19RU56

Description	Brand	Mfr. Model	Item No.
<b>Accessories</b>			
Mop Sink Utility Shelf, Stainless Steel, 24 in L x 8 in W	Adv. Tabco	K-245	11U336
Mop Sink Utility Shelf, Stainless Steel, 36 in L x 8 in W	Adv. Tabco	K-246	11U337
Wall Guards, Stainless Steel, 24 in L x 12 in H	Mustee	67.2424	1RLN6

**Food Waste Disposers**



- Quiet Dura-Drive split-phase induction motors have permanently lubricated bearings
- Quick Lock mounting system for easy installation
- Intermittent-duty, except Commercial models are continuous-duty

1725 rpm, 60 Hz, with overload protection and manual reset.

**ESSENTIAL XTR**

Features SoundSeal technology for quiet operation and MultiGrind technology that provides 2 grinding stages versus 1 stage in many standard disposers. Includes a SinkTop Switch accessory with button and power to ease activation.

**COMMERCIAL FOOD SERVICE EQUIPMENT**

■ 1-yr. manufacturer's warranty

Note: New installations require a mounting adapter, sold separately on this page or go to Grainger.com and search for "disposer, mounting adapter."

**LC-50**

Automatic reversing motor provides longer life and trouble-free operation. Stainless steel grind chamber. Disposer mounting included.

**SS Series**

Triple-lip motor seal protects motor from water damage while a secondary spring-loaded oil seal provides double protection against water and loss of grease. Cast nickel-chrome alloy stationary and rotating shredding elements provide long life and corrosion resistance and are designed for reverse-action grinding. Feature overload protection and stainless steel grind chamber.

**COMMERCIAL MOUNTING ADAPTERS**

Use to mount commercial food waste disposer to sink.



HP	Connection Drain	Phase	Voltage	Overall Height	Grinding Chamber Capacity	Manufacturers Warranty	Mfr. Model	Item No.
<b>Badger and Evolution Series</b>								
1/2 hp	1 1/2 in	Single	120	11 3/8 in	26 oz	1 yr	BADGER 1	5H502
		Single	120	11 3/8 in	26 oz	1 yr	BADGER 1 WITH CORD	31EE15
1/2 hp	1 1/2 in	Single	120	12 3/8 in	26 oz	2 yr	BADGER 5	5H877
		Single	120	12 3/8 in	26 oz	3 yr	BADGER 5 WITH CORD	31EE16
3/4 hp	1 1/2 in	Single	120	12 1/2 in	35 oz	4 yr	Badger 5 XP	2YB90
		Single	120	12 1/2 in	40 oz	4 yr	Evolution Compact™	2YB94
1 hp	1 1/2 in	Single	120	13 1/2 in	40 oz	7 yr	Evolution Septic Assist™	2YB95
1 hp	1 1/2 in	Single	120	13 1/2 in	40 oz	7 yr	Evolution Excel™	2YB91
<b>Essential XTR Series</b>								
3/4 hp	1 1/2 in	Single	120	12 1/4 in	35 oz	6 yr	Essential XTR	54DC92
HP	Connection Drain	Phase	Voltage	Overall Height	Grinding Chamber Capacity	Mfr. Model	Item No.	
<b>Commercial Food Service Equipment</b>								
1/2 hp	1 1/2 in	Single	115/120	14 1/4 in	50 oz	LC-50-11	4PL52	
		Single	115/208-230	17 in	85 oz	SS-100-28	29NZ57	
1 hp	2 in	Three	208-230/460	17 in	85 oz	SS100-47	29NZ58	
2 hp		Three	208-230/460	18 7/8 in	111 oz	SS200-35	3DVA2	
3 hp	3 in	Three	208-230/460	23 1/2 in	317 oz	SS-300-25	29NZ61	
5 hp		Three	208-230/460	31 1/2 in	317 oz	SS-300	3DVA3	
		Three	208-230/460	20 in	317 oz	SS-500-30	29NZ62	
For Use With		Material of Construc.	Sink/Bowl Hole Dia. (in.)	Mfr. Model	Item No.			
<b>Commercial Mounting Adapters</b>								
Waste King			4 1/2	11327-A	4PL35			
Waste King			6	11327-D	4PL36			
Bus Boy		Steel	6	11327-K	4PL39			
Hobart			4 1/2	11327-H	4PL38			
Salvajor			6 3/4	11599-H	4PL41			

**Septic Assist, 2YB95**

Bio-Charge technology injects a microorganism-rich solution that breaks down and liquefies waste for safe handling in a septic tank.

**Excel, 2YB91**

Jam-Sensor circuit automatically increases motor torque up to 500%.

Capacity	Material of Construction*	Pipe Dia. - Drains	Overall Height	Overall Width	Overall Depth	Brand	Item No.
<b>Grease Interceptor</b>							
14 lb	PP	2 in	16 5/8 in	14 1/2 in	17 1/2 in	Endura	40D974
20 lb	PP	2 in	16 5/8 in	14 1/2 in	17 1/2 in	Endura	40D975
30 lb	CFS	2 in	14 in	15 in	17 1/2 in	Watts	1WXD7
	PP	2 in	16 5/8 in	23 3/4 in	17 1/2 in	Endura	40D976
40 lb	CFS	3 in	21 1/2 in	24 1/2 in	36 in	Zurn	38UK33
	PP	2 in	16 5/8 in	23 3/4 in	17 1/2 in	Endura	40D977
50 lb	CFS	3 in	17 in	19 1/2 in	12 1/2 in	Zurn	4WPJ7
	PP	2 in	16 1/2 in	31 1/4 in	18 1/2 in	Endura	40D978
70 lb	PP	2 in	11 in	31 in	23 1/2 in	Endura	40D979
	CFS	4 in	18 3/4 in	22 1/2 in	14 1/4 in	Zurn	4WPJ8
100 lb	PP	3 in	16 1/2 in	31 1/4 in	18 1/2 in	Endura	40D980
	PP	3 in	17 1/2 in	31 in	23 1/2 in	Endura	40D981
100 lb	PP	4 in	17 1/2 in	31 in	23 1/2 in	Endura	40D982
	CFS	4 in	21 1/2 in	24 1/2 in	16 in	Zurn	4WPJ9
100 lb	PP	3 in	23 1/2 in	31 in	23 1/2 in	Endura	40D983
	PP	4 in	23 1/2 in	31 in	23 1/2 in	Endura	40D984
<b>Lint Interceptor</b>							
—	CFS	2 in	16 1/2 in	17 in	13 in	Zurn	38UK34
<b>Solids Interceptor</b>							
14 lb	PP	2 in	16 31/100 in	17 4399/1000 in	12 3/32 in	Endura	40D985
<b>Solids Interceptor Basket</b>							
—	PP	2 in	14 8/25 in	13 3997/500 in	11 1/32 in	Endura	40D986

\* PP=Polypropylene. CFS=Coated Fabricated Steel.



**Grease and Lint Interceptors**



1WXD7

Endura models have 1-pc. plastic tank with an airtight silicone seal, easy-to-open latching system, and an innovative removable baffle design. 40D985 and 40D986 have a removable dual-screen filtration system with coarse and fine screens. Watts models are epoxy-coated steel with removable baffle and deep seal trap with clean-out. Recessed or floor mounted. Zurn grease interceptors have a Dura-Coated steel body, flow diffusing baffle, integral trap, and external vented inlet flow control. The Lint Interceptor 38UK34 separates out solids such as buttons, lint, stones, and string, and can handle up to 3 washing machines. Unit features an acid-resistant coated interior and exterior, a nonskid secured cover with removable lift handle, aluminum lint intercepting secondary screen assembly, and permanent primary straining baffle with 3/8" dia. perforated holes. Model has a high inlet and low outlet.