



CONTINUED

For information on faucet spout shapes, see page 2614.



SENSORFLO®

SLOAN.

American Standard



KOHLER®

TOTO®



## Sensor Single-Hole Deck-Mount Bathroom Faucets

Brand	Series	Faucet Body Material	Flow Rate	Flow Outlet Type	Power Source	Temperature Control	Spout Length	Spout Height	Mfr. Model	Item No.
<b>Straight-Spout</b>										
American Standard	Moments Selectronic	Cast Brass	0.5 gpm	Laminar	Lithium Battery	No	5 in	5 in	2506155.002	41H809
Kohler	Insight	Brass	0.5 gpm	Aerated	—	No	5 in	—	K-13461-CP	493J89 #
	Insight	Brass	0.5 gpm	Aerated	—	No	5 in	—	K-13463-CP	493J90
Sloan	Optima	Brass	0.5 gpm	Aerated	Battery	Yes	4 1/2 in	5 1/2 in	EAF250-ISM	5YJP3 †
	Optima	Brass	0.5 gpm	Aerated	Solar and Battery Powered	Yes	4 1/2 in	5 1/2 in	EAF275-ISM	5YJP4 †
<b>Angled Straight-Spout</b>										
Sloan	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EFX350.000.0000	23MF35
	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EFX650.000.0000	23MF42 *
	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	No	4 in	5 in	EFX650.010.0000	23MF44
	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	No	5 1/2 in	6 1/2 in	EFX250.000.0000	23MF26
	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	Yes	4 in	5 in	EFX350.110.0000	23MF38
	BASYS	Cast Zinc	0.5 gpm	Laminar	Battery	Yes	6 1/2 in	10 in	EFX150.500.0000	23MF17
	BASYS	Cast Zinc	0.5 gpm	Laminar	Electronic	Yes	4 in	5 in	EFX300.500.0000	23MF34
	BASYS	Cast Zinc	0.5 gpm	Laminar	Self Sustaining	No	4 in	5 in	EFX380.010.0000	23MF41
	BASYS	Cast Zinc	0.5 gpm	Laminar	Self Sustaining	No	4 in	5 in	EFX680.010.0000	23MF47
	BASYS	Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	No	4 in	5 in	EFX375.000.0000	23MF40
	BASYS	Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	No	5 1/2 in	6 1/2 in	EFX275.000.0000	23MF27
	BASYS	Cast Zinc	0.5 gpm	Laminar	Solar and Battery Powered	Yes	5 1/2 in	6 1/2 in	EFX277.500.0000	23MF31
	BASYS	Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EFX350.012.0000	23MF37
	BASYS	Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EFX650.002.0000	23MF43
	BASYS	Cast Zinc	1.5 gpm	Aerated	Battery	No	4 in	5 in	EFX650.012.0000	23MF45 *
	BASYS	Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	No	5 1/2 in	6 1/2 in	EFX275.002.0000	23MF28
	BASYS	Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	Yes	5 1/2 in	6 1/2 in	EFX277.502.0000	23MF32
	BASYS	Cast Zinc	1.5 gpm	Aerated	Solar and Battery Powered	Yes	6 1/2 in	10 in	EFX175.502.0000	23MF19
	<b>Gooseneck-Spout</b>									
American Standard	Selectronic	Cast Brass	0.35 gpm	Spray	Lithium Battery	No	2 in	7 in	6055164.002	41H846
	Selectronic	Metal	0.5 gpm	Laminar	Lithium Battery	No	7 in	7 in	6055165.002	4THG5
	HyTronic	Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	No	5 3/8 in	11 3/8 in	116.203.AB.1	5UTW6
	HyTronic	Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	Yes	5 3/8 in	11 3/8 in	116.213.AB.1	5UTP3
	HyTronic	Cast Brass	0.5 gpm	Laminar	AC Powered	Yes	5 1/4 in	11 3/8 in	116.429.AB.1	6XAE8
Chicago Faucets	HyTronic	Cast Brass	0.5 gpm	Laminar	AC Powered	Yes	5 3/8 in	11 3/8 in	116.113.AB.1	5UTP1
	HyTronic	Cast Brass	1 gpm	Laminar	6V Lithium CRP2	No	5 1/4 in	11 3/8 in	116.430.AB.1	6XAG4
	HyTronic	Cast Brass	1.5 gpm	Laminar	12V AC Transformer	No	5 1/4 in	11 3/8 in	116.427.AB.1	21FD43
	HyTronic	Cast Brass	1.5 gpm	Laminar	6V Lithium CRP2	Yes	5 1/4 in	11 3/8 in	116.432.AB.1	6XAG6
	Insight	Brass	0.5 gpm	Aerated	—	No	6 3/8 in	—	K-13475-CP	493J96
Kohler	Insight	Brass	0.5 gpm	Aerated	—	No	6 3/8 in	—	K-13473-CP	493J95 #
	—	Brass	0.5 gpm	Aerated	—	No	6 3/8 in	—	—	—
Sensorflo	SENSORFLO®	Brass	0.5 gpm	Spray	AC Powered	No	8 3/8 in	8 in	SF-9200	55MJ20
	SENSORFLO®	Brass	0.5 gpm	Spray	Battery	No	8 3/8 in	8 in	SF-9100	55MJ15
Sloan	—	Brass	2.2 gpm	Laminar	6V DC Plug-In Power Converter	No	5 1/4 in	10 in	SF2200-4	5UVA2
	—	Brass	2.2 gpm	Laminar	Battery	No	5 1/4 in	10 in	SF2250-4	5WHW9
Sloan	Optima	Brass	2.2 gpm	Laminar	Plug-In	Yes	8 7/8 in	12 1/4 in	ETF-700-4-PLG-TEE-CP-2.2GPM-LAM-IR-S-FCT	491G82
Zurn	AquaSense	Cast Brass	0.5 gpm	Laminar	Battery	Yes	5 3/8 in	12 in	Z6922-XL	30PT27

\* Integrated base body faucet. † Grid strainer. ‡ Drain with pop-up rod. # Includes (2) AAA batteries. \*\* Thermostatic mixing valve. †† SST mixing valve. †† Includes metal throat plate.



SLOAN. ZURN.

## Gooseneck-Spout Sensor Single-Hole Wall-Mount Bathroom Faucets

Hands-free sensor eliminates the spread of germs and starts/stops water flow without touching faucet. Tall gooseneck-spout extends above counter and curves to point straight down into sink. Single wall-mount hole installation saves counter space. Chrome finish. ADA Compliant.

Brand	Series	Faucet Body Material	Flow Rate	Flow Outlet Type	Power Source	Spout Length	Spout Height	Mfr. Model	Item No.
Chicago Faucets	HyTronic	Cast Brass	0.5 gpm	Laminar	6V Lithium CRP2	5 3/8 in	12 in	116.204.AB.1	5UTW7
Sloan	Optima	Brass	2.2 gpm	Laminar	Electronic, Plug in Transformer	10 1/4 in	10 1/4 in	ETF500-P	5YJRO
Zurn	AquaSense	Brass	0.5 gpm	Laminar	Battery	5 3/8 in	12 in	Z6922-XL	468D22