

# PLUMBING

## Glass Filler, Bar Sink, Laundry and Eyewash Faucets

Scan. Order. Done.  
Details on page A1.



For information on faucet spout shapes, see page 2614.



### Single-Hole Wall-Mount Glass Fillers

Glass fillers install into one hole on a vertical surface such as a wall. They provide a narrow stream of water for filling drinking glasses or water bottles. Straight-spout faucets extend straight out from the body of the faucet. Glass-activated push lever handles except 26Y282 is metering requiring users to push to start, shuts off automatically. Chrome finish.



Chicago Faucets  
41N760



Metering  
Chicago Faucets  
26Y282



T&S  
2MCU2

Brand	Series	Faucet Handle Material	Faucet Body Material	Flow Rate	Flow Outlet Type	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
Chicago Faucets	312	Metal	Cast Brass	1 gpm	Laminar	4 3/4 in	1 1/2 in	Yes	312-ABCP	41N760
	324	Metal	Cast Brass	0.25 gpm	Laminar	4 in	1 1/2 in	Yes	324-665PSHABCP	26Y282
	712	Metal	Cast Brass	1 gpm	Aerated	4 in	9 3/4 in	No	712-ABCP	41N760
T&S Brass	—	Plastic	Brass	0.25-2.25 gpm	Aerated	4 1/8 in	4 3/8 in	Yes	B-1200	2MCU2



Single-Hole  
Chicago Faucets  
48YD70



Two-Hole Deck-Mount  
Moen  
6MPT6



Two-Hole Wall-Mount  
T&S  
10C480



Three-Hole  
Moen  
52JN02



Two-Hole Off Center  
Delta  
4NLK5

### Gooseneck Bar Sink Faucets

Bar sink faucets are compact with a tall spout. Install on small sinks in tight areas where food is prepared or beverages are served, such as bars and restaurants. Feature metal faucet handles, aerated flow spouts, and chrome finish. **Single-Hole Faucets** install into one hole on a bar sink or counter. **Two-Hole Centerset Faucets** install onto sinks, counters, walls or other vertical or horizontal surfaces that have with two centered holes that are 4" apart when measured from center-of-hole to center-of-hole. **Three-Hole Widespread Faucets** install into a sink or counter with three holes where the outermost holes are 8" apart when measuring from center-of-hole to center-of-hole.



Brand	Series	No. of Handles	Faucet Body Material	Flow Rate	Flow Outlet Type	Spout Length	Spout Height	ADA Compliance	Mfr. Model	Item No.
<b>Single Hole Deck-Mount Lever Handle</b>										
Chicago Faucets	50	2	Cast Brass	1.5 gpm	Aerated	5 1/4 in	13 3/4 in	Yes	50-E35-XKABCP	48YD70
T&S Brass	—	2	Brass	8.67 gpm	Aerated	5 1/4 in	13 1/2 in	No	B-0300	4XKK7
<b>Two-Hole Centerset Deck-Mount Wristblade Handle</b>										
Moen	M-Bition	2	Cast Metal	1.2 gpm	Aerated	4 3/4 in	8 3/4 in	Yes	8948	6MPT6
	M-Bition	2	Metal	1.5 gpm	Aerated	4 3/4 in	10 1/2 in	Yes	8938	4NEJ5
<b>Two-Hole Centerset Wall-Mount Lever Handle</b>										
T&S Brass	—	2	Brass	13.8 gpm	Laminar	10 3/4 in	6 3/4 in	Yes	B-0341	10C480
<b>Two-Hole Off Center-Right Deck-Mount Joystick Handle</b>										
Delta	Classic	1	Brass	1.5 gpm	Aerated	5 in	10 in	Yes	1903-DST	4NLK5
<b>Three-Hole Widespread Deck-Mount Wristblade Handle</b>										
Moen	M-Dura	2	Brass	1.5 gpm	Aerated	5 1/4 in	10 3/4 in	Yes	8248	52JN02
	M-Dura	2	Brass	1.5 gpm	Aerated	8 in	13 1/4 in	Yes	8225smf15	46KK55
Moen	M-Dura	2	Brass	2.2 gpm	Aerated	8 in	13 1/4 in	Yes	8225	6MPT7



Deck-Mount  
American Standard  
448N36



Deck-Mount  
T&S  
5NRE9



Wall-Mount  
T&S  
5NRF5



Wall-Mount  
Zurn  
46CE16

### Two-Hole Laundry Sink Faucets

Faucets provide water for washing laundry and fabrics in commercial and residential laundry facilities. These chrome-finish faucets have a short low-arc-spout and two handles. **Centerset Faucets** install onto horizontal (deck-mount) or vertical (wall-mount) surfaces with two centered holes that are 4" apart when measured from center-of-hole to center-of-hole. **Widespread Faucets** install into walls or vertical surfaces that have two centered holes that are 8" apart when measured from center-of-hole to center-of-hole. ADA Compliant.



Brand	Series	Faucet Handle Type	Faucet Body Material	Flow Rate	Mounting Type	Flow Outlet Type	Spout Length	Spout Height	Mfr. Model	Item No.
<b>Centerset Deck-Mount</b>										
American Standard	7074	Lever	Cast Brass	1.5 gpm	Deck	Laminar	7 1/2 in	4 3/4 in	7074240.002	448N36
	—	Lever	Brass	2.2 gpm	Deck	Aerated	6 in	—	B-1120	5NRE8
	—	Lever	Brass	2.2 gpm	Deck	Aerated	6 in	6 1/8 in	B-1110	5NRE9
T&S Brass	—	Lever	Brass	2.2 gpm	Deck	Aerated	8 in	6 3/4 in	B-1121	4XKJ9
	—	Lever	Brass	18.39 gpm	Deck	Aerated	12 in	10 in	B-0221	4XKK5
	—	Lever	Brass	18.39 gpm	Deck	Aerated	18 in	12 in	B-0220	4XKK6
	—	Lever	Brass	23.09 gpm	Deck	Aerated	6 in	8 in	B-0222	4XKK4
<b>Centerset Wall-Mount</b>										
T&S Brass	—	Lever	Brass	2.2 gpm	Wall	Aerated	6 in	5 1/8 in	B-1115	5NRF5
	—	Big-Flo	Cross	Brass	Wall	Aerated	12 in	8 1/2 in	B-0290	5NRF2
<b>Widespread Wall-Mount</b>										
	—	Lever	Brass	2.2 gpm	Wall	Aerated	6 in	—	B-0230-01	5NRF1
T&S Brass	—	Lever	Cast Brass	23.09 gpm	Wall	Aerated	12 in	7 1/2 in	B-0231	5NRF0
Zurn	AquaSpec	Lever	Brass	0.5 gpm	Wall	Aerated	9 1/2 in	6 3/4 in	Z843J1-XL-3F	46CE16



### SPEAKMAN

#### Service Sink Faucet with Eyewash

Eyewash (2WLL7) is attached directly to faucet's cold water integral stop port. Faucet and eyewash can operate independently. Includes eyewash, drench hose with twin plastic spray heads, and wall-mount bracket. Chrome finish.

Series	Flow Rate	Faucet Spout Shape	Connection	No. of Holes	Mounting Hole Center to Center	Spout Length	Mfr. Model	Item No.
Eyesaver	2.66 gpm	Straight	1/2 in FNPT	2	8 in	9 in	SEF-9000	2WLL7