60 Pieces

5UPV1

H

## 

## Air & Non-Potable Water Push-to-Connect Tube Fitting Kits

These fittings, also called push fittings, connect tubing without the use of special tools, glue, soldering, or unions. Tubing is pushed into the fitting and held in place by a grab ring which disconnects the tubing for frequent changes. Included fitting shapes: connectors, elbows, tees and unions. Nickel-plated brass material.

	my niu	3			
t	Compatible Tube Sizes Included	Max. Operating Pressure	Max. Operating Temp.	No. of Pieces	ltem No.
es -	1/8 in			60	5UPV0
	1⁄4 in			60	5UPV1
	3% in			60	5UPV2
	1/2 in	190 psi	200 °F	36	5UPV3
	6 mm			60	5UPH7
	8 mm			60	5UPH8
	10 mm			36	5UPH9



00000 00000 00000

ובכובה בבכורה הכור

22227 444

## **Potable Water Push-to-Connect Tube Fittings**

These fittings, also called push fittings, connect tubing without the use of special tools, glue, soldering, or unions. Tubing is pushed into the fitting and held in place by a grab ring which disconnects the tubing for frequent changes.

**Standard Brass**—Fittings are made of an alloy of copper and zinc. They're strong and resist corrosion from water, heat, acids, minerals, and peaty soils. **Polysulfone**—(PSU) tube fittings are used with potable water where repeated sterilization is required including medical and food processing applications. They are made from a high-temperature thermoplastic material that resists degradation from hot water and steam. White color

	Connec.: Push-to- Connect x	For Tube OD	Pipe Size	Max. Oper. Press. (PSI)	Max. Oper. Temp. (°F)	Body Mat.*	Brand	ltem No.		Connec.: Push-to- Connect x	For Tube OD	Pipe Size	Max. Oper. Press. (PSI)	Max. Oper. Temp. (°F)	Body Mat.*	Brand	ltem No.
tandard Brass 0° Elbow	Push-to-Co	nnect Tube Fit	tings						Straight Adapte	r	1⁄2 in	1/2 in	200	200	BR	Sharkbite	19F86
	Push-to-	1/2 x 1/2 in 3/4 x 3/4 in 1 x 1 in	-	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	19F855	Ø	FNPT	3/4 in 1 in	<sup>3/4</sup> in 1 in	200 200 200	200 200 200	BR BR	Sharkbite	19F87
6	Connect									MNPT	1/2 in 3/4 in 1 in	1/2 in 3/4 in 1 in	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	19F85 19F87
)° Elbow Adap	iter										2 x 2 in	—	200 200	200	BR BR		
	FNPT	1⁄2 in	1⁄2 in	200	200	BR	Sharkbite	19F879	0	Push-to- Connect	1/2 x 1/2 in 3/4 x 3/4 in 1 x 1 in	-	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	45RF
									Straight Connector								
m										Push-to- Connect	1/2 x 1/2 in 3/4 x 3/4 in 1 x 1 in	-	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	19F8
	MNPT	3⁄8 in	⅔ in	200	200	BR	Sharkbite	105007	Straight Reduci	ng Connec	tor						
	WINPT	98 111 98 11	98 111	200	200	DR	Sharkulle	19290/	6	Push-to- Connect	3% x 3% in 3% x 1/2 in 1 x 3% in	-	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	19F8
)° Swivel Elbo	w Adapter								Straight Slip Co	nnector							
ÍÌ.	Push-to-	½ x ½ in 1½ x 1½ in	_	200 200	200 200	BR BR	Sharkbite Sharkbite			Push-to- Connect	<u>3/4 x 3/4 in</u> <u>1 x 1 in</u> 1 1/4 x 1 1/4 in	-	200 200 200	200 200 200	BR BR BR	Sharkbite Sharkbite Sharkbite	19F8
1	Connect								Straight Transit	ion Connec	tor						
									60	Push-to- Connect	1/2 x 1/2 in 3/4 x 3/4 in	-	200 200	200 200	BR BR	Sharkbite Sharkbite	
all Valve		1 x 1 in	_	200	200	BR	Sharkbite	49EL59	Tee								
10	Push-to-	11/4 x 11/4 in	—	200	200	BR	Sharkbite	499M51			1/2 x 1/2 x 1/2 in	_	200	200	BR	Sharkbite	19F8
6	Connect								5	Push-to- Connect	<sup>3</sup> / <sub>4</sub> x <sup>3</sup> / <sub>4</sub> x <sup>3</sup> / <sub>4</sub> in 1 x 1 x 1 in	=	200 200	200 200	BR BR	Sharkbite Sharkbite	
d Stop		1⁄2 in	_	200	200	BR	Sharkbite	19F856	Polysulfone Pus	sh-to-Conn	ect Tube Fitting	s					
CA		3⁄4 in	_	200	200	BR	Sharkbite	19F861	90° Elbow		1/2 x 1/2 in	_	160	200	PL	John G.	16T7
	Push-Fit	1 in 1½ in	_	200 200	200 200	BR BR	Sharkbite Sharkbite	19F870			3/4 x 3/4 in	_	160	200	PL	John G.	16T7
ducing Tee		2 in — 200 200 BR Sharkbite 499M5	499M59		Push-to- Connect	<sup>3</sup> ⁄ <sub>4</sub> x <sup>3</sup> ⁄ <sub>4</sub> in	_	250	75	PSU	Watts	1DA					
		3⁄4 x 1⁄2 x 3⁄4 in	_	200	200	BR	Sharkbite	19F867	Straight Adapte	r							
The second	Push-to- Connect	1 x ¾ x 1 in	_	200	200	BR	Sharkbite	19F893	ociargin Mddpte	•	1½ in	1⁄2 in	160	200	PL	John G.	16T7
	Juniout	1¼ x ¾ x 1¼ in	_	200	200	BR	Sharkbite	499M55		MNPT	1⁄2 in	1⁄2 in	250	75	PSU	Watts	1DA

## Potable Water Push-to-Connect Tube Fitting Kits

Push-to-connect tube fitting kits contain an assortment of brass fittings suitable for use with potable water applications.

Specific	Fitting Shapes	Included	Sizes	tible Tube Included	Max. Operating Pressure	Max. Operating Temp.	Fitting Bod Material	ly No. of Pieces	Item No.
Conr	nector, Dismoun	t Clip		n, 3/4 in 74 in	000 noi	200 °F	Brass	3	19F901 19F910
Connector, Coup Tong, Elbow,	ling, Disconnect Plug, Reducing		ect	_	200 psi	200 F	DZR Brass	s 26	19F868
Compatible Pipe Size	Compatible Tube Size	Material	ltem No.	Comp	atible Pipe S		be Size	Material	ltem No.
Sharkbite Discor	nect Clips			Sharkbi	te Disconnec	t Tongs & To	ols		
1/2 in	1/2 in		1DJC4	3/8 in, 1/2	in, 5% in, 3/4 in	1, 1 in -		Copper/Steel	793UM6
3⁄4 in	3⁄4 in	Disatia	1DJC6	1/2 in		1/2	źin S	tainless Steel	52JR56
1/2 in	1/2 in	Plastic -	45RF69		3⁄4 in	3/.	in S	tainless Steel	52JR57
1 in	1 in		45RF71		1 in	1	in S	tainless Steel	52JR58



SharkBite

Sign in to Grainger.com® to see YOUR Pricing and MORE