

PVC Drain, Waste & Vent Pipe Fittings, Schedule DWV & 40

- White color
- Tees read: run x run x outlet

Convey effluent streams with gravity, such as black water or gray water waste. Lightweight PVC is nonflammable with good electrical insulation, and its smooth interior walls resist scaling. Not for use in pressure applications.

Socket x socket—Also called slip or hub fittings, the socket ends fit over the end of a PVC pipe and require glue or adhesive to secure the connection.

Socket x spigot—Include socket (hub or slip) end that fits over a pipe and a spigot (also known as street) end that fits inside a socket. Use glue or adhesive to secure the connection.

Spigot x threaded—A spigot end connects to another fitting and requires solvent cement to seal connection. Threaded connections use PTFE tape to secure seal.

Threaded x threaded—Threaded on all connection ends. Use PTFE tape to secure seal.


















Spigot x threaded—Spigot end connects to another fitting, and requires solvent cement to seal connection. Threaded ends use PTFE tape to secure seal.

Spigot x spigot—Fit inside sockets on other fittings. Spigots require solvent cement to seal connections.





















Socket x socket—Socket ends fit over the ends of pipe and require glue or adhesive to secure the connection.

Socket x threaded—Socket ends require glue or adhesive to secure connection. Threaded ends use PTFE tape to secure seal.

SCHEDULE DWV: Thinner walls are not intended for pressure applications.

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.	Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.	Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.
Socket x Socket Schedule DWV Pipe Fittings					Socket x Spigot Schedule DWV Pipe Fittings					Spigot x Threaded Schedule DWV Pipe Fittings				
22-1/2° Elbow					Bull Nose Tee					90° Short Turn Elbow				
	6 in x 6 in	F Socket	73 to 180	56GX24		4 in x 4 in x 4 in	F Socket	73 to 180	56GX30		4 in x 4 in	F Socket	73 to 180	56GX45
						6 in x 6 in x 6 in	F Socket	73 to 180	56GX31					
45° Elbow					Coupling					Adapter				
	3 in x 3 in	F Socket	73 to 180	56GX20		3 in x 3 in	F Socket	73 to 180	56GX09		4 in x 1/4 in	F Socket x M Spigot	73 to 180	56GX47
	4 in x 4 in	F Socket	73 to 180	56GX21		4 in x 4 in	F Socket	73 to 180	56GX10					
	6 in x 6 in	F Socket	73 to 180	56GX22		6 in x 6 in	F Socket	73 to 180	56GX15					
90° Long Sweep Elbow					Sanitary Tee					Adapter Bushing				
	4 in x 4 in	F Socket	73 to 180	56GX44		3 in x 3 in x 3 in	F Socket	73 to 180	56GX27		4 in x 2 in	F Socket x F Spigot	73 to 180	56GX49
						4 in x 4 in x 4 in	F Socket	73 to 180	56GX28					
						6 in x 6 in x 6 in	F Socket	73 to 180	56GX29					
90° Sanitary Elbow					Two-Way Cleanout Tee					Reducing Bushing				
	3 in x 3 in	F Socket	73 to 180	56GX41		4 in x 4 in x 4 in	F Socket	73 to 180	56GX33		4 in x 4 in	M Spigot x F Socket	73 to 180	56GX19
	4 in x 4 in	F Socket	73 to 180	56GX42										
	6 in x 6 in	F Socket	73 to 180	56GX43										
90° Short Turn Elbow					Wye					Spigot x Threaded Schedule DWV Pipe Fittings				
	4 in x 4 in	F Socket	73 to 180	56GX23		4 in x 4 in x 4 in	F Socket	73 to 180	56GX25	Cleanout Adapter				
						6 in x 6 in x 6 in	F Socket	73 to 180	56GX26		3 in x 3 in	M Spigot x FNPT	73 to 180	56GX32
											6 in x 6 in	M Spigot x FNPT	73 to 180	56GX34
Adapter					Socket x Spigot Schedule DWV Pipe Fittings									
	4 in x 4 in	F Socket	73 to 180	56GX35	45° Street Elbow									
						3 in x 3 in	F Socket x M Spigot	73 to 180	56GX38					
						4 in x 4 in	F Socket x M Spigot	73 to 180	56GX39					
						6 in x 6 in	F Socket x M Spigot	73 to 180	56GX40					

SCHEDULE 40 DWV: Fittings have thinner walls than Schedule 80, and are used in lower pressure flow applications.

Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.	Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.	Description	Fitting Pipe Size	Pipe Fitting Connection Type	Temp. Range (°F)	Item No.	
Threaded x Threaded Schedule 40 DWV Pipe Fittings					Socket x Spigot Schedule 40 DWV Pipe Fittings					Reducing Adapter					
Cleanout Plug					22-1/2° Elbow										
	1 1/2 in	MNPT	0 to 140	1WKH6		4 in x 4 in	M Spigot x F Socket	-20 to 140	1WKL3		2 in x 1 1/2 in	F Socket x M Spigot	-20 to 140	1WKK1	
	2 in	MNPT	0 to 140	1WKH7							4 in x 3 in	F Socket x M Spigot	-20 to 140	1WKJ9	
	3 in	MNPT	0 to 140	1WKH8	22-1/2° Street Elbow					Reducing Bushing					
	4 in	MNPT	0 to 140	1WKH9		1 1/2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1CNX4		4 in x 1 1/2 in	F Socket x M Spigot	73 to 180	56GX48	
	6 in	MNPT	0 to 140	1WKW5		2 in x 2 in	M Spigot x F Socket	-20 to 140	1CNX5						
Flush Cleanout Plug					45° Street Elbow					Trap Adapter					
	4 in	MNPT	0 to 140	1WKT1		3 in x 3 in	M Spigot x F Socket	-20 to 140	1CNX6		1 1/2 in x 1 1/2 in	M Spigot x M Socket	-20 to 140	1CNY1	
											1 1/2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKU9	
Slip Joint Nut					90° Street Elbow					Socket x Threaded Schedule 40 DWV Pipe Fittings					
	1 1/2 in	NPSM	-20 to 140	1WJP2		1 1/2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKC9	Female Adapter					
											1 1/2 in x 1 1/2 in	FNPT x F Socket	-20 to 140	1WJY2	
Spigot x Threaded Schedule 40 DWV Pipe Fittings					90° Street Elbow					Male Adapter					
Cleanout Adapter						1 1/2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKA8		2 in x 2 in	M Spigot x F Socket	-20 to 140	1WKF1	
	1 1/2 in x 1 1/2 in	M Spigot x FNPT	-20 to 140	1WKF9		2 in x 2 in	M Spigot x F Socket	-20 to 140	1WKB1		1 1/2 in x 1 1/2 in	FNPT x F Socket	-20 to 140	1WKG4	
	2 in x 2 in	M Spigot x FNPT	-20 to 140	1WKG1		3 in x 3 in	M Spigot x F Socket	-20 to 140	1WKB3		1 1/2 in x 1 1/2 in	MNPT x F Socket	-20 to 140	1WKG5	
	3 in x 3 in	M Spigot x FNPT	-20 to 140	1WKG2		4 in x 4 in	M Spigot x F Socket	-20 to 140	1WKB6		2 in x 2 in	MNPT x F Socket	-20 to 140	1WKG6	
	4 in x 4 in	M Spigot x FNPT	-20 to 140	1WKG3		6 in x 6 in	M Spigot x F Socket	-20 to 140	1WKB4		3 in x 3 in	MNPT x F Socket	-20 to 140	1WKG7	
	6 in x 6 in	F NPT x F NPT	-20 to 140	3JWE8	Adapter					Reducing Bushing					
Cleanout Adapter with Plug						2 in x 2 in	M Spigot x F Socket	-20 to 140	1WKJ6		1 1/2 in x 1 1/2 in	MNPT x F Socket	-20 to 140	1WKG9	
	1 1/2 in x 1 1/2 in	M Spigot x FNPT	-20 to 140	1WKR6		3 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKF4		1 1/2 in x 1 1/2 in	MNPT x F Socket	-20 to 140	1WKG5	
	2 in x 2 in	M Spigot x FNPT	-20 to 140	1WKR7		3 in x 2 in	M Spigot x F Socket	-20 to 140	1WKF5		2 in x 2 in	MNPT x F Socket	-20 to 140	1WKG6	
	3 in x 3 in	M Spigot x FNPT	-20 to 140	1WKR8		4 in x 2 in	M Spigot x F Socket	-20 to 140	1WKF7		3 in x 3 in	MNPT x F Socket	-20 to 140	1WKG7	
	4 in x 4 in	M Spigot x FNPT	-20 to 140	1WKR9		4 in x 3 in	M Spigot x F Socket	-20 to 140	1WKF6		4 in x 4 in	MNPT x F Socket	-20 to 140	1WKG8	
	6 in x 6 in	M Spigot x FNPT	-20 to 140	1WKR6	Flush Bushing										
Male Adapter						1 1/2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	3JWF6						
	1 1/2 in x 1 1/2 in	M Spigot x MNPT	-20 to 140	1WKU5		2 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKF2						
	2 in x 2 in	M Spigot x MNPT	-20 to 140	1WKU4		3 in x 1 1/2 in	M Spigot x F Socket	-20 to 140	1WKF4						
	3 in x 3 in	M Spigot x MNPT	-20 to 140	3JWF4		3 in x 2 in	M Spigot x F Socket	-20 to 140	1WKF5						
	4 in x 4 in	M Spigot x MNPT	-20 to 140	1WKR9		4 in x 2 in	M Spigot x F Socket	-20 to 140	1WKF7						
	6 in x 6 in	M Spigot x FNPT	-20 to 140	1WKR6		4 in x 3 in	M Spigot x F Socket	-20 to 140	1WKF6						
Spigot x Spigot Schedule 40 DWV Pipe Fittings						6 in x 4 in	M Spigot x F Socket	-20 to 140	1WKW4						
Cleanout Plug															
	4 in	Spigot	0 to 140	56GX36											
	6 in	MNPT	0 to 140	56GX37											
	3 in	Spigot	0 to 140	56GX50											

CONTINUED