



**Fan With Drive Package**



**Fan without Drive Package**



**Belt-Drive Panel Exhaust Fans**

• Max. inlet temp.: 104°F

Used to pull stale air, heat, odors, and some moisture out of indoor spaces to reduce airborne contaminants and improve indoor air quality. Fans are typically quieter and provide more control over the fans' blade speed and airflow than direct-drive panel exhaust fans. Models can be mounted vertically or horizontally on the ceiling for use in air supply and air intake applications. They are better suited than direct-drive fans for high airflow (≥ 2000 cfm) or high static pressure (≥ 0.50") applications. Fans mount to an exterior wall and are suitable for factories, warehouses, light manufacturing plants, schools, storage facilities, and other indoor areas where fans cannot be mounted to the ceiling.

Blade Dia.	Name-plate Voltage (AC)	Phase	Motor Speed (RPM)	Motor HP	Exhaust Airflow @ 0.000 in SP (cfm)	Noise Level @ 0.000 in SP@5ft (sones)	Square Opening Req. (in.)	Open Dripproof Motor Item No.	Totally Enclosed Motor Item No.
<b>Fans with Drive Package</b>									
<b>Aluminum Blade &amp; Steel Frame</b>									
24 in	115/208-230V	1	1,725	1/8	5,608	14.2	26 1/2	7AR54	7AR55
		1	1,725	1/2	6,469	17.7	26 1/2	7M878	7M882
		1	1,725	2	8,115	24	26 1/2	7M880	7M884
	115/230V	1	1,725	2	14,990	31	32 1/2	7M895	—
		1	1,725	3/4	10,798	19.7	32 1/2	7M892	—
		3	1,725	1/2	6,469	17.7	26 1/2	—	7M888
208-230/460V	3	1,725	3/4	7,357	21	26 1/2	—	7M889	
	3	1,760	1	8,115	24	26 1/2	7M886	—	
	3	1,760	1	8,115	24	26 1/2	—	7M890	
26 in	208-230/460V	3	1,725	3/4	14,345	19.7	38 1/2	—	7AR62
		1	1,725	1/2	9,474	16.3	32 1/2	7AR57	7AR58
		1	1,725	3/4	10,798	19.7	32 1/2	—	7M896
30 in	115/208-230V	1	1,725	3/4	10,798	19.7	32 1/2	—	7M899
		1	1,725	1/2	14,990	31	32 1/2	—	7AR59
		3	1,725	1/2	9,474	16.3	32 1/2	—	7M895
	208-230/460V	3	1,725	3/4	10,798	19.7	32 1/2	—	7M8A5
		3	1,760	1	11,901	23	32 1/2	7M8A1	—
		3	1,750	1 1/2	13,639	27	32 1/2	7M8A2	7M8A7
230/460V	3	1,760	1	11,901	23	32 1/2	—	7M8A6	
	3	1,745	2	14,990	31	32 1/2	7M8A3	7M8A8	

Blade Dia.	Name-plate Voltage (AC)	Phase	Motor Speed (RPM)	Motor HP	Exhaust Airflow @ 0.000 in SP (cfm)	Noise Level @ 0.000 in SP@5ft (sones)	Square Opening Req. (in.)	Open Dripproof Motor Item No.	Totally Enclosed Motor Item No.		
36 in	115/208-230V	1	1,725	3/4	14,345	19.7	38 1/2	—	7AR61		
		1	1,725	1	15,803	23	38 1/2	7M8B0	7M8B3		
		1	1,725	1 1/2	18,117	28	38 1/2	7M8B1	7M8B4		
		1	1,725	2	19,922	31	38 1/2	7M8B2	7M8B5		
		1	1,725	3/4	14,345	13	38 1/2	7AR60	—		
		1	1,725	3	22,791	38	38 1/2	—	7M8B6		
	208-230/460V	3	1,750	1 1/2	18,117	28	38 1/2	7M8B8	7M8C3		
		3	1,760	1	15,803	23	38 1/2	7M8B7	—		
		3	1,770	3	22,791	38	38 1/2	7M8C0	—		
		3	1,745	5	26,979	50	38 1/2	—	7M8C6		
		3	1,760	1	15,803	23	38 1/2	—	7M8C2		
		3	1,745	2	19,922	31	38 1/2	7M8B9	7M8C4		
42 in	230/460V	3	1,740	3	22,791	38	38 1/2	—	7M8C5		
		3	1,760	5	26,979	50	38 1/2	7M8C1	—		
		1	1,725	1	18,024	17.8	44 1/2	7AR63	7AR64		
		1	1,725	1 1/2	20,652	21	44 1/2	7M8C7	7M8C9		
		1	1,725	2	22,735	24	44 1/2	7M8C8	7M8D0		
		1	1,740	3	26,012	31	44 1/2	—	7M8D1		
	208-230/460V	3	1,750	1 1/2	20,652	21	44 1/2	7M8D2	7M8D7		
		3	1,760	1	18,024	17.8	44 1/2	7AR65	—		
		3	1,770	3	26,012	31	44 1/2	7M8D4	—		
		3	1,750	5	30,825	41	44 1/2	—	7M8E0		
		3	1,760	1	18,024	17.8	44 1/2	—	7AR66		
		3	1,745	2	22,735	24	44 1/2	7M8D3	7M8D8		
48 in	230/460V	3	1,765	3	26,012	31	44 1/2	—	7M8D9		
		3	1,760	5	30,825	41	44 1/2	7M8D5	—		
		1	1,725	1 1/2	26,377	24	50 1/2	7AR67	7AR68		
		1	1,725	2	28,995	27	50 1/2	7M8E2	—		
		1	1,725	3	33,223	32	50 1/2	—	7M8E4		
		3	1,750	1 1/2	26,377	24	50 1/2	7AR69	7AR70		
	208-230/460V	3	1,770	3	33,223	32	50 1/2	7M8E6	—		
		3	1,765	3	33,223	32	50 1/2	—	7M8F1		
		3	1,750	5	39,364	40	50 1/2	—	7M8F2		
		3	1,770	7 1/2	45,053	49	50 1/2	—	7M8F3		
		3	1,745	2	28,995	27	50 1/2	7M8E5	7M8F0		
		3	1,760	5	39,364	40	50 1/2	7M8E7	—		
54 in	115/230V	1	1,725	3	33,602	37	56 1/2	—	7M8F6		
		1	1,725	3	33,602	37	56 1/2	—	7M8G2		
		1	1,725	3 1/2	45,573	48	56 1/2	7M8E8	7M8G3		
		1	1,725	4	45,573	48	56 1/2	7M8E9	—		
		1	1,725	5	45,573	48	56 1/2	—	7M8F5		
		1	1,725	5 1/2	45,573	48	56 1/2	—	7M8F6		
	208-230/460V	3	1,750	5	39,833	37	56 1/2	—	7M8G2		
		3	1,770	7 1/2	45,573	48	56 1/2	—	7M8G3		
		3	1,745	2	29,332	22	56 1/2	7AR73	7AR74		
		3	1,765	3	33,602	27	56 1/2	—	7M8G1		
		3	1,760	5	39,833	37	56 1/2	7M8F7	—		
		3	1,770	7 1/2	45,573	48	56 1/2	7M8F8	—		
60 in	230/460V	3	1,770	10	50,124	59	56 1/2	7M8F9	—		
		3	1,750	10	50,124	59	56 1/2	—	7M8G4		
		3	1,750	5	48,356	35	62 1/2	—	7M8H1		
		3	1,770	7 1/2	55,335	45	62 1/2	—	7M8H2		
		3	1,760	5	48,356	35	62 1/2	7M8G6	—		
		3	1,770	7 1/2	55,335	45	62 1/2	7M8G7	—		
	115/230V	1	1,725	10	60,918	54	62 1/2	—	7M8H3		
		1	1,725	10	60,918	54	62 1/2	7M8G8	—		
		1	1,765	15	69,692	74	62 1/2	—	7M8H4		
		1	1,770	15	69,692	74	62 1/2	7M8G9	—		
		<b>Steel Blade &amp; Steel Frame</b>									
		20 in	115/208-230V	1	1,725	1/4	3,581	16.2	22 1/2	7AD16	7AD18
1	1,725			1/2	4,404	14.3	22 1/2	7AD52	7AD54		
1	1,725			1/2	4,587	19.7	22 1/2	7AD24	7AD26		
1	1,725			1/2	5,550	17.9	22 1/2	7AD60	7AD62		
1	1,725			3/4	6,348	22	22 1/2	7AD64	—		
1	1,725			3/4	5,550	17.9	22 1/2	—	7AD63		
208-230/460V	3		1,725	1/2	8,734	27	26 1/2	7M7W0	—		
	1		1,725	1/4	4,826	17.3	26 1/2	7CC73	7CC74		
	1		1,725	1/4	5,292	21	26 1/2	7CC76	7CC77		
	1		1,725	1/2	6,039	12.7	26 1/2	7M7V7	7M7W2		
	1		1,725	1/2	6,950	14.7	26 1/2	—	7M7W3		
	1		1,725	3/4	7,927	19.8	26 1/2	—	7M7W4		
24 in	115/208-230V	1	1,725	3/4	7,069	30	26 1/2	—	7CC83		
		1	1,725	1 1/2	10,002	46	26 1/2	7AR52	—		
		1	1,725	1	8,734	27	26 1/2	—	7M7W5		
		1	1,725	3/4	7,927	19.8	26 1/2	7M7V9	—		
		1	1,725	3/4	7,069	30	26 1/2	7CC82	—		
		3	1,725	1/2	6,175	24	26 1/2	—	7CC81		
	208-230/460V	3	1,725	3/4	7,069	30	26 1/2	7AD31	7CC84		
		3	1,725	3/4	7,927	19.8	26 1/2	—	7M7X1		
		3	1,760	1	8,734	27	26 1/2	7M7W7	—		
		3	1,725	1/2	6,175	24	26 1/2	7AD30	—		
		3	1,760	1	8,734	27	26 1/2	—	7M7Y2		
		1	1,725	1/4	7,069	13.2	32 1/2	7CC85	7CC86		
30 in	115/208-230V	1	1,725	1/2	7,713	14.6	32 1/2	7CC88	7CC89		
		1	1,725	1/2	8,867	17.8	32 1/2	7CC91	7CC92		
		1	1,725	1/2	9,829	15.4	32 1/2	7M7X4	7M7X9		
		1	1,725	3/4	11,169	18.3	32 1/2	—	7M7Y0		
		1	1,725	1	10,078	22	32 1/2	—	7CC95		
		1	1,725	1	11,061	26	32 1/2	7CC97	7CC98		
	208-230/460V	3	1,725	1	12,328	21	32 1/2	7M7X6	7M7Y1		
		1	1,725	1 1/2	14,098	26	32 1/2	—	7M7Y2		
		1	1,750	1 1/2	14,098	26	32 1/2	7M7X7	—		
		1	1,725	2	15,488	31	32 1/2	7M7X8	7M7Y3		
		1	1,725	3/4	10,078	22	32 1/2	7CC94	—		
		1	1,725	3/4	11,169	18.3	32 1/2	7M7X5	—		
230/460V	3	1,725	1/2	9,829	15.4	32 1/2	—	7M7Y7			
	3	1,725	3/4	10,078	22	32 1/2	7AD35	7CC96			
	3	1,750	1 1/2	14,098	26	32 1/2	7M7Y5	7M7Z0			
	3	1,760	1	12,328	21	32 1/2	7M7Y4	—			
	3	1,760	1	11,061	26	32 1/2	—	7CC99			
	3	1,760	1	12,328	21	32 1/2	—	7M7Y9			
3	1,745	2	15,488	31	32 1/2	7M7Y6	7M7Z1				

CONTINUED