



55KJ56



45RK41

FRIGIDAIRE LG FRIEDRICH

## Residential-Grade Window Air Conditioners

- Programmable, except 470D39 and 61CZ61
- 24-hr. timer, except 470D39 and 61CZ61

Units are made of residential-grade materials and have a decorative front grille that blends in with home interiors. Typically used to cool rooms in houses and apartments. Remote capability, except 470D39 and 61CZ61.

**Frigidaire**—FHW models are Wi-Fi capable.

**LG Commercial**—61CZ59 and 61CZ60 are Wi-Fi capable.

**Perfect Aire**—Feature a remote control with a built-in room temperature sensor that regulates room temperature around the remote, allowing the remote to become the thermostat.

**Friedrich**—CCW and CEW models can be installed in a window or through the wall. All units can be managed via Wi-Fi to allow centralized control of settings. Compatible with Amazon Alexa and Google Home. Units have Seacoast Protection to guard against corrosion.

- Quiet operation
- Auto restart
- Left/right reversible power cord
- Washable filter

Cooling Cap. (BtuH)	Average Coverage Area (sq ft)	CEER Rating	Refrigerant Type	Voltage (AC)	NEMA Plug Configuration	No. of Speeds	H	W	D	Chassis Type	Brand	Mfr. Model	Item No.
<b>Cooling Only</b>													
5,000	100 to 150	12.1	R-32	115V	LCDI, 5-15P	2	12 in	16 in	15 1/4 in	Fixed	Frigidaire	FFRE053WA1	61DD85
	100 to 150	11.0	R-410A	115V	LCDI, 5-15P	2	11 3/8 in	17 3/8 in	14 3/8 in	Fixed	Lg	LW5016	61CZ61
5,050	100 to 150	12.1	—	115V	LCDI, 5-15P	—	12 1/4 in	16 in	13 3/4 in	—	Perfect Aire	5PAC5000	60FV08
	100 to 150	11.0	R-32	115V	LCDI, 5-15P	2	11 3/8 in	16 1/8 in	16 1/4 in	Fixed	Frigidaire	FFRA051WA1	470D39
6,000	150 to 250	12.1	R-32	115V	LCDI, 5-15P	3	13 1/2 in	18 1/2 in	19 3/4 in	Slide Out	Friedrich	CCW06B10B	60RE42
	150 to 250	12.1	R-32	115V	LCDI, 5-15P	3	13 1/4 in	18 1/2 in	15 1/2 in	Fixed	Frigidaire	FFRE063WA1	61DD86
8,000	150 to 250	12.1	R-32	115V	LCDI, 5-15P	Variable	13 3/4 in	18 1/2 in	15 1/4 in	Fixed	Frigidaire	FHWW063WB1	55KJ55
	150 to 250	12.1	—	115V	LCDI, 5-15P	—	13 3/2 in	18 3/4 in	13 3/4 in	—	Perfect Aire	5PAC6000	60FV09
10,000	300 to 350	12.0	R-32	115V	LCDI, 5-15P	3	13 1/2 in	18 1/2 in	19 3/4 in	Slide Out	Friedrich	CCW08B10B	60RE43
	300 to 350	12	R-32	115V	LCDI, 5-15P	3	13 1/2 in	18 1/2 in	17 1/2 in	Fixed	Frigidaire	FFRE083WA1	61DD87
12,000	300 to 350	12.0	R-32	115V	LCDI, 5-15P	Variable	13 3/4 in	18 3/2 in	17 1/2 in	Fixed	Frigidaire	FHWW083WB1	55KJ55
	400 to 450	12.0	R-32	115V	LCDI, 5-15P	Variable	14 3/2 in	19 in	21 1/2 in	Fixed	Frigidaire	FHWW103WB1	55KJ55
15,000	400 to 450	12	R-32	115V	LCDI, 5-15P	3	14 1/2 in	19 in	21 1/2 in	Fixed	Frigidaire	FFRE103WA1	61DD88
	400 to 450	12.0	R-32	115V	LCDI, 5-15P	3	15 in	23 3/2 in	22 1/4 in	Slide Out	Lg	LW1017ERSM	61CZ60
18,000	450 to 550	12.0	R-410A	115V	LCDI, 5-15P	3	14 1/2 in	19 in	21 1/2 in	Fixed	Frigidaire	FFRE123WB1	61DD89
	450 to 550	12	R-32	115V	LCDI, 5-15P	3	14 1/2 in	19 in	21 1/2 in	Fixed	Frigidaire	FHWW123WB1	55KJ55
25,000	450 to 550	12.0	R-32	115V	LCDI, 5-15P	3	15 in	23 3/2 in	22 1/4 in	Slide Out	Lg	LW1217ERSM	61CZ59
	550 to 700	11.8	R-410A	115V	LCDI, 5-15P	3	18 in	23 3/2 in	25 3/2 in	Slide Out	Friedrich	CCW12B10	55HF06
15,100	550 to 700	11.8	R-32	115V	LCDI, 5-15P	Variable	17 1/2 in	23 3/2 in	25 3/2 in	Fixed	Frigidaire	FHWW153WB1	55KJ55
	550 to 700	11.8	R-32	115V	LCDI, 5-15P	3	17 1/2 in	23 3/2 in	25 3/2 in	Slide Out	Frigidaire	FFRE153WA1	61DD90
18,000	700 to 1000	11.8	R-410A	230V	LCDI, 6-20P	3	18 in	23 3/2 in	25 3/2 in	Slide Out	Friedrich	CCW18B30	55HF08
	700 to 1000	11.8	R-32	230V	LCDI, 6-15P	3	17 1/2 in	23 3/2 in	25 3/2 in	Slide Out	Frigidaire	FHWC183WB2	61DD91
28,000	1400 to 1500	10.3	R-32	230V	LCDI, 6-20P	3	18 3/2 in	26 1/2 in	26 1/2 in	Slide Out	Frigidaire	FHWC253WB2	61DD92
	1400 to 1500	9.4	R-32	230V	LCDI, 6-30P	3	18 3/2 in	26 1/2 in	26 1/2 in	Slide Out	Frigidaire	FHWC282WB2	61DD93
<b>Slider/Casement</b>													
8,000	300 to 350	11.2	R-410A	115V	LCDI, 5-15P	3	20 1/4 in	14 1/2 in	25 1/2 in	Fixed	Frigidaire	FHSC082WB1	45RK41
10,000	400 to 450	10.4	R-410A	115V	LCDI, 5-15P	3	20 1/4 in	14 1/4 in	23 1/2 in	Fixed	Frigidaire	FHSC102WB1	22XR23
<b>Cooling/Heating, Electric Heat</b>													
8,000	300 to 350	10.9	R-410A	115V	LCDI, 5-15P	3	14 3/2 in	19 3/4 in	23 3/4 in	Slide Out	Friedrich	CEW08B11A	55HF10
12,000	450 to 550	10.9	R-410A	230V	LCDI, 6-20P	3	14 3/2 in	19 3/4 in	23 3/4 in	Slide Out	Friedrich	CEW12B33	55HF11
18,000	700 to 1000	10.7	R-410A	230V	LCDI, 6-20P	3	18 in	23 1/2 in	25 3/2 in	Slide Out	Friedrich	CEW18B33	55HF12
24,000	1400 to 1500	9.4	R-410A	230V	LCDI, 6-20P	3	18 3/2 in	27 in	26 3/2 in	Slide Out	Friedrich	CEW24B33	55HF13
25,000	1400 to 1500	9.4	R-410A	230V	LCDI, 6-30P	3	18 3/2 in	26 1/2 in	26 1/2 in	Slide Out	Frigidaire	FHWE252WB2	61DD97
<b>Cooling/Heating</b>													
25,000	1400 to 1500	9.5	—	230V	LCDI, 6-30P	—	18 3/4 in	26 1/2 in	26 3/4 in	—	Perfect Aire	3PACH25000	379A66
<b>Cooling/Heating, Heat Pump with Electric Heat</b>													
8,000	300 to 350	9.8	R-410A	115V	LCDI, 5-15P	3	15 1/2 in	22 3/2 in	23 3/4 in	Slide Out	Frigidaire	FHWH082WA1	61DD94
11,000	400 to 450	9.8	R-410A	115V	LCDI, 5-15P	3	15 1/2 in	22 3/2 in	23 3/4 in	Slide Out	Frigidaire	FHWH112WB1	61DD95



426R65

5E169



## Air Conditioner Covers

Fit over the front grille or outside cabinet of an idle AC unit to block drafts, dirt, and allergens from entering a building.



Description	For Use With	Includes	Mfr. Model	Item No.
<b>Window Air Conditioner Covers, Frost King</b>				
Outdoor	Small Window Air Conditioners	(1) 18 in x 27 in x 16 in Polyurethane Reinforced Vinyl Air Conditioner Cover	AC2H	426R64
Outdoor	Large Window Air Conditioners	(1) 20 in x 28 in x 30 in Polyurethane Reinforced Vinyl Air Conditioner Cover	AC5H	426R65
Indoor	Small Window Air Conditioners	(1) 17 in x 25 in Quilted Fabric Air Conditioner Cover	AC9H	426R66
Indoor	Large Window Air Conditioners	(1) 20 in x 28 in Quilted Fabric Air Conditioner Cover	AC11H	426R67
<b>Through-the-Wall Air Conditioner Cover, Chill Stop'R</b>				
Indoor	Through-The-Wall Air Conditioners Up to 19 in H x 27 3/4 in W x 6 in D	—	1212-06	5E169

## Hazardous Location Through-the-Wall Air Conditioners

FRIEDRICH

■ Hot gas bypass for cooling operation at low ambient temps., down to 45°F (7°C) without freezing. Sealed motor and solid-state relays prevent sparking while cooling potentially hazardous environments. Can be used where flammable gases, vapors, and liquids are handled or used within enclosed containers or systems, but are not normally present in concentrations high enough to be ignitable. Commonly used to cool laboratories, control rooms, and storage areas. Have an e-coated coil and powder-coated steel cabinet to resist corrosion. Hardwired; 15A circuit with a time-delay fuse. Meet ANSI/UL 484 Room A/C, UL Listed for use in Class I, Div. 2, Groups A, B, C, and D, ISA 12.12.101, and NFPA 70.

Cooling Cap. (BtuH)	Average Coverage Area (sq ft)	EER	Refrigerant Type	Voltage (AC)	No. of Speeds	H	W	D	Mfr. Model	Item No.
14,000/14,500	550 to 700	9.7/9.7	R-410A	208/230V	1	15 1/8 in	25 1/8 in	27 3/8 in	SH15M30	22D138
21,000/21,000	700 to 1000	9.6/9.7	R-410A	208/230V	1	17 1/8 in	25 1/8 in	27 3/8 in	SH20M30	35MW48
—	—	8.5/8.8	R-410A	208/230V	—	17 1/8 in	25 1/8 in	27 3/8 in	SH24N30A	35MW49



22D138