

1-800-GRAINGER (472-4643)



Commercial-Grade Through-the-Wall Air Conditioners

- Programmable
- Auto restart
- Quiet operation
- Control panel lockout (ON-OFF)
- 24-hr. timer
- Anti-intrusion protection

These through-the-wall air conditioners are made for commercial-grade applications with components that withstand more demanding environments. They're commonly used for cooling offices, retail stores, multifamily buildings, barracks, and dorms. Units have remote capability and can be managed via Wi-Fi to allow centralized control of settings for one or more units. They're also compatible with Amazon Alexa and Google Home. New installations require a wall sleeve and fit in Friedrich and Fedders A and B 27" sleeves.



Cooling Cap.	Average Coverage Area	CEER Rating	Voltage	NEMA Plug Configuration	No. of Speeds	H	W	D†	Refrigerant Type	Mr. Model	Item No.
Cooling Only											
8,000 BtuH	300 to 350 sq ft	10.6	115V AC	LCDI, 5-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT08A10	494L39
10,000 BtuH	400 to 450 sq ft	10.6	115V AC	LCDI, 5-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT10A10	494L40
10,000 BtuH	400 to 450 sq ft	10.6	230V AC	LCDI, 5-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT10A30	494L41
12,000 BtuH	450 to 550 sq ft	9.5	115V AC	LCDI, 5-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT12A10B	494L42
12,000 BtuH	450 to 550 sq ft	9.5	230V AC	LCDI, 6-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT12A30B	494L43
16,000 BtuH	550 to 700 sq ft	9.3	230V AC	LCDI, 6-15P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WCT16A30	494L44
Cooling/Heating, Electric Heat											
10,000 BtuH	400 to 450 sq ft	10.6	230V AC	LCDI, 6-20P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WET10A33	494L36
12,000 BtuH	450 to 550 sq ft	9.5	230V AC	LCDI, 6-20P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WET12A33	494L37
15,400 BtuH	550 to 700 sq ft	9.3	230V AC	LCDI, 6-20P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WET16A33	494L38
Cooling/Heating, Heat Pump											
12,000 BtuH	450 to 550 sq ft	9.3	230V AC	LCDI, 6-20P	3	15 3/4 in	26 1/2 in	21 in	R-410A	WHT12A33	494L45
Accessories											
Architectural Grille										AG	3UD86
Drain Kit										DK	3UD88
Wall Sleeve, 16 3/4 in H x 27 in W x 16 3/4 in D, For Use With Wall master through the wall air conditioners										WSE	4PKZ3

† Depth includes front cover.

Residential-Grade Through-the-Wall Air Conditioners

- 24-hr. timer
- Auto restart
- Washable filter

Through-the-wall air conditioners are made of residential-grade materials and have a decorative front grille that blends in with home interiors. They're typically used to cool rooms in houses and apartments. Units include a remote control.

Friedrich—Units can be managed with Wi-Fi and are compatible with Amazon Alexa and Google Home. Units have Seacoast Protection to guard against corrosion. Trim kit is included to give units a finished appearance. Chassis fits 24 1/2" to 27" sleeves.

- Quiet operation

Frigidaire—Chassis fits most existing wall sleeves. New installations require Wall Sleeve Kit 5PP42.

- Programmable

GE—Units are ADA compliant. Wall sleeve is included.

- Programmable

Perfect Aire—Feature a remote control with a built-in room temperature sensor that regulates room temperature around the remote, allowing the remote to become the thermostat.

- Programmable



Cooling Cap.	Average Coverage Area	CEER Rating	Voltage - Plug Type	Fits Wall Sleeve Dimensions	Refrigerant Type	Brand	Mr. Model	Item No.	
Cooling Only									
8,000 BtuH	300 to 350 sq ft	10.6	115V AC, 5-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT08A10	494L30	
9,800/10,000 BtuH	400 to 450 sq ft	10.6	208/230V AC, 6-15P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FFTA103WA2	470D59	
10,000 BtuH	400 to 450 sq ft	10.6	115V AC, 5-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT10A10	494L31	
10,000 BtuH	400 to 450 sq ft	10.6	230V AC, 6-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT10A30B	494L32	
10,000 BtuH	400 to 450 sq ft	10.6	115V AC, 5-15P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FFTA103WA1	470D58	
11,700/12,000 BtuH	450 to 550 sq ft	10.5	208/230V AC, 6-15P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FFTA123WA2	470D62	
12,000 BtuH	450 to 550 sq ft	10.5	115V AC, 5-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT12A10	494L33	
12,000 BtuH	450 to 550 sq ft	10.5	230V AC, 6-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT12A30	494L34	
14,000/14,000 BtuH	550 to 700 sq ft	9.3	208/230V AC, 6-15P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FFTA142WA2	470D64	
14,000 BtuH	550 to 700 sq ft	9.3	230V AC, 6-20P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UCT14A30B	494L35	
14,000 BtuH	550 to 700 sq ft	9.5	230V AC, LCDI 6-15P	15 1/4 in x 25 1/2 in x 17 1/2 in	—	Perfect Aire	3PATW14002	216UV1	
Cooling/Heating, Electric Heat									
4,100/8,300 BtuH	300 to 350 sq ft	—	115V AC, 5-20P	15 1/2 in x 26 in x 16 1/2 in	R-410A	GE	AJEQ08AWH	6AMC2	
8,000 BtuH	300 to 350 sq ft	9.6	115V AC, 5-15P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UET08A11	494L26	
8,000 BtuH	300 to 350 sq ft	9.6	115V AC, 5-15P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FHTE083WA1	470D57	
9,800/10,000 BtuH	400 to 450 sq ft	9.6	208/230V AC, 6-20P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FFHT102WA2	470D60	
10,000 BtuH	400 to 450 sq ft	9.6	230V AC, 6-20P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UET10A33	494L27	
11,400/11,600 BtuH, 9,500/11,600 BtuH	400 to 450 sq ft	—	208/230V AC, 6-20P	15 1/2 in x 26 in x 16 1/2 in	R-410A	GE	AJEQ12DCH	6AMC3	
12,000 BtuH	450 to 550 sq ft	9.6	230V AC, 6-20P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UET12A33	494L28	
12,000 BtuH	450 to 550 sq ft	9.5	230 V, 6-20P	15 3/4 in x 25 5/8 in	R-410A	Frigidaire	FHTE123WA2	61DD99	
14,000/14,000 BtuH	550 to 700 sq ft	9.3	208/230V AC, 6-20P	15 1/4 in x 25 1/2 in x 16 in, 17 1/2 in or 22 in	R-410A	Frigidaire	FHTE143WA2	470D65	
14,000 BtuH	550 to 700 sq ft	9.3	230V AC, 6-20P	15 1/2 in x 25 1/2 in x 16 3/4 in	R-410A	Friedrich	UET14A33	494L29	
Accessories									
Architectural Grille, For Use with Friedrich Uni-Fit Through The Wall USC Sleeve							Friedrich	UXAA	46E371
Through-The-Wall AC Sleeve, 15 1/4 in Height x 25 1/2 in Width x 17 1/2 in Depth, For Use With Standard 24 in Thru-the-Wall AC Units							Perfect Aire	PAWS1	60K292
Wall Sleeve, 15 1/2 H x 25 1/2 W x 16 3/4 D, For Use With Friedrich Uni-Fit Air Conditioners							Friedrich	USC	2RLC7

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**