







3KG84



Weatherproof Outlet Boxes

Boxes are supplied with closure plugs and self-threading ground screw.



Mfr

Item

								½ IN HUBS		3/4 IN HUBS	
No. of		No. of						Mfr.	Item	Mfr.	Item
Gangs		Inlets	Material	Color	L	W	D	Model	No.	Model	No.
1	Standard	3	Aluminum	Gray	4.5 in	2.75 in	2 in	5320-0	3KG83	5324-0	3KG85
1	Standard	4	Aluminum	Gray	4.5 in	2.75 in	2 in	5321-0	3KG84	5330-0	2DCV4
1	Standard	5	Aluminum	Gray	4.5 in	2.75 in	2 in	5323-0	2DCV3 *	3332-0	2DCV6 *
1	Standard	5	Aluminum	Gray	4.5 in	2.75 in	2 in	5322-0	4YF70 †	5331-0	2DCV5 †
1	Extra Deep	3	Aluminum	Gray	4.5 in	2.75 in	2.63 in	5385-0	2DCW1	5386-0	2DCW2
1	Extension	0	Aluminum	Gray	_	2.75 in	1.0 in	5406-0	2DCW7	5406-0	2DCW7
1	Extension	6	Aluminum	Gray	5.25 in	3.5 in	1.5 in	5400-0	3KF67	_	
2	Standard	3	Aluminum	Gray	4.56 in	4.58 in	2 in	5333-0	4A243	5341-0	3KF89
2	Standard	4	Aluminum	Gray	4.56 in	4.58 in	2 in	5335-0	3KF88	5343-0	3KF90
2	Standard	5	Aluminum	Gray	4.56 in	4.58 in	2 in	5337-0	4A244 †	5345-0	4A245 †
2	Standard	5	Aluminum	Gray	4.56 in	4.56 in	2 in	_		5342-0	2DCV8 *
2	Standard	7	Aluminum	Gray	4.56 in	4.56 in	2 in	5340-0	2DCV7	5346-0	2DCV9
2	Extra Deep	5	Aluminum	Gray	4.5 in	4.5 in	2.78 in	_	_	5388-0	2DCW4
2	Extension	0	Aluminum	Gray	_	4.65 in	1.03 in	5407-0	4YF23	5407-0	4YF23
3	Extra Deep	7	Aluminum	Gray	6.38 in	4.5 in	2.63 in	_	_	5390-0	2DCW6
_	4 Closure Plugs	5	Aluminum	Gray	4 in	4 in	1.5 in	5361-0	2V567	_	_
- 1	Round with 4	5	Aluminum	Gray	4 in	4 in	1.5 in			5372-0	3KG86
	Closure Plugs		Alullillulli	uray	4 111	4 111	1.5 111	_	_	3372-0	SKUOU
0	Closure Plugs	_	Zinc	Gray	_	0.5	_	5269-0	30UJ94	_	_
0	Closure Plugs	_	Die-Cast Zinc	Gray	_	0.75	_	_	_	5270-0	30UJ95
1	Marine-Rated, FD	2	Thermoplastic	Yellow	5.92 in	2.77 in	3.53 in	_	_	HBL60CM83A	52HF24
1	Marine-Rated, FD	2	Thermoplastic Flastomer	Gray	5.9531 in	2.7656 in	3.5313 in	_	_	HBL6083	3D939

Nn. nf

Mounting





Weatherproof Covers and Plates

Protect outdoor switches or receptacles. Covers are self-closing. Gray color. Thermoplastic plates have stainless steel metallic parts and are corrosion-resistant. 3D249 has fiber shield to weatherproof toggle and lock switches. All are UL Listed and CSA Certified-Plates with model numbers ending in "WO" are UL Listed for wet and damp locations, cover open. All other plates are UL Listed for wet and damp locations, cover closed.



2DCV2



4YF68



6C595

Description	Lid Style	No. of Gangs	Orientation	Cover Material	Model	No.
Bell	Liu otyte	ualiys	Ullelitation	GUVET MATERIAL	Monei	NU.
Rectangular, 1-Hole		1			5186-0	3KF60
Rectangular, 3-Hole		i			5189-0	2V626
4 in Round Cluster - Covers					3103 0	20020
Round, 3-Hole	No Lid	1	Vertical	Cast Aluminum	5197-0	2V627
FS Cast Hub Device Boxes	110 2.0		vortioui	ouot / marrimann	0.07.0	
Single Receptacles, 1,406" dia.	(3) Self Closing	3	Vertical	Cast Zinc	5093-0	19L545
Blank-Box Mount	No Lid	3	Vertical	Cast Zinc	5177-0	19L546
FS or FD Weatherproof Boxes						
Lever Switch and Cover	No Lid	1	Vertical	Cast Zinc	5121-0	2DCV2
Duplex Receptacle	(2) Self Closing	1	Horizontal	Cast Zinc	5180-0	2V705
Duplex Receptacle	Self Closing	1	Vertical	Cast Aluminum	5146-0	3KH41
Duplex Cover, Padlockable	Self Closing	1	Vertical	Cast Aluminum	5027-0	4YF74
Single Receptacle, 1.406" dia.	Self Closing	1	Horizontal	Cast Aluminum	5152-0	3KH42
Single Receptacle, 1.406" dia.	Self Closing	1	Vertical	Cast Zinc	5155-0	2V704
GFCI Receptacle	Self Closing	1	Horizontal	Cast Aluminum	5101-0	3KH39
GFCI Receptacle	Self Closing	1	Vertical	Cast Aluminum	5103-0	3KH40
GFCI Receptacle, 9/32"	Self Closina	1	Vertical	Cast Aluminum	5028-0	5X914
Hole for Padlock	Jen Glosnig	'	VELLICAL	Oast Alullillulli	3020-0	3/314
Cover w/20A 120/277V	No Lid	1	Vertical	Cast Aluminum	5137-0	4YF69
DPST Switch	IVO LIG	'			3107 0	41103
Blank-Box Mount	No Lid	1	Horizontal	Stamped Steel	5173-0	2V706
	140 Eld		or Vertical	Construction	01700	20700
Lever Cover w/Two 10A,	No Lid	2	Vertical	Cast Aluminum	5124-0	4YF68
125V SPST Switches						
Duplex Receptacles	(2) Self Closing	2	Vertical	Cast Aluminum	5148-0	4A247
Duplex and GFCI Receptacle	Self Closing	2	Vertical	Cast Aluminum	5033-0	4LV83
GFCI Receptacle, Padlockable	Self Closing	2	Vertical	Cast Aluminum	5045-0	4LV84
Blank-Box Mount	No Lid	2	Horizontal	Cast Aluminum	5175-0	4A246
Hubbell Wiring Device-Kellems		1	Hadaaatal	0+ 7:	DIMETOOO	047047
Duplex and GFCI Receptacle	Self Closina	+	Horizontal Vertical	Cast Zinc	RW51020 HBL5222	24X917 6C595
Duplex Duplex	Self Closing	+	Vertical	Thermoplastic Thermoplastic	HBL5221	6C594
Duplex	Self Closing	1	Horizontal	Cast Aluminum	HBL5205W0	6C592
Duplex	Self Closing	+	Horizontal	Cast Aluminum	HBL5206W0	6C593
Single (1.40)	Self Closing	-i-	Vertical	Thermoplastic	HBL7423W0	6C615
Single (1.40)	Self Closing	1	Vertical	Thermoplastic	HBL7425W0A	5C991
Single (1.59)	Self Closing	+	Vertical	Cast Aluminum	HBL7420	3D249
Single (1.72)	Self Closing	i	Vertical	Thermoplastic	HBL7424W0	3D250
Single (2.15)	Self Closing	i	Vertical	Cast Aluminum	HBL9420	3D297
Single (2.15)	Self Closing	2	Vertical	Thermoplastic	HBL7777A	3D279
	Our Globing		vortioui	Reinforced	HDETTTIN	ODLIG
Flanged 15/20A Straight	Self Closing	1	Vertical	Thermoplastic	WP1	3D463
Blade Inlets/Outlets	our didding		vortioui	Polyester	*** '	05400
20/30A Twist-Lock	Self Closing	1	Vertical	Thermoplastic	WP2	3D464
GFCI	Self Closing	i	Vertical	PVC	CWP26CR	2EAU6
Duplex	Self Closing	<u>i</u>	Vertical	Thermoplastic	HBL52CM21	3D194
GFCI, Surge Receptacles and St						
Surge Receptacles	_	1	Vertical	Zinc	RW51470	61UH98
Surge Receptacles	_	1	Horizontal	Zinc	RW51810	61UH99
Portable Outlet Box				-		
Duplex	Self Closing	1	Vertical	PBT Resin	HBL3056	39EA01
GFĊI	Self Closing	1	Vertical	PBT Resin	HBL3061	39EA05

While-In-Use Weatherproof Covers





Snap-fit design speeds installation. Padlockable. Corner drill points for box mounting. All have easy-toremove cordset exit ports and adhered gasket. Single-gang has 16 possible configurations. Double-gang has 70 possible configurations. All are UL Listed and CSA Certified for wet locations while in use [NEC Article 406.8(B)]. Extra-Duty rated models (XD Suffix) comply with NEC requirements [NEC Article 406.9(B)(1)] for extra-duty applications and wet locations.

No	. OT F	receptacie	Wounting					IVITr.	item
Ga	ngs	Type	Orientation	Color	W	D	Н	Model	No.
Poly	carbonate Body								
		CI, Toggle or Round	Horizontal or Vertical	Clear	3 13/16 in	2 ¾ in	5 ⁴⁹ / ₆₄ in	WP3100C	1YVX3
	2 Duplex, GF	CI, Toggle or Round	Vertical	Clear	5 in	2 5/8 in	5 ½ in	WP1220C/8	4CAZ5
Die-Cast Aluminum Body									
	 Duplex, GF 	CI, Toggle or Round	Vertical	Gray	3 % in	3 1/8 in	3 1/4 in	WP1010MXD	29TH97
	 Duplex, GF 	CI, Toggle or Round	Horizontal	Gray	5 ¾ in	3 1/8 in	3 1/4 in	WP1010HMXD	29TH98
	2 Duplex, GF	CI, Toggle or Round	Vertical	Gray	5 ¾ in	3 1/8 in	3 1/4 in	WP1030MXD	29TH99

^{*} Inlets on ends, sides, and back. † Inlets on ends and back.