

For more information on MERV, see page 2919.



Air WHandler® **Antimicrobial Pleated Air Filters**

- MERV 8
- High capacity
- Synthetic media
- Moisture-resistant die-cut beverage board frame
- Wire-backed design
- UL Classified

Treated with an antimicrobial agent that prevents mold and mildew from growing on the air filter. Ideal for commercial buildings, healthcare facilities, and locations where moisture is present and mold or mildew may grow on standard filters.

Nom. H	Nom. W	Case Qty.	ltem No.	Nom. H	Nom. W	Case Qty.	Item No.
	lomina	Depth	1	2 in Nominal Depth			
8 in	16 in	12	2EJZ6	10 in	10 in	12	2EKE1
8 in	30 in	12	3DVK4	10 in	20 in	12 12	2EKE2
10 in	10 in	12	2EJZ7	12 in	20 in	12	2EKE3
10 in	20 in	12 12	2EJZ8	12 in	24 in	12	2EKE4
10 in	24 in	12	2EJZ9	14 in	20 in	12	2EKE5
10 in	25 in	12	2EKA1	14 in	25 in	12	2EKE6
10 in	30 in	12	3DVK5	15 in	20 in	12	2EKE7
12 in	12 in	12	2EKA2	16 in	16 in	12	2EKE8
12 in	16 in	12	2EKA3	16 in	20 in	12	2EKE9
12 in	18 in	12	3DVK6	16 in	24 in	12	2EKF1
12 in	20 in	12 12	2EKA4	16 in	25 in	12 12	2EKF2
12 in	24 in	12	2EKA5	18 in	18 in	12	3DVL6
12 in	25 in	12 12	2EKA6	18 in	20 in	12	2EKF5
12 in	30 in	12	3DVK7	18 in	22 in	12	2EKF3
14 in	20 in	12	2EKA7	18 in	24 in	12	2EKF4
14 in	24 in	12	2EKA8	18 in	25 in	12	2EKF6
14 in	25 in	12	2EKA9	20 in	20 in	12	2EKF7
14 in	30 in	12	3GUY2	20 in	24 in	12	2EKF8
15 in	20 in	12	2EKC1	20 in	25 in	12	2EKF9
15 in	25 in	12 12	2EKC2	20 in	30 in	12 12	2EKG1
15 in	30 in	12	3DVK9	24 in	24 in	12	2EKG2
15 in	31 in	12 12	3DVL1	25 in	25 in	12	2EKG3
16 in	16 in	12	2EKC3	4 in N	ominal		
16 in	20 in	12	2EKC4	12 in	24 in	6	2EKG4
16 in	23 in	12	3GUY3	16 in	20 in	6	2EKG5
16 in	24 in	12	2EKC5	16 in	25 in	6	2EKG6
16 in	25 in	12	2EKC6	18 in	24 in	6	2EKG7
16 in	30 in	12	3DVL2	20 in	20 in	6	2EKG8
18 in	18 in	12 12	2EKC7	20 in	24 in	6	2EKG9
18 in	20 in	12	2EKC8	20 in	25 in	6	2EKH1
18 in	22 in	12	2EKC9	24 in	24 in	6	2EKH2
18 in	24 in	12	2EKD1	25 in	29 in	6	2EKH3
18 in	25 in	12	2EKD2	28 in	30 in	6	2EKH4
19 in	27 in	12	3DVL3				
20 in	20 in	12	2EKD3				
20 in	23 in	12	3GUY4				
20 in	24 in	12	2EKD4				
20 in	25 in	12	2EKD5				
20 in	30 in	12 12	2EKD6				
22 in	22 in	12	2EKD7				
22 in	25 in	12	3DVL4				
24 in	24 in	12	2EKD8				
24 in	30 in	12	3DVL5				
25 in	25 in	12	2EKD9				

Air W Handler® **Hydrophobic Pleated Air Filters**

- MERV 8
- High capacity
- Synthetic media
- Plastic frame with mesh support
- UL Classified

2922

Filters not only remove contaminants from the air, they also remove moisture from the air. Commonly used to filter the air intake in dehumidification and swimming pool equipment.




Air W Handler® **Odor Removal Panel Air Filters**

- Moisture-resistant die-cut beverage board frame
- ASHRAE compliant

Activated charcoal absorbs unpleasant odors and other gaseous contaminants in the air stream to improve indoor air quality.

For Nuisance Odors, Pleated, Impregnated Carbon—Ideal for removing nuisance odors such as pet smells, tobacco smoke, food odors, and mustiness from the air.

- Carbon concentration: 20 g/sq. ft.





For VOCs and Exhaust Fumes. **Non-Pleated, Active Carbon Honevcomb**—Use to trap odors. VOCs (volatile organic compounds, such as fumes given off by paint or cleaning chemicals), exhaust fumes, and other gaseous contaminants. Commonly used in industrial areas to remove unpleasant smells in the air and capture harmful airborne pollutants to improve indoor air quality.

- Carbon concentration: 0.45 g/mL

Nom.	Nom.	Case	Item							
Н	W	Qty.	No.							
	Exhaust Fum									
Pleated, Active Carbon Honeycomb										
1 in Nominal Depth										
10 in	10 in	4	6B869							
12 in	24 in	4	6W735							
14 in	25 in	4	6B861							
16 in	16 in	4	6B857							
16 in	20 in	4	6W736							
16 in	24 in	4	6B856							
16 in	25 in	4	6W737							
20 in	20 in	4	6W738							
20 in	25 in	4	6W739							
24 in	24 in	4	6W740							
2 in Nominal Depth										
12 in	24 in	4	6W741							
16 in	20 in	4	6W742							
16 in	25 in	4	6W743							
18 in	24 in	4	6B852							
20 in	20 in	4	6W744							
20 in	25 in	4	6W745							
24 in	24 in	4	6W746							
25 in	25 in	4	6B846							

Air W Handler® **High-Temperature Pleated Air Filters**

- MERV 8
- Standard capacity
- Synthetic media
- Galvanized steel frame Wire-backed design
- Max. temp.: 400°F
- UL Classified

Withstand higher temperatures than other types of pleated air filters. Suitable for air intakes on drying ovens and other high-temperature baking applications.

NOM.	NOM.	NOM.	case	item
Н	W	D	Qty.	No.
12 in	24 in	2 in	12	5M326
16 in	20 in	2 in	12	5M327
16 in	25 in	2 in	12	5M316
20 in	20 in	2 in	12	5M329
20 in	25 in	2 in	12	5M330
24 in	24 in	2 in	12	5M331

