



**Residential
31LK63**



**Commercial
Conventional Top
783RL9**



**Commercial
Slope Top
3UH08**



**Receptacle
3UG89**

CADET
INVITING WARMTH

Dayton

QMARK
THE QUALITY CONNECTION

Standard Electric Baseboard Heaters

Overheat protection

Work by convection and have a heating element encased in a metal sheath surrounded by aluminum fins to transfer heat. Install along baseboards to warm rooms and small spaces in buildings such as multifamily housing or offices. Thermostat required (sold separately).

Residential Grade, Conventional Top—Multiple knockouts at each end. Includes wiring pigtails.

Commercial Grade, Conventional Top—Feature multiple knockouts at each end, wiring pigtails, and installation mounting guides. 3KB39 adds built-in cable clamps.

Commercial Grade, Slope Top—45° slope-top discourages use of heater as a shelf or step. Mount directly to the floor. Carpeting can be brought up to the front of the unit.

| Wattage Output | Voltage | Housing Color | Overall Length | Overall Height | Overall Depth | Mounting Type | Brand | Mfr. Model | Item No. |
|--|-------------|---------------|----------------|----------------|---------------|---------------|--------|------------|----------|
| Residential Grade, Conventional Top | | | | | | | | | |
| 150W/563W | 208/240V AC | White | 36 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 3F750W | 31LK58 |
| 262W/350W | 208/240V AC | White | 24 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 2F350W | 31LK56 |
| 375W/500W | 208/240V AC | White | 30 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 2F500W | 31LK57 |
| 376W/500W | 208/240V AC | White | 30 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG82 | 3UG82 |
| 500W | 120V AC | White | 30 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG76 | 3UG76 |
| 500W | 120V AC | White | 30 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 2F500-1W | 31LK63 |
| 564W/750W | 208/240V AC | White | 36 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG83 | 3UG83 |
| 750W | 120V AC | White | 36 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG77 | 3UG77 |
| 750W/1000W | 208/240V AC | White | 48 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 4F1000W | 31LK59 |
| 752W/1000W | 208/240V AC | White | 48 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG84 | 3UG84 |
| 937W/1250W | 208/240V AC | White | 60 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 5F1250W | 31LK60 |
| 940W/1250W | 208/240V AC | White | 60 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG85 | 3UG85 |
| 1000W | 120V AC | White | 48 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG78 | 3UG78 |
| 1000W | 120V AC | White | 48 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 4F1000-1W | 31LK64 |
| 1125W/1500W | 208/240V AC | White | 72 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 6F1500W | 31LK61 |
| 1128W/1500W | 208/240V AC | White | 72 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG86 | 3UG86 |
| 1250W | 120V AC | White | 60 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG79 | 3UG79 |
| 1500W | 120V AC | White | 72 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG80 | 3UG80 |
| 1500W | 120V AC | White | 72 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 6F1500-1W | 31LK65 |
| 1500W/2000W | 208/240V AC | White | 96 in | 6 3/4 in | 2 1/2 in | Wall | Cadet | 8F2000W | 31LK62 |
| 1504W/2000W | 208/240V AC | White | 96 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3UG87 | 3UG87 |
| 1800W/2500W | 208/240V AC | White | 96 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 4TM76 | 4TM76 |
| Commercial Grade, Conventional Top | | | | | | | | | |
| 750W | 208 V AC | White | 3 ft | 8 3/8 in | 2 1/8 in | Floor | Qmark | QMKC2503W | 783RL9 |
| 1000W | 208V AC | White | 48 in | 6 3/4 in | 2 1/2 in | Floor | Dayton | 3KB39 | 3KB39 |
| Commercial Grade, Slope Top | | | | | | | | | |
| 375W/500W | 208/240V AC | Beige | 28 in | 10 in | 3 1/4 in | Floor | Qmark | 3UH08 | 3UH08 |
| 750W/1000W | 208/240V AC | Beige | 48 in | 10 in | 3 1/4 in | Floor | Qmark | 3UH10 | 3UH10 |
| 1125W/1500W | 208/240V AC | Beige | 72 in | 10 in | 3 1/4 in | Floor | Qmark | 3UH11 | 3UH11 |
| 1500W/2000W | 208/240V AC | Beige | 96 in | 10 in | 3 1/4 in | Floor | Qmark | 3UH12 | 3UH12 |
| 1875W/2500W | 208/240V AC | Beige | 120 in | 10 in | 3 1/4 in | Floor | Qmark | 3UH13 | 3UH13 |

| Item | Voltage | Color | For Use With | Brand | Item No. |
|-----------------------|---------|-------|-------------------------------|--------|----------|
| Accessories | | | | | |
| Receptacle, Duplex | 120V AC | White | Residential Baseboard Heaters | Dayton | 3UG89 |
| Inside Corner Section | — | White | Residential Baseboard Heaters | Dayton | 3UG88 |

Dayton

Oil-Filled Electric Baseboard Heaters

- White housing
- Floor mount
- Overheat protection

Oil-filled heating element minimizes temperature swings and provides residual heat even after the unit is shut off. Units use convection heating. Install along baseboards to warm rooms and small spaces in buildings such as multifamily housing or offices. Hardwired and require a thermostat to control heat settings, see 3UG32 (sold separately, below).

| Wattage Output | Voltage | Overall Length | Overall Height | Overall Depth | Item No. |
|----------------|-------------|----------------|----------------|---------------|----------|
| 375W/500W | 208/240V AC | 28 in | 8 3/8 in | 3 in | 3UG30 |
| 500W | 120V AC | 28 in | 8 3/8 in | 3 in | 3EM28 |
| 562W/750W | 208/240V AC | 34 in | 8 3/8 in | 3 in | 3UG31 |
| 750W/1000W | 208/240V AC | 46 in | 8 3/8 in | 3 in | 3UG27 |
| 938W/1250W | 208/240V AC | 58 in | 8 3/8 in | 3 in | 3ENA4 |
| 1000W | 120V AC | 46 in | 8 3/8 in | 3 in | 3ENA1 |
| 1125W/1500W | 208/240V AC | 70 in | 8 3/8 in | 3 in | 3UG28 |
| 1250W | 120V AC | 58 in | 8 3/8 in | 3 in | 3ENA2 |
| 1500W | 120V AC | 70 in | 8 3/8 in | 3 in | 3ENA3 |
| 1500W/2000W | 208/240V AC | 94 in | 8 3/8 in | 3 in | 3UG29 |



3UG30



31LK66



3UG32



19RA10

CADET
INVITING WARMTH

Dayton

QMARK
THE QUALITY CONNECTION

Thermostats for Electric Baseboard Heaters

Control the temperature of standard and oil-filled electric baseboard heaters.

| Thermostat Control Range | Voltage | No. of Poles | For Use With | Brand | Mfr. Model | Item No. |
|--------------------------|---------------------|--------------|-------------------------------|--------|------------|----------|
| Unit Mount | | | | | | |
| 40° to 85°F | 120/208/240V AC | 1 | Baseboard Heaters | Cadet | BT1F1W | 31LK66 |
| | 120/208/240V AC | 2 | Baseboard Heaters | Cadet | BT1F2W | 31LK67 |
| | 120/208/240V AC | 2 | Hydronic Baseboard Heaters | Cadet | EBKNW | 31LK40 |
| 40° to 100°F | 120/208/240/277V AC | 1 | Residential Baseboard Heaters | Dayton | 3UG90 | 3UG90 |
| | 120/208/240/277V AC | 2 | Hydronic Baseboard Heaters | Dayton | 3UG32 | 3UG32 |
| | 120/208/240/277V AC | 2 | Residential Baseboard Heaters | Dayton | 3UG91 | 3UG91 |
| | 120/277V AC | 1 | 2500 Series Baseboard Heater | Qmark | TA1AW | 19RA18 |
| 60° to 120°F | 120/277V AC | 2 | 2500 Series Baseboard Heater | Qmark | TA2AW | 19RA10 |
| | 120/208/240V AC | 2 | Slope Top Baseboard Heaters | Qmark | 3UH14 | 3UH14 |
| Wall Mount | | | | | | |
| 50° to 80°F | 120/208/240/277V AC | 1 | Baseboard Heaters | Dayton | 3UH07 | 3UH07 |
| 55° to 85°F | 120/208/240/277V AC | 2 | Baseboard Heaters | Dayton | 3UF74 | 3UF74 |