



Drop-In Panel Radiant Electric Ceiling Heaters

Install in 2 ft. x 2 ft. or 2 ft. x 4 ft. drop ceilings. Include built-in T-bar suspension clips for mounting. Can also be recess- or surface-mounted on hard ceiling surfaces with a required mounting frame. Units use radiant heating to quietly spot heat small spaces. Remote wall-mounted line voltage thermostat required.

Wattage Output Heaters	Voltage	Mounting Type	Housing Color	Overall Length	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.	Description	For Use With	Color	Brand	Mfr. Model	Item No.
375W	120V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Dayton	54UD14	54UD14	Mounting Frames	Recessed, 24 in H x 24 in W	White	Dayton	2YU96	2YU96
	120V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Qmark	CP371F	54UD22						
	208V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Dayton	54UD15	54UD15						
	208V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Qmark	CP378F	54UD23						
	240V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Dayton	54UD16	54UD16						
	240V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Qmark	CP372F	54UD24						
	277V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Dayton	54UD17	54UD17						
750W	277V AC	Recessed, Surface	White	24 in	24 in	5 3/4 in, 7 in	Qmark	CP377F	54UD25	Recessed, 48 in H x 24 in W	54UD18, 54UD19, 54UD20, 54UD21, 54UD26, 54UD27, 54UD28, 54UD29	White	Qmark	QRF2448	39K929
	120V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Dayton	54UD18	54UD18						
	120V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP751F	54UD26						
	208V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Dayton	54UD19	54UD19						
	208V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP758F	54UD27						
	240V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Dayton	54UD20	54UD20						
	240V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP752F	54UD28						
750W	277V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Dayton	54UD21	54UD21	Surface, 24 in H x 24 in W	54UD14, 54UD15, 54UD16, 54UD17, 54UD22, 54UD23, 54UD24, 54UD25, 54UD18, 54UD19, 54UD20, 54UD21, 54UD26, 54UD27, 54UD28, 54UD29	White	Dayton	2YU98	2YU98
	277V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP757F	54UD29						
	277V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP757F	54UD29						
750W	277V AC	Recessed, Surface	White	48 in	24 in	5 3/4 in, 7 in	Qmark	CP757F	54UD29	Surface, 48 in H x 24 in W	54UD26, 54UD27, 54UD28, 54UD29	White	Qmark	QSF2448	39K928



General Purpose Electric Plenum Heaters

- Fan-forced
- Disconnect switch
- Mechanical selector dial, thermostat

Can be installed for free-air discharge or with a duct system to supplement central heating in hard-to-access or concealed areas, such as between a finished and drop ceiling or a plenum space. Can be rotated on their axis, but must be suspended horizontally and independently supported. Cannot be mounted vertically. Mounting bracket included.



Wattage Output	Voltage	Air Flow	Overall Height	Overall Width	Overall Depth	Brand	Item No.
1 Phase Heaters							
3kW	208V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX3
3kW	240V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX4
3kW	277V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX5
5kW	208/240V AC	275 cfm	14 1/2 in	14 3/4 in	19 3/4 in	Markel Products	56FD65
5kW	208V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX8
5kW	240V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX9
5kW	277V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCY1
7.5kW	208V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY5
7.5kW	240V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY6
7.5kW	277V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY7
10kW	240V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ2
10kW	277V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ3
3 Phase Heaters							
3kW	208V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCX6
5kW	208V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCY2
5kW	240V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCY3
5kW	480V AC	350/400 cfm	12 1/2 in	24 in	19 1/2 in	Dayton	2HCY4
7.5kW	208V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY8
7.5kW	240V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY9
7.5kW	480V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCY1
10kW	208V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ4
10kW	240V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ5
10kW	480V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ6
15kW	208V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ7
15kW	240V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ8
15kW	480V AC	850/1,000 cfm	17 1/2 in	35 3/8 in	18 in	Dayton	2HCZ9

Item	Fits 3 to 5 kW			Item No.	Fits 7.5 to 15 kW			Item No.
	H	W	D		H	W	D	
Adjustable Louver Kit	12 1/2 in	14 in	1 in	2KMN8	—	—	—	—
Disposable Filter	10 in	12 in	1 in	3TKC3	12 in	16 in	1 in	3TKC7
Disposable Filter	12 1/2 in	14 in	1 in	2KMN4	17 in	13 1/2 in	1 in	2KMN6
Louver Kit	—	—	—	—	17 in	13 1/2 in	1 in	2KMN9
Register Kit	12 in	10 in	2 1/2 in	2KMP1	14 in	12 in	2 1/2 in	2KMP2
Reusable Filter	10 in	12 in	1 in	3TKC5	12 in	16 in	1 in	3TKC9
Reusable Filter	12 1/2 in	14 in	1 in	2KMN5	17 in	13 1/2 in	1 in	2KMN7



Freeze Protection Electric Plenum Heater

- Thermostat range: 40°F to 90°F
- Has a set of normally open (NO) contacts that can send a signal to an optional alarm device that activates if the heater cycles off on its over-temperature

safety control. It notifies users before freezing occurs. Unit heats hard-to-access or concealed areas like plenum spaces. Ceiling mounted using included bracket or threaded rod mounting.

Wattage Output	Voltage	Air Flow	Overall Height	Overall Width	Overall Depth	Item No.
2.5kW/1.9kW	208/240V AC	150/130 cfm	12 1/2 in	14 in	14 in	2HDA1