Hazardous-Location Electric Cabinet Wall Heaters



Class I Div. 1 and 2 Groups B. C. and D

9" Markel, 8" QMark

Quiet, convection-style heaters used in hazardous industrial environments like petroleum refineries, gasoline storage areas, petrochemical facilities, and dry Min. height from floor: cleaning plants. Wall mount with included brackets. Thermostat not included.

Note: Required contactors sold separately on page 165. Required thermostats sold separately on

Wattage Output	Voltage	Phase	Housing Color	Cabinet Height	Cabinet Width	Cabinet Depth	Brand	Mfr. Model	Item No.
	120V AC	1	Gray	18 in	34 in	9 in	Markel Products	FEP-1812-1RA	49CT92
	208V AC	1	Beige	20 in	34 in	9 in	Qmark	ICG18081	3LA87
1.8 kW	208V AC	1	Gray	18 in	34 in	9 in	Markel Products	FEP-1820-1RA	49CT93
	240V AC	1	Beige	20 in	34 in	9 in	Qmark	ICG18041	3LA88
	240V AC	1	Gray	18 in	34 in	9 in	Markel Products	FEP-1824-1RA	49CT94
	208V AC	1	Beige	20 in	34 in	9 in	Qmark	ICG36081	5NF11
	208V AC	1	Gray	18 in	34 in	9 in	Markel Products	FEP-3620-1RA	49CT95
3.6 kW	240V AC	1	Beige	20 in	34 in	9 in	Qmark	ICG36041	5NF09
3.0 KW	240V AC	1	Gray	18 in	34 in	9 in	Markel Products	FEP-3624-1RA	49CT96
	480V AC	3	Beige	20 in	34 in	9 in	Qmark	ICG360483	5NF10
	480V AC	3	Gray	18 in	34 in	9 in	Markel Products	FEP-3648-3RA	49CT97
7.6 kW	240V AC	1	Gray	18 in	58 in	9 in	Markel Products	FEP-7624-1RA	49CT98
1.0 KVV	480V AC	3	Gray	18 in	58 in	9 in	Markel Products	FEP-7648-3RA	49CT99







Indoor Suspended Infrared Radiant Electric Ceiling Heaters

Units use infrared radiant heating to quietly warm people and objects, not the ambient air, without taking up floor or wall space. Suspend from the ceiling to spotheat areas in workshops, garages, and warehouses. May only be used indoors.

Wattage Output	Voltage	Beam Pattern	Overall Length	Overall Width	Overall Depth	Mfr. Model	Item No.	
Quartz Lamp, S	ilver Housii	1g						
900W/1600W	277V AC	60°	24 in	3 ¾ in	3 % in	MM-24A	2KDA6	
3000W/3800W	600V AC	60°	46 in	3 ¾ in	3 % in	MM-46A	2KDA7	



Indoor/Outdoor Suspended Infrared AURA Solaira **Radiant Electric Wall Heaters**

■ Beam pattern: 45°

Can withstand rain and are typically used to spot heat spaces like condominium terraces, gazebos, under patio umbrellas, and other low-clearance seating areas. Units use infrared radiant heating to quietly warm people and objects, not the air. Included bracket allows for vertical and horizontal orientation.

Wattage Output	Voltage	Overall Length	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
Carbon Fiber En		using					
1500W	120V AC	27 in	6 ½ in	5 ½ in	Aura	CF15120B	55EA57
2250W/3000W	208/240V AC	38 ½ in	6 ½ in	5 ½ in	Aura	CF30240B	55EA58
Quartz Lamp, BI	ack Housing						
1125W/1500W	208/240V AC	15 ½ in	6 in	4 in	Solaira	SCOSY15240B	11Z944
1125W/1500W	208/240V AC	22 in	6 in	5 in	Solaira	SCOSYXL15240b	11Z948
1500W	120V AC	15 ½ in	6 in	4 in	Solaira	SC0SY15120B	11Z942
1500W	120V AC	22 in	6 in	5 in	Solaira	SCOSYXL15120b	11Z946
1500W/2000W	208/240V AC	15 ½ in	4 in	4 1/4 in	Solaira	SCOSYXL20240b	11Z950
Quartz Lamp, Si	lver Housing						
1125W/1500W	208/240V AC	16 in	10 in	6 in	Solaira	SALPHA15240G	11Z935
1500W	120V AC	16 in	10 in	6 in	Solaira	SALPHA15120G	11Z934
1500W/2000W	208/240V AC	16 in	10 in	6 in	Solaira	SALPHA20240G	11Z936
2250W/3000W	208/240V AC	31 in	10 in	6 in	Solaira	SALPHAH2-30240G	11Z937
3000W/4000W	208/240V AC	31 in	10 in	6 in	Solaira	SALPHAH2-40240G	11Z938
4500W/6000W	208/240V AC	46 in	10 in	6 in	Solaira	SALPHA3-60240L1G	11Z939
Quartz Lamp, W	hite Housing						
1125W/1500W	208/240V AC	15 ½ in	6 in	4 in	Solaira	SC0SY15240W	11Z945
1125W/1500W	208/240V AC	22 in	6 in	5 in	Solaira	SCOSYXL15240w	11Z949
1500W	120V AC	15 ½ in	6 in	4 in	Solaira	SC0SY15120W	11Z943
1500W	120V AC	22 in	6 in	5 in	Solaira	SCOSYXL15120w	11Z947
1500W/2000W	208/240V AC	15 ½ in	4 in	4 1/4 in	Solaira	SCOSYXL20240w	11Z951
Calaira Cantrala		Description	1			Mfr. Model	Item No.

	Description	Model	NO.
Solaira Controls			
Control and Enclosure, 120V; 2	08-240V, 30A	PASCR30-1-DIN	783RM0
Digital Variable Heat Control, 12	20/208/240V AC, 16 A	SMRTV16-DV	20HN32
Digital Variable Heat Control, 12	20/208/240V AC, 34 A	SMTRV34-DV	20HN33
Occupancy Sensor, 208/240V A	C, 16.6 A	SMRTOCC40	20HN39
Occupancy Sensor, 208/240V A	C, 25 A	SMRTOCC60	20HN40
Remote Temperature Monitor, 2	240V AC	SMRTVTEM-R	20HN35
Timer Control for Heater, 208/2	40V AC, 16.6 A	SMRTTIM40	20HN37
Timer Control for Heater, 208/2	40V AC, 25 A	SMRTTIM60	20HN38
Variable Heat Control Knob, Wil	reless Handheld Remote, 240V AC	SMRTVRMT	20HN34
		Mfr.	Item
For Use With	Voltage	Model	No.



11**Z**943

SWIREAW15240

11Z963