



Natural Gas,  
Propane  
16W290



Propane  
16W283



### Direct-Fired Portable Gas Ducted & Tent Heaters

Heaters have an open flame that directly heats the air, warming a space. The exhaust gases mix into the air, so these heaters are used in ventilated spaces. They provide the primary source of heat in tented spaces and construction sites where the heat can be ducted. Heaters feature built-in air pressure gauge, LED diagnostics, power failure indicator, and remote-mounted thermostat.

Heating Capacity Output	Heating Area	Fuel Consumption	Overall Height	Overall Width	Overall Depth	Mfr. Model	Item No.
<b>Natural Gas, Propane</b>							
80,000 BtuH	20,000 sq ft	3.7 lb/hr, 80 cfh	22 in	28 in	13 1/2 in	CS080BSDN22168T	407M21
170,000 BtuH	40,000 sq ft	7.9 lb/hr, 170 cfh	32 in	32 3/8 in	24 3/8 in	CS170BSDN22168T	16W287
350,000 BtuH	80,000 sq ft	350 cfh, 2.63 gph	41 in	48 3/8 in	28 in	CS350SDSN22168T	16W290
<b>Propane</b>							
80,000 BtuH	20,000 sq ft	3.7 lb/hr	22 in	28 in	13 1/2 in	TS080CSPN22168T	16W283
170,000 BtuH	40,000 sq ft	7.9 lb/hr	32 in	32 3/8 in	24 3/8 in	TS170BSPN22168T	16W285
							Item No.
<b>Description</b>							Mfr. Model
<b>Accessories</b>							Item No.
Ducting with Adapter, Gray, 12 ft L x 12 in Dia., For Use with 16W283, 16W285, 16W287						500-26346	16W307
Ducting with Adapter, White, 12 ft L x 12 in Dia., For Use with 16W283, 16W285, 16W287						500-26347	16W308
Ducting with Adapter, White, 12 ft L x 18 in Dia., For Use with 16W288, 16W290						500-22835	16W311
End Diffuser, 13 3/8 in H x 32 1/8 in W x 22 1/2 in D, For Use with 16W307, 16W308, 16W309						500-26350	16W310
End Diffuser, 19 1/2 in H x 52 3/8 in W x 28 1/2 in D, For Use with 16W311, 16W312						500-23189	16W313
Unit Diffuser, 19 1/2 in H x 23 3/8 in W x 24 1/8 in D, For Use with 16W283						132902	16W305
Unit Diffuser, 19 1/2 in H x 32 1/8 in W x 24 1/8 in D, For Use with 16W285						500-26351	16W306



52JP73



### Indirect-Fired Portable Gas Ducted & Tent Heaters

These heaters have a chamber that is isolated from the flame, allowing the exhaust fumes to be vented outside and the heated air to remain clean. They provide the primary source of heat in tented spaces and construction sites where the heat can be ducted.

Heating Capacity Output	Heating Area	Key Features	Fuel Consumption	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
<b>Heaters</b>									
400,000 BtuH	17,000 sq ft	Automatic Safety Shut-Off, Power Failure Indicator, Thermostat	400 cfh, 4.4 gph	59 in	29 in	82 in	Sure Flame	IX405	52JP73
400,000 BtuH	17,000 sq ft	Automatic Safety Shut-Off, Thermostat	400 cfh, 4.4 gph	45 in	24 in	60 in	Heat Wagon	VG400	5PFW5
							Brand	Mfr. Model	Item No.
<b>Description</b>							Brand	Mfr. Model	Item No.
<b>Accessories</b>							Brand	Mfr. Model	Item No.
Gas Pressure Regulator, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5							Itron	B42R	6DMN6
Ducting, 25 ft, For Use with 5PFW5, 6DMP0, 6DMP2, 6DMP4							Heat Wagon	WD1225	6DMR0
3/4 in High Pressure Gas Hose, 25 ft, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5							Heat Wagon	7525	6DMR4
3/4 in High Pressure Gas Hose, 50 ft, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5							Heat Wagon	7550	6DMR5

5PFW5



### Direct-Fired Portable Gas Remediation & Tent Heaters

Units raise and maintain the ambient air temperature high enough to kill insects, making them ideal for treating insect infestations. They can also act as a primary source of heat for tented spaces and construction sites. They have an open flame that directly heats the air to heat a space.

Heating Capacity Output	Heating Area	Key Features	Air Temp. Rise	Fuel Consumption	Overall Height	Overall Width	Overall Depth	Mfr. Model	Item No.
<b>Heat Wagon Heaters</b>									
250,000 BtuH	12,500 sq ft	Automatic Safety Shut-Off, Power Failure Indicator	170°F	255 cfh, 2.6 gph	36 in	31 in	45 in	DG250	11Z967
400,000 BtuH	20,000 sq ft	Automatic Safety Shut-Off, Power Failure Indicator	180°F	404 cfh, 4.3 gph	39 in	34 in	61 in	DG400	11Z968
							Mfr. Model	Item No.	
<b>Description</b>							Mfr. Model	Item No.	
<b>Accessories</b>							Mfr. Model	Item No.	
Duct Adapter, For Use with 11Z967							Heat Wagon	AR250	11Z969
Duct Adapter, For Use with 11Z968							Heat Wagon	AR400	11Z970
Ducting, 25 ft L x 18 in Dia., For Use with 11Z967							Heat Wagon	WD1625HT5	11Z971
Ducting, 25 ft L x 20 in Dia., For Use with 11Z968							Heat Wagon	WD2025HT5	11Z972
Gas Pressure Regulator, For Use with 11Z967, 11Z968, 52JP73, 5PFW3, 5PFW4, 5PFW5							Itron	B42R	6DMN6
Thermostat, 120 V AC, For Use with 11Z967, 11Z968							Heat Wagon	DIGTHDF-5	11Z973

11Z967



453V13



453V15

### Dyna-Glo Portable Kerosene Radiant Floor Heaters

They efficiently warm small spaces like garages up to 500 sq. ft. Heaters use radiant heating to emit warmth that gets absorbed by people and objects, warming them faster than others that warm the ambient air. They're placed on the floor and can be moved as heating needs change.

Heating Capacity Output	Tank Cap.	Hours on One Filling	Color	Overall Height	Overall Width	Overall Depth	Mfr. Model	Item No.
10,000 BtuH	0.7 gal	13 hr	Black	19 3/8 in	22 3/8 in	11 1/2 in	RMC-55R7B	453V14
10,000 BtuH	0.7 gal	13 hr	White	19 3/8 in	22 3/8 in	11 1/2 in	RMC-55R7	453V13
10,500 BtuH	0.8 gal	12 hr	White	21 3/8 in	12 3/8 in	12 3/8 in	WK11C8	453V15