



Indirect-Fired Portable Oil & Kerosene Torpedo Heaters

▪ LED diagnostics

Units have a chamber that is isolated from the flame, allowing the exhaust fumes to be vented outside and the heated air to remain clean. They provide the primary source of heat in large spaces like construction sites where the heat can be ducted.



5PFW9

Heating Capacity Output	Heating Area	Tank Capacity/ Hours on One Filling	Overall Height	Overall Length	Overall Depth	Brand	Mfr. Model	Item No.
Heaters, Wheeled Mounted								
91,900 BtuH	4,600 sq ft	17.2 gal/22 hr	31 in	49 in	49 in	Heat Wagon	HVF110	5PFW8
174,900 BtuH	8,800 sq ft	27.7 gal/19 hr	38 in	57 in	57 in	Heat Wagon	HVF210	5PFW9
231,000 BtuH	17,500 sq ft	57 gal/20 hr	48 in	83 in	83 in	Heat Wagon	HVF410	5PFX1
254,400 BtuH	13,000 sq ft	35.7 gal/16 hr	38 in	69 in	69 in	Heat Wagon	HVF310	5PFX0

Description	Brand	Mfr. Model	Item No.
Accessories			
Duct Adapter, 10 in. For Use with 5PFW9	Heat Wagon	AR210	6DMP1
Duct Adapter, 10 in. For Use with 5PFX0	Heat Wagon	AR310	6DMP3
Duct Adapter, 12 in. For Use with 5PFW9	Heat Wagon	AR212	6DMP2
Duct Adapter, 12 in. For Use with 5PFX0	Heat Wagon	AR312	6DMP4
Duct Adapter, 12 in. For Use with 5PFX1	Heat Wagon	AR401	6DMP5
Duct Adapter, 18 in. For Use with 5PFX1	Heat Wagon	AR402	6DMP6
Duct Adapter, 8 in. For Use with 5PFW8	Heat Wagon	AR110	6DMP0
Ducting, 20 ft. For Use with 6DMP0, 6DMP2, 6DMP4	Heat Wagon	WD1220	6DMP9
Ducting, 25 ft. For Use with 5PFW5, 6DMP0, 6DMP2, 6DMP4	Heat Wagon	WD1225	6DMP0
Ducting, 25 ft. For Use with 5PFW6, 6DMP5, 6DMP7	Heat Wagon	WD2025	6DMR3
Ducting, 25 ft. For Use with 6DMP1	Heat Wagon	WD1425	6DMR1
Ducting, 25 ft. For Use with 6DMP3, 6DMP6	Heat Wagon	WD1825	6DMR2
Flue Stack, 18 in. For Use with 5PFW8, 5PFW9, 5PFX0, 5PFX1	Selkirk	EF1	6DMN9
Thermostat, For Use with 52JP74, 52JP75, 52JP76, 5PFW8, 5PFW9, 5PFX0, 5PFX1	Heat Wagon	ACC-THIDF	6DMN8



Natural Gas
36FK50

In-Floor Vented Gas Heaters



Heaters install in an opening in the floor and provide supplemental heat in drafty areas with limited space. They lower into the floor and mount either parallel or perpendicular to the floor joists. Venting is required. They can be controlled with a unit-installed thermostat or a separate wall thermostat.

Heating Capacity Input	Heating Capacity Output	Heating Area	Thermostat Incl.	Grille Dim. - L x W	Rough-In Dim. - L x W x D	Mfr. Model	Item No.
Natural Gas							
45,000 BtuH	31,000 BtuH	1,000 sq ft	No	32 in x 24 in	32 3/8 in x 24 1/4 in x 28 in	4505622A	36FK50
60,000 BtuH	42,000 BtuH	1,400 sq ft	No	42 in x 24 in	42 3/8 in x 24 1/4 in x 28 in	6005622A	36FK51
Propane							
45,000 BtuH	31,000 BtuH	1,000 sq ft	No	32 in x 24 in	32 3/8 in x 24 1/4 in x 25 in	4505621A	36FK52
60,000 BtuH	42,000 BtuH	1,400 sq ft	No	42 in x 24 in	42 3/8 in x 24 1/4 in x 28 in	6005621A	36FK53



Natural Gas,
Solid Face Style
36FK36

Freestanding Vented Gas Floor Heaters



These units provide supplemental heat and can be placed on the floor anywhere in a room without cutting into the floor. They're usually set close to a wall since they require venting that's ducted out of the room.

Heating Capacity Input	Heating Capacity Output	Thermostat Incl.	Vent Diameter	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
Natural Gas, Solid Face Style									
20,000 BtuH	15,500 BtuH	No	3 in	21 1/2 in	23 in	11 in	Williams	2001622A	36FK36
20,000 BtuH	16,300 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV20ENAT	4LFZ6
35,000 BtuH	24,500 BtuH	Unit-Mounted	4 in	26 in	37 in	18 3/8 in	Empire	RH35NAT	4LGF7
35,000 BtuH	25,000 BtuH	No	4 in	28 1/2 in	25 in	15 1/2 in	Williams	3501522A	36FK37
40,000 BtuH	32,600 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV40ENAT	4LGA5
50,000 BtuH	34,500 BtuH	No	4 in	32 1/2 in	30 in	16 in	Williams	5001522A	36FK38
50,000 BtuH	35,000 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	23 3/8 in	Empire	RH50ENAT	4LGG2
55,000 BtuH	44,825 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV55ENAT	4LGA7
65,000 BtuH	47,000 BtuH	No	5 in	32 1/2 in	34 in	19 1/2 in	Williams	6501522A	36FK39
Natural Gas, Visual Flame Style									
25,000 BtuH	17,500 BtuH	Unit-Mounted	4 in	26 in	37 in	18 3/8 in	Empire	RH25NAT	4LGF5
35,000 BtuH	25,000 BtuH	No	4 in	28 1/2 in	25 in	15 1/2 in	Williams	3502522A	36FK44
50,000 BtuH	25,000 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	23 3/8 in	Empire	RH50BNAT	2RC68
50,000 BtuH	34,500 BtuH	No	4 in	32 1/2 in	30 in	16 in	Williams	5002522A	36FK45
65,000 BtuH	33,000 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	27 1/8 in	Empire	RH65BNAT	2RCH5
65,000 BtuH	45,500 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	27 1/8 in	Empire	RH65CNAT	4LGG6
65,000 BtuH	47,000 BtuH	No	5 in	32 1/2 in	34 in	19 1/2 in	Williams	6502522A	36FK46
Propane, Solid Face Style									
20,000 BtuH	15,500 BtuH	No	3 in	21 1/2 in	23 in	11 in	Williams	2001621A	36FK40
20,000 BtuH	16,300 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV20ELP	4LFZ5
25,000 BtuH	17,500 BtuH	Unit-Mounted	4 in	26 in	37 in	18 3/8 in	Empire	RH25LP	4LGF4
35,000 BtuH	24,500 BtuH	Unit-Mounted	4 in	26 in	37 in	18 3/8 in	Empire	RH35LP	4LGF6
35,000 BtuH	25,000 BtuH	No	4 in	28 1/2 in	25 in	15 1/2 in	Williams	3501521A	36FK41
40,000 BtuH	32,600 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV40ELP	4LGA4
50,000 BtuH	34,500 BtuH	No	4 in	32 1/2 in	30 in	16 in	Williams	5001521A	36FK42
50,000 BtuH	35,000 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	23 3/8 in	Empire	RH50CLP	4LGG1
55,000 BtuH	44,825 BtuH	Unit-Mounted	3 1/2 in	26 in	37 in	15 3/4 in	Empire	DV55ELP	4LGA6
65,000 BtuH	45,500 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	27 1/8 in	Empire	RH65CLP	4LGG5
65,000 BtuH	47,000 BtuH	No	5 in	32 1/2 in	34 in	19 1/2 in	Williams	6501521A	36FK43
Propane, Visual Flame Style									
50,000 BtuH	25,000 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	23 3/8 in	Empire	RH50BLP	2RCH2
65,000 BtuH	32,500 BtuH	Unit-Mounted	5 in	29 3/8 in	34 in	27 1/8 in	Empire	RH65BLP	2NCR5

Accessory Type	Compatible Grainger Part No.	Brand	Mfr. Model	Item No.
Accessories				
Blower	36FK37, 36FK38, 36FK39, 36FK41, 36FK42, 36FK43, 36FK44, 36FK45, 36FK46, 36FK47, 36FK48, 36FK49	Williams	2102	36FK85
Floor Pad	36FK38, 36FK39, 36FK42, 36FK43, 36FK45, 36FK46, 36FK48, 36FK49	Williams	4163	36FK86

Propane, Visual
Flame Style
2NCR5



Propane, Solid
Face Style
4LFZ5

Natural Gas,
Visual Flame Style
36FK44

