



Conduit and Cable Clamps, Hangers, and Clips

	Description	B-LINE BY Eaton Mfr. Model	Item No.	NVENT CADDY Mfr. Model	Item No.
4RHH5	KwikWire™—Adjustable Wire Rope System; Replaces Jack Chain or ATR for Support				
	KwikWire™ Clamps For 1/8" or 3/16" Wire Rope	BKC200-1	4RHY3	—	—
	KwikWire™ 1/16" Wire Rope, 500-ft. Spool, 75-lb. Rating When Used with BKC100 Clamps	BKW063	4RHY8	—	—
	KwikWire™ 3/32" Wire Rope, 500-ft. Spool, 150-lb. Rating When Used with BKC100 or BKC150 Clamps	BKW094	4RHY9	—	—
	KwikWire™ 1/8" Wire Rope, 500-ft. Spool, 250-lb. Rating When Used with BKC150 or BKC200 Clamps	BKW125	4RHZ1	—	—
	KwikWire™ 3/16" Wire Rope, 250-ft. Spool, 640-lb. Rating When Used with BKC200 Clamps	BKW188	4RHZ2	—	—
	KwikPak™ Dispenser Box - Includes 100 Clamps (No. 4RHY1) and 500-ft. Spool (No. 4RHY8), 75-lb. Rating	BKP10063	4RHY5	—	—
	KwikPak™ Dispenser Box - Includes 100 Clamps (No. 4RHY2) and 500-ft. Spool (No. 4RHY9), 150-lb. Rating	BKP10094	4RHY6	—	—
	KwikPak™ Dispenser Box - Includes 50 Clamps (No. 4RHY3) and 250-ft. Spool (No. 4RHZ1), 250-lb. Rating	BKP20125	4RHY7	—	—
	KwikWire™ Wire Rope Cable Cutter	BKCC	4RHY4	—	—
	Acoustical T-Bar Ceiling Fasteners				
	T-Bar Support Clip, Allows for Independent Support of Fixtures, 65-lb. Rating, Fits 19/16" T-Bar, Stud Size 1/4" x 3/8"	BA1	4RHG7	IDS	2KXJ6
	T-Bar Support Clip, Allows for Independent Support of Fixtures, 65-lb. Rating, Fits 3/16" T-Bar, Stud Size 1/4" x 3/8"	BA1-95	4RHH1	—	—
	T-Bar Twist Fastener, Supports Electrical Boxes from 19/16" T-Bar with 1/4" x 3/8" Stud, 50-lb. Rating, Black Finish	BA-4-16	4RHH4	4G16	2KXJ9
	T-Bar Twist Fastener, Supports Electrical Boxes from 19/16" T-Bar with #8 x 3/8" Stud, 25-lb. Rating, White Finish	BA-2-16-W	4RHH2	4G8WH	2KXJ8
	Drop Wire Clip for #12 to #8 Wire Prevents Sway of Dedicated Electrical Drop Wire	BA311	4RHH3	—	—
	Conduit T-Bar Clip Attaches 1/2" and 3/4" Conduit to T-Bar	BG-8-12-A6	4RHW4	—	—
	Hurricane Clip Troffer Fastener Provides Positive Support for Troffers and Lay-In Light Fixtures	BA15	4RHG9	515	2KXJ4
	Beam Clamps				
	Hammer-On Beam Clamp, Provides 1/4"-20 Thread to Hang Electrical Boxes, 75-lb. Rating, 3/8" to 1/2" Flange	BU-2-4	4RJC6	M24	2KWY7
	Hammer-On Beam Clamp, Provides 1/4"-20 Thread to Hang Electrical Boxes, 3/16" to 1/2" Flange	BU-5-8	4RJC8	M58	2KWY9
	Hammer-On Beam Clamp, Provides 1/4" Stud to Hang Electrical Boxes, 100-lb. Rating, 1/8" to 1/4" Flange	BU-2-4-S	4RJC7	M24S	2KWY8
	Hammer-On Beam Clamp, Provides 1/4" Stud to Hang Electrical Boxes, 3/16" to 1/2" Flange	BU-5-8-S	4RJC9	M58S	2KWZ1
	Standard Beam Clamp, 100-lb. Rating, Up to 1/2" Flange	BC1	4RHK8	BC	2KWY1
	Standard Beam Clamp, 100-lb. Rating, Up to 1/2" Flange with 1/2" and 3/4" Conduit Clip	BG-8-12-C2	4RHHV	BC812M	2KWY2
	Hammer-On Flange Beam Fastener, Provides 1/4" Hole to Hang Chain, Drop Wire, S-Hooks, Etc., 1/16" to 1/8" Flange	BE-1-2	4RHR6	2H4	2KWY3
	Hammer-On Flange Beam Fastener, Provides 1/4" Hole to Hang Chain, Drop Wire, S-Hooks, Etc., 1/8" to 1/4" Flange	BE-2-4	4RHR7	4H24	2KWY4
	Hammer-On Flange Beam Fastener, Provides 1/4" Hole to Hang Chain, Drop Wire, S-Hooks, Etc., 200-lb. Rating, 3/16" to 1/2" Flange	BE-5-8	4RHR8	4H58	2KWY5
	Hammer-On Flange Beam Fastener, Provides 1/4" Hole to Hang Chain, Drop Wire, S-Hooks, Etc., 200-lb. Rating, 3/16" to 3/4" Flange	BE-9-12	4RHR9	4H912	2KWY6
	Iron, 1/8" in to 3/16" in Jaw Opening, For Use With 3/8" Threaded Rod, 250 lb Load Rating	—	—	CRLB37EG	6PRFA
	Wall Mount Cable Hooks, 30-lb. Rating				
	3/4" Cable Hook	BCH12	4RHK9	CAT12	2KXD7
	1 3/16" Cable Hook	BCH21	4RHN1	—	—
	2" Cable Hook	BCH32	4RHN6	—	—
	4" Cable Hook	BCH64	4RHR1	—	—
	Cable Hook/Beam Clamp Assemblies, 30-lb. Rating				
	3/4" Hook, Up to 1/2" Flange Thickness	BCH12-C2	4RHL2	CAT12BCB	2KXE4
	1 3/16" Hook, Up to 1/2" Flange Thickness	BCH21-C2	4RHN2	—	—
	2" Hook, Up to 1/2" Flange Thickness	BCH32-C2	4RHN9	—	—
	4" Hook, Up to 1/2" Flange Thickness	BCH64-C2	4RHR2	—	—
	Cable Hook to Wire/Rod Assemblies, 30-lb. Rating				
	3/4" Hook, #12 Wire to 1/4" Rod	BCH12-W2	4RHL8	CAT124Z34	2KXE9
	1 3/16" Hook, #12 Wire to 1/4" Rod	BCH21-W2	4RHN5	—	—
	2" Hook, #12 Wire to 1/4" Rod	BCH32-W2	4RHP8	—	—
	Cable Hook/Hammer-On Beam Clamp Assemblies, 30-lb. Rating				
	3/4" Hook, 1/8" to 1/4" Flange Thickness	BCH12-U-2-4	4RHL7	CAT1224	2KXE8
	1 3/16" Hook, 1/8" to 1/4" Flange Thickness	BCH21-U-2-4	4RHN4	—	—
	2" Hook, 1/8" to 1/4" Flange Thickness	BCH32-U-2-4	4RHP6	—	—
	4" Hook, 1/8" to 1/4" Flange Thickness	BCH64-U-2-4	4RHR4	—	—
	Cable Hook/Angle Bracket Assemblies, 30-lb. Rating				
	3/4" Hook to 1/4" Threaded Rod	BCH12-RB	4RHL6	CAT12AB	2KXF2
	1 3/16" Hook to 1/4" Threaded Rod	BCH21-RB	4RHN3	—	—
	2" Hook to 1/4" Threaded Rod	BCH32-RB	4RHP5	—	—
	4" Hook to 1/4" Threaded Rod	BCH64-RB	4RHR3	—	—
	Angle Bracket Hanger, 180-lb. Rating, Supports up to 3 Cable Hooks per Side	BCH-HBA	4RHR5	CATHBA	2KXE2
	Cable and Conduit Brackets				
	Cable Bracket, Fits 0.430 to 0.560" MC/AC Cable up to 4 Runs, 50-lb. Rating	BRC5-1	4RJC4	MCS50	2KWX8
	Cable Bracket, Fits 0.430 to 0.560" MC/AC Cable up to 9 Runs, 50-lb. Rating	—	—	MCS100	2KWX9
	Staple-Lok Cable Support, Fits up to 1/2" OD Cable	—	—	CJ6S	2KXC4
	Cable Bracket, Fits 14/2 to 10/3 AWG Cable, Supports Horizontal Runs Of MC/AC/FMC Cable Through Metal Studs	—	—	459	2KXC7
	Low Voltage Cover Plate Mounting Brackets—Replace Electrical Box in Class 2, Low Voltage Outlets				
	Single-Gang Old Work Support Bracket	BB10	4RHH8	MP1	2KXD4
	Single-Gang Old Work Support Bracket, Plastic Design	BB10P	4RHJ1	MP1P	2KXD2
	Single-Gang New Work Support Bracket	BB15	4RHJ3	MP1S	2KXB2
	2-Gang Old Work Support Bracket with Screws	BB20L	4RHJ4	MPLS2	2KXD6
	Bridle Rings				
	3/4" Bridle Ring, #10-24 Thread, 50-lb. Rating	BR-12-T	4RJA2	2BRT12	2KXH4
	1 1/2" Bridle Ring, #10-24 Thread, 50-lb. Rating	BR-20-T	4RJA4	2BRT20	2KXH5
	1 1/2" Bridle Ring, 1/4" Thread, 50-lb. Rating	BR-20-4T	4RJA3	4BRT20	2KXH6
	2" Bridle Ring, #10-24 Thread, 50-lb. Rating	BR-32-T	4RJA8	2BRT32	2KXH8
	2" Bridle Ring, 1/4" Thread, 50-lb. Rating	BR-32-4T	4RJA6	4BRT32	2KXH9
	4" Bridle Ring, 1/4" Thread, 50-lb. Rating	BR-64-4T	4RJA9	4BRT64	2KXJ2
	1 1/2" Bridle Ring, 1/4" Lag Screw for Wood Beams, 50-lb. Rating	BR-24-4W	4RJA5	—	—
	2" Bridle Ring, 1/4" Lag Screw for Wood Beams, 50-lb. Rating	BR-32-4W	4RJA7	4BRT32WS	2KXJ1
	Miscellaneous				
	Flange Clip to Support Wire, Rod, S-Hooks, or Bolting Straps, 1/16" to 1/4" Vertical Flange, 160-lb. Rating	BF3	4RHT2	VF14	2KWZ2
	Flange Clip to Support Wire, Rod, S-Hooks, or Bolting Straps, 1/16" to 1/4" Z-Purlin Flange, 160-lb. Rating	BF4	4RHT3	AF14	2KWZ3
	Angle Bracket Attachment, Attaches #8 Wire or 1/4" Plain Rod to Ceiling, 160-lb. Rating	BH1-H7	4RHX4	708AB	2KWZ5
	Angle Bracket Attachment, Attaches 1/4" ATR or Stud to Ceiling, 160-lb. Rating	BH4-H7	4RHX6	4T1B	2KWZ4
	Rod Attachment with Hammer-On Beam Clamp, 1/8" to 1/4" Flange, 160-lb. Rating, Attaches 1/4" ATR or Stud	BH4-E-2-4	4RHX5	4T124	2KWX1
	Rod Attachment with Hammer-On Beam Clamp, 1/8" to 1/4" Flange, 160-lb. Rating, Attaches 3/8" ATR or Stud	BH6-E-2-4	4RHX7	—	—
	Metal Stud Grommet, Provides 360° Protection, Universal Design Fits All Factory Punched Metal Stud Holes	BM2	4RHZ7	ESG1	2KXC6
	Conduit and Cable Antirattle Support for FMC, EMT or ENT Conduit Size up to 1" Dia.	—	—	781	2KXC9
	Angle Bracket, 0.281 Dia. Holes, 25-lb. Rating	BH7	4RHX8	AB	2KXL2
	Signal Reference Grid Wire Clamp, Attaches #8 to #4 AWG Stranded Wire to 3/4" to 1" Round or Square Computer Floor Posts	BM5	4RHZ9	RG6	2KXL3
	Cable to Drop Wire Hanger, Fits 0.375 to 0.706" MC/AC Cable, 3/8" FMC, or 1/2" EMT, 20-lb. Rating	—	—	PCS1	2KXU3
	Conduit Angle Bracket, Supports Horizontal Runs of 1/2" or 3/4" EMT/Rigid/ENT Conduit Through Metal Studs	BG-8-12-H7	4RHW1	—	—
	S Hook, #11 Gauge, 29-lb. Rating; For Support of Lighting, Speakers and Other Fixtures	BH10	4RHX1	771	2KXK4
	Jack Chain, #12 Single, 100-lb., 29-lb. Rating; For Support of Lighting, Speakers and Other Fixtures	BH9	5GAR0	—	—
	Fixture Hanger, Side Mount, For Use With: Jack Chain, S-Hooks, and Fluorescent Fixtures; 29-lb. Rating	BH15	4RHX2	—	—
	Fixture Hanger, Top Mount, For Use With: Jack Chain, S-Hooks, and Fluorescent Fixtures; 29-lb. Rating	BH16	4RHX3	—	—