



6JJK8



31TP30



414X14

Duct-Mount Humidifiers

Add moisture to indoor air to make the space feel warmer, minimize static shocks, and help prevent wood surfaces from drying out. For use in office buildings, homes, and warehouses.

Bypass—Allow warm air from a building's furnace to pass over the humidifiers' water tray, and the air absorbs the water.

Fan-Powered—Use a fan to push air across the humidifiers' water tray allowing the air to absorb the water. Add more moisture to indoor air and can fit into smaller spaces than bypass models.

Steam—Have electrodes to create steam and add moisture to air that is moving through the HVAC system. Use less water to humidify the air than fan-powered and bypass models.

Note: Max. Sq. Foot Cap. is an approximation based on 8-ft. ceiling height.

Daily Humidification Output	Coverage Area	Humidity Settings	Plenum Opening Req.	Humidistat Control Modes	Overall HxWxD	Brand	Mfr. Model	Item No.
Humidifiers								
Bypass, Gravity Drain								
12 gal	2,000 sq ft	20% to 60%	9 7/8 in H x 9 5/8 in W	Automatic/Manual	14 in x 14 1/2 in x 10 1/8 in	Honeywell Home	HE150A1005	6JJK8
	2,000 sq ft	20% to 60%	9 7/8 in H x 9 5/8 in W	Manual	14 in x 14 1/2 in x 10 1/8 in	Honeywell Home	HE100A1000	6JJK7
	3,000 sq ft	30% to 60%	9 1/2 in H x 9 1/2 in W	Automatic/Manual	13 in x 15 1/2 in x 10 5/8 in	Aprilaire	500	31TP26
17 gal	2,500 sq ft	20% to 60%	12 1/2 in H x 9 3/4 in W	Automatic/Manual	17 1/2 in x 15 in x 10 1/8 in	Honeywell Home	HE200A1000	6JJK9
	2,500 sq ft	20% to 60%	12 1/2 in H x 9 3/4 in W	Automatic/Manual	17 1/2 in x 15 in x 10 1/8 in	Honeywell Home	HE250A1005	6JLJ0
	4,000 sq ft	30% to 60%	10 in H x 12 1/8 in W	Automatic/Manual	15 1/8 in x 15 1/2 in x 10 3/8 in	Aprilaire	600	31TP28
17 gal	4,000 sq ft	30% to 60%	12 3/4 in H x 10 in W	Manual	15 1/8 in x 15 1/2 in x 10 3/8 in	Aprilaire	600M	31TP29
	Bypass, Gravity Drain Optional							
17 gal	4,000 sq ft	30% to 60%	10 in H x 12 1/8 in W	Automatic/Manual	15 1/8 in x 15 1/2 in x 10 3/8 in	Aprilaire	400	31TP24
	4,000 sq ft	30% to 60%	10 in H x 12 1/8 in W	Manual	15 1/8 in x 15 1/2 in x 10 3/8 in	Aprilaire	400M	31TP25
Fan-Powered, Gravity Drain								
18 gal	3,000 sq ft	20% to 60%	14 1/8 in H x 13 1/2 in W	Automatic/Manual	16 3/4 in x 15 1/2 in x 10 3/8 in	Honeywell Home	HE300A1005	6JLJ1
	4,200 sq ft	30% to 60%	14 3/8 in H x 14 1/8 in W	Automatic/Manual	18 in x 15 1/8 in x 10 3/8 in	Aprilaire	700	31TP30
	4,200 sq ft	30% to 60%	14 3/8 in H x 14 1/8 in W	Manual	18 in x 15 1/8 in x 10 3/8 in	Aprilaire	700M	31TP31
Steam, Gravity Drain								
22 gal	4,000 sq ft	40% to 60%	—	—	20 1/8 in x 10 in x 7 in	Honeywell Home	HM750A1000/U	414X14
35 gal	6,200 sq ft	30% to 60%	—	—	21 in x 10 1/8 in x 7 1/8 in	Aprilaire	800	31TP32
								Compatible Mfr. Model No.
								Brand
								Item No.
								Brand
								Item No.

Replacement Pads

- 110, 220, 500, 500A, 500M, 550, 550A, 558
- 110, 220, 550, 558, HE100, HE150, HE220, HE225
- 350, 360, 560, 560A, 568, 600, 600A, 600M, 700, 700A, 700M, 760, 760A, 768
- 350, 360, 560, 568, 600, 700, 760, 769, HE200, HE250, HE260, HE265, HE300, HE360, HE365
- 360, 560, 560A, 568, 600, 700, 760, 760A, 768, Aprilaire 350, HC26A1008, HC26E1004, HE260A/B, HE265A/B, HE360A/B, ME360, WB2-17, WP2-18
- 400, 400A, 400M

* OEM replacements.

Ductable Dehumidifiers

Dry the air and help prevent mold, mildew, and odors in offices, schools, and other indoor spaces where continual moisture removal is needed. Can operate as a freestanding unit.

Ductable Dehumidifiers with Fresh-Air Intake—Separate control allows models to pull in fresh air from outside to dissipate stale air and help reduce trapped airborne contaminants in indoor areas.



443W15

Daily Water Removal Capacity (80F/60 RH)	Air Flow @ 0.0 in wg	Coverage Area	For Duct Dia.	Operating Humidity Range	Overall Height	Overall Width	Overall Depth	Brand	Mfr. Model	Item No.
Ductable Dehumidifiers										
65 pt	160 cfm	1,800 sq ft	8 in	0% to 90%	12 in	12 in	28 1/2 in	Honeywell Home	DR65A3000/U	443W15
80 pt	185 cfm	4,400 sq ft	10 in	40% to 60%	15 in	14 in	26 in	Aprilaire	E080	787CM7
100 pt	280 cfm	5,500 sq ft	10 in	40% to 60%	15 in	14 in	26 in	Aprilaire	E100	787CM8
Ductable Dehumidifiers with Fresh-Air Intake										
90 pt	320 cfm	2,800 sq ft	10 in	0% to 90%	19 3/8 in	14 3/8 in	32 3/8 in	Honeywell Home	DR90A3000/U	443W16
120 pt	400 cfm	3,500 sq ft	10 in	0% to 90%	20 1/2 in	14 3/4 in	32 3/8 in	Honeywell Home	DR120A3000/U	443W17
Filter Type										
Compatible Grainger Part No.		Performance Rating		Overall HxWxD		Brand		Mfr. Model		Item No.
Replacement Filter		443W16, 443W17		MERV 11		14 in x 17 1/2 in x 1 3/4 in		Honeywell Home		50070171-002/U
Pleated										20Y116



Heat Pump Reversing Valves and Solenoid Coils

Slide-type, 4-way valves. Solenoid coils include wiring harness.

Cap. in Tons (R-22)	Cap. in Tons (R-502)	Suction Tube I.D.	High Pressure Tube I.D.	Mfr. Model	Item No.
1.0 to 2.5	1.0 to 2.5	5/8 in	3/8 in	V2-410060-470	5AV34
1.0 to 5.0	1.0 to 5.0	5/8 in	1/2 in	V6-410280-170	5AV35
1.0 to 5.0	1.0 to 5.0	5/8 in	1/2 in	V6-41080-170	5AV36
3.0 to 8.5	3.0 to 11.9	1 1/8 in	1/2 in	V10-41080-170	5AV32
3.0 to 9.5	3.0 to 11.9	1 1/8 in	1/2 in	V10-418140-170	5AV33
Voltage	Watts @ 50 Hz	Watts @ 60 Hz	Mfr. Model	Item No.	
24	5 W	4 W	LDK-110000-070	5AV38	
208/240	5 W	4 W	LDK-410000-070	5AV39	



5AV39



Condensate Drain Pans

Rolled edges are easy on the hands.

Steel—Seamless, nestable pans have 2 possible drain outlet positions.

Plastic—Ribbed bottoms and reinforced corners for strength.



3HAJ3

Dim. (in.)*	Mfr. Model	Item No.
26-ga. Galv. Steel, 3/4" Drain Line Fitting & Plug		
48 27 2	6-M2748	3HAD7
60 30 2	6-M3060	3HAD8
Black Plastic, 3/4" PVC Fitting		
27 39 2	6-2739L	3HAK1
27 48 2	6-2748L	3HAJ5
27 63 2	6-2763L	3HAJ6
30 30 2	6-3030L	3HAJ4
30 50 2	6-3050L	3HAJ9
30 60 2	6-3060L	3HAJ3
32 63 2	6-3263L	3HAJ7
36 36 2	6-3636L	3HAJ8
36 60 2	6-3660L	3HAJ2

Accessories	Mfr. Model	Item No.
Condensation Flood Detector Switch	WS-1	6XJG7
Condensation Overflow Safety Switch	SOS-1	6XJH7
In-Pan Switch	CC-1	6XJH8

* L and W dimensions are for the base of the pan.



10L931

Sponge Rubber Seal Strip

Adhesive backing bonds to wood, metal, glass, and other smooth surfaces. For indoor use as weather stripping, cushion, insulator, seal, and gap-filler. Max. temp.: 200°F.

L	W	Thick-ness	Item No.
50 ft	0.5 in	3/8 in	10L933
50 ft	0.75 in	1/4 in	10L934
50 ft	1 in	1/8 in	10L935
50 ft	1 in	3/8 in	10L936
25 ft	0.75 in	1/8 in	10L931
25 ft	1 in	3/8 in	10L932