



EATON
by Schneider Electric

Air Conditioning Disconnect Switches


For indoor or outdoor use.

| Amps | Short Circuit Protection | For Use With | Max. HP @ 240V | W | H | D | Brand | Mfr. Model | Item No. |
|-------------------------|--------------------------|----------------|----------------|----------------------------------|-----------------------------------|----------------------------------|----------|---------------|----------|
| Polycarbonate | | | | | | | | | |
| 30 A 240V AC | Fuse | Class RK1 Fuse | 3 hp | 5 in | 8 ³ / ₄ in | 3 ¹ / ₂ in | Eaton | ACD221RNM-A2 | 5XHR5 |
| 60 A 240V AC | None | — | 10 hp | 5 in | 8 ³ / ₄ in | 3 ¹ / ₂ in | Eaton | ACD222URNM-A2 | 5XHR3 |
| 60 A 240V AC | Fuse | Class RK1 Fuse | 10 hp | 5 in | 8 ³ / ₄ in | 3 ¹ / ₂ in | Eaton | ACD222RNM-A2 | 5XHR4 |
| 60 A 240V AC | Circuit Breaker | — | 10 hp | 6 ¹ / ₂ in | 8 ³ / ₄ in | 3 ³ / ₄ in | Square D | QO200TRNM | 6HD95 |
| Galvanized Steel | | | | | | | | | |
| 30 A 240V AC | Fuse | Class H Fuse | 3 hp | 5 ¹ / ₂ in | 8 ³ / ₄ in | 3 ¹ / ₄ in | Eaton | DPF221R | 5XHR1 |
| 60 A 240V AC | None | — | 10 hp | 5 ¹ / ₂ in | 8 ³ / ₄ in | 3 ¹ / ₄ in | Eaton | DPU222R | 5XHP9 |
| 60 A 240V AC | None | — | 10 hp | 6 ³ / ₄ in | 11 ³ / ₄ in | 4 ¹ / ₂ in | Eaton | DPU222RFG20 | 5XHR2 * |
| 60 A 240V AC | Fuse | Class H Fuse | 10 hp | 5 ¹ / ₂ in | 8 ³ / ₄ in | 3 ¹ / ₄ in | Eaton | DPF222R | 5XHR0 |
| 60 A 240V AC | None | — | 10 hp | 4 ³ / ₄ in | 6 ¹ / ₂ in | 3 ³ / ₄ in | Square D | QO200TR | 1H245 |

* Includes 20A GFCI receptacle.

DIVERSITeCH

Equipment Pads



| Depth | Length | Width | Weight Cap. | Mfr. Model | Item No. |
|---|--------|-------|-------------|------------|----------|
| UltraLite Lightweight Concrete Composite Equipment Pad | | | | | |
| 3 in | 30 in | 30 in | 1,071 lb | UC3030-3 | 2YJ84 |
| | 36 in | 36 in | 1,547 lb | UC3636-3 | 2YJ85 |
| | 48 in | 24 in | 528 lb | UC2448-3 | 60KZ93 |
| | 48 in | 36 in | 624 lb | UC3648-3 | 2YJ83 |
| The Black Pad Plastic Equipment Pad | | | | | |
| 2 in | 30 in | 30 in | 1,188 lb | ACP30302 | 3HAD9 |
| | 36 in | 36 in | 1,452 lb | ACP36362 | 3HA2E |
| | 30 in | 30 in | 1,188 lb | ACP30303 | 3HA1E |
| 3 in | 36 in | 36 in | 1,452 lb | ACP36363 | 3HA3E |
| | 48 in | 36 in | 1,716 lb | ACP36483 | 3HA4E |

Mounting base for air conditioning units, filters, heaters, pool pumps, and refrigeration, or any type of equipment requiring weight distribution support. Ribbing allows self leveling and transfers load evenly. UV stable and vibration resistant.

DUCTMATE

Condensing Unit Braces

- Engineered wall-mount bracket for air conditioners, heat pumps, and other equipment
- No site preparation or leveling

No settling. Good for coastal and flood-prone areas or where hurricanes, snowfall, mud, or steep grades are a concern. Mounting fasteners not included.

Note: Because of the wide range of wall materials (brick, concrete, wood, etc.) the mounting is the responsibility of the installer.



| Description | Mfr. Model | Item No. |
|---------------|----------------|----------|
| 36" L x 30" W | GRAIRBRACE36GA | 6EKE2 |
| 45" L x 36" W | GRAIRBRACE45GA | 6EKE3 |
| 55" L x 48" W | GRAIRBRACE55GA | 6EKE4 |

DIVERSITeCH

Equipment Security Cages and Lock Set

Adjustable cages protect 1 or more condensers from copper theft. High-security padlocks have 2"-thick shackle to resist bolt cutters. Keyed alike for convenient control.



| Description | Mfr. Model | Item No. |
|---|------------|----------|
| A/C Condenser Security Cage, 16 ga. Steel, .1" tubing size, H Adjustable 34 to 59", W x D Adjustable 30 to 51" | ACGUB | 5ULD4 |
| Mini-Split Cage, 16 ga Powder Coated Steel, Adjusts From 32" H x 32" W x 12" D to 57" H x 45" W x 16 1/2" D, Includes 2 Locks | ACMS | 45MY32 |
| Padlock, Steel, For Use With Mfr. No. ACGU, Includes a Magnetic Hide-A-Key Box | ACL | 5ULD5 |


DIVERSITeCH

Equipment Mounting Accessories

Mounting Brackets—12-ga., powder-coated steel with prepunched holes; 600-lb. load rating. For hanging A/C condensers and heat pumps outside at any height.

Mounting Block—Raises furnace 1 1/2" for quiet, dry operation. Each block handles over 500 lb. Peel-and-stick installation.

Risers—Stable, sturdy, plastic risers elevate condensers, heat pumps and air handlers. Butyl mastic on top and bottom prevents slipping and reduces vibration and noise.




| Description | Pkg. Qty. | Item No. |
|--------------------------|-----------|----------|
| Mounting Brackets | | |
| 30" | 2 | 6XJH9 |
| 36" | 2 | 6XJH0 |
| 42" | 2 | 6XJH1 |
| Mounting Block | | |
| 6" x 4" x 2.35" | 1 | 6XJH6 |
| Risers | | |
| 3" Black | 1 | 6XJH3 |
| 6" Black | 1 | 6XJH4 |
| 3" Gray | 1 | 6XJG8 |
| 6" Gray | 1 | 6XJG9 |
| 12" Gray | 1 | 6XJH0 |
| 2-Pc., 3", Gray | 1 | 6XJH1 |
| 2-Pc., 6", Gray | 1 | 6XJH2 |
| 4" Extension | 1 | 6XJH5 |

DIVERSITeCH

Assembled Flexible Connector Whips

Liquid-tight conduit kits have 1 straight metallic connector and a removable 90° metallic connector for optional connections. 3 wire colors for easy hookup.



Note: Check your local codes for correct requirements.

| Conduit Dia. (in.) | Conduit L. (in.) | Wire Size | Mfr. Model | Item No. |
|--------------------|------------------|-----------|------------|----------|
| 1/2 in | 48 in | #10 THHN | 6-12-4 | 2YJ79 |
| 1/2 in | 72 in | #10 THHN | 6-12-6 | 2YJ80 |
| 3/4 in | 48 in | #8 THHN | 6-34-4 | 2YJ81 |
| 3/4 in | 72 in | #8 THHN | 6-34-6 | 2YJ82 |

Streamline

A BRAND OF MUELLER INDUSTRIES

Insulated Copper Tube Line Sets

Refrigeration-grade copper tubing and insulation preassembled and packaged together for efficient installation of split systems.



Note: Prices subject to change without notice. Call 1-800-GRAINGER (472-4643) for current market price.

| Liquid Line Size (in.) | Suction Line Size (in.) | L. (ft.) | Insulation Thickness (in.) | Mfr. Model | Item No. |
|------------------------------|-------------------------|----------|----------------------------|--------------|----------|
| Refrigerant Line Sets | | | | | |
| 1/4 OD | 3/8 OD | 35 ft | 1/2 in | 40620350B6 | 4E965 * |
| | 3/8 OD | 50 ft | 1/2 in | 40620500B6 | 38N857 * |
| | 1/2 OD | 35 ft | 1/2 in | 40820350B6 | 4E967 * |
| | 1/2 OD | 50 ft | 1/2 in | 40820500B6 | 38N858 * |
| | 3/8 OD | 35 ft | 1/2 in | 41020350B6 | 4E969 |
| | 3/8 OD | 50 ft | 1/2 in | 41020500B6 | 38N859 * |
| 1/4 OD Flared Ends | 3/8 OD Flared Ends | 35 ft | 1/2 in | 40620350B3B6 | 38N861 * |
| | 3/8 OD Flared Ends | 50 ft | 1/2 in | 40620500B3B6 | 38N860 * |
| | 1/2 OD Flared Ends | 35 ft | 1/2 in | 40820350B3B6 | 38N863 * |
| | 1/2 OD Flared Ends | 50 ft | 1/2 in | 40820500B3B6 | 38N862 * |
| | 3/8 OD Flared Ends | 35 ft | 1/2 in | 41020350B3B6 | 1CNP5 * |
| | 3/8 OD Flared Ends | 50 ft | 1/2 in | 41020500B3B6 | 38N864 * |
| 3/8 OD | 3/8 OD | 15 ft | 1/2 in | 61020150B6 | 6XZ53 * |
| | 3/8 OD | 30 ft | 1/2 in | 61020300 | 38N856 |
| | 3/8 OD | 35 ft | 1/2 in | 61020350B6 | 6XZ54 * |
| | 3/8 OD | 50 ft | 1/2 in | 61020500B6 | 12T748 * |
| | 3/8 OD | 50 ft | 1/2 in | 61020500 | 38N855 |
| | 3/4 OD | 30 ft | 1/2 in | 61220300 | 6XZ57 |
| | 3/4 OD | 30 ft | 1/2 in | 61220301 | 4E871 † |
| | 3/4 OD | 50 ft | 1/2 in | 61220500 | 6XZ58 |
| | 3/4 OD | 50 ft | 1/2 in | 61220501 | 4E870 † |
| | 7/8 OD | 30 ft | 1/2 in | 61420300 | 6XZ61 |
| | 7/8 OD | 30 ft | 1/2 in | 61420301 | 3F346 † |
| | 7/8 OD | 50 ft | 1/2 in | 61420500 | 6XZ62 |
| 3/8 OD Flared Ends | 1 1/8 OD | 50 ft | 1/2 in | 61820500 | 3F347 † |
| | 1 1/8 OD | 50 ft | 1/2 in | 61820500 | 1EWH2 * |
| | 3/8 OD Flared Ends | 35 ft | 1/2 in | 61020350B3B6 | 38N866 * |
| | 3/8 OD Flared Ends | 50 ft | 1/2 in | 61020500B3B6 | 38N865 * |
| | 3/8 OD | 30 ft | 1/2 in | 51020300 | 3F342 |
| | 3/8 OD | 30 ft | 1/2 in | 51220300 | 3F344 |
| 3/4 OD | 3/4 OD | 50 ft | 1/2 in | 51220500 | 3F345 |

* Both lines are insulated. † 90° bend on end of line.

| Item | Connec. Size | Mfr. Model | Item No. |
|----------------------------------|--------------------------|------------|----------|
| Fittings | | | |
| 1/4" Flare Gasket | 1/4 in | A 00401 | 38N874 |
| 1/4" SAE Cap | 1/4 in | A 16447 | 38N867 |
| Copper Flare Seal Bonnet | 1/4 in | A 04544 | 38N868 |
| Flare Bushing | 1/4 in | A 00414 | 38N885 |
| | 5/8 in x 1/4 in | A 07813NL | 38N872 |
| | 5/8 in x 1/2 in | A 07812NL | 38N878 |
| Flare Fitting | 1/4 in SAE M x 1/4 MPT | A 04585 | 38N875 |
| | 1/4 in SAE M x 1/2 MPT | A 00330 | 38N883 |
| | 1/4 in SAE M x 3/4 SAE M | A 00325 | 38N884 |
| | 3/8 in SAE M x 3/8 SAE M | A 00327 | 38N886 |
| Flare Fitting 90 Degrees | 1/4 in SAE x 1/2 in NPT | A 00335 | 38N881 |
| Flare Gasket | 3/8 in | A 00402 | 38N882 |
| | 1/4 in | A 05051 | 38N869 |
| Flare Nut | 3/8 in | A 05052 | 38N870 |
| | 1/2 in | A 05053 | 38N871 |
| | 3/8 in | A 05157 | 38N879 |
| Half Union Connector | 1/2 in x 1/2 in | A 04780 | 38N877 |
| | 1/4 in x 1/4 in | A 15725 | 38N876 |
| Swivel FE Flare X Solder Adapter | 3/8 in x 3/8 in | A 15726 | 38N873 |
| | 1/2 in x 1/2 in | A 15727 | 38N880 |