

1-800-GRAINGER (472-4643)



Single-Zone Ductless Mini-Split Systems with Wall-Mount Air Handler

- Cooling/Heating, Heat Pump
- WiFi-capable
- Seacoast Protection guards against corrosion
- Programmable
- Remote Control

Include a condenser and a wall-mount air handler for standard installations. New installations require refrigerant line set, sold separately on Grainger.com.



55MN54

Cooling Cap.	Average Coverage Area	Heating Cap. - Heat Pump	SEER	Voltage	Indoor Head Height	Indoor Head Width	Indoor Head Depth	Mfr. Model	Item No.
9,000 BtuH	350 to 400 sq ft	10,500 BtuH	19.5	115V AC	11 1/8 in	33 3/8 in	8 1/2 in	FPHW091A	55MN54
9,000 BtuH	350 to 400 sq ft	10,500 BtuH	22.5	208/230V AC	11 1/8 in	33 3/8 in	8 1/2 in	FPHW093A	55MN56
12,000 BtuH	450 to 550 sq ft	14,000 BtuH	22	115V AC	11 1/8 in	33 3/8 in	8 1/2 in	FPHW121A	55MN55
12,000 BtuH	450 to 550 sq ft	14,000 BtuH	22	208/230V AC	11 1/8 in	33 3/8 in	8 1/2 in	FPHW123A	55MN57
18,000 BtuH	700 to 1,000 sq ft	19,500 BtuH	23.3	208/230V AC	13 1/8 in	45 1/8 in	10 in	FPHW183A	55MN58
23,500 BtuH	1,200 to 1,400 sq ft	26,500 BtuH	21	208/230V AC	13 1/8 in	45 1/8 in	10 in	FPHW243A	55MN59
36,000 BtuH	2,000 to 2,500 sq ft	28,000 BtuH	16.4	208/230V AC	13 1/8 in	50 1/8 in	10 1/4 in	FPHW363B	55MN60



Single-Zone Split System with Heat Pump

- 208/230VAC
- Cooling/Heating, Heat Pump
- Seacoast Protection guards against corrosion
- Programmable
- Remote control



55MN60

Includes a condenser and a wall-mount air handler for standard installations. The air handler fastens to a wall (typically near the ceiling) to blow cooled or heated air into a single room or area. This wall-mount system is typically easier to reach for installation and maintenance compared to ceiling-mount systems.



Ductless Split System Air Conditioners

- 208/230VAC
- Cooling/Heating
- Programmable: 785WT3 only



785WT3—Compact cassette unit installs in a suspended ceiling and mounts flush to the ceiling to ease installation and for a clean appearance.

785WT2—Concealed duct unit installs in the ceiling or furr down for an unobtrusive installation.

Cooling Cap.	Average Coverage Area	Heating Cap. - Heat Pump	SEER	Indoor Head Height	Indoor Head Width	Indoor Head Depth	Mfr. Model	Item No.
36,000 BtuH	2,000 to 2,500 sq ft	36,000 BtuH	19.5	11 3/4 in	33 1/2 in	33 1/2 in	FPHC363A	785WT3
24,000 BtuH	1,400 to 1,500 sq ft	28,000 BtuH	18	10 1/8 in	35 1/8 in	28 1/8 in	FPHD243	785WT2



55MN75



55MN74



Ductless Mini-Split Accessories

These accessories are made for Friedrich ductless mini-split air conditioners to ensure compatibility and proper function.

For Universal Ductless Mini-Split Accessories, go to Grainger.com.

Description	Mfr. Model	Item No.
Cassette Grille, For use with Friedrich Ductless Cassette Larger BTU	FPCG182436	55MN76
Cassette Grille, For use with Friedrich Ductless Cassette Smaller BTU	FPCG0912	55MN75
Wall Controller, For use with All Friedrich Ductless Split Systems	FPWC1	55MN74



Ceiling Air Conditioner

- Air-cooled, vented

Slim top-to-bottom profile fits above drop ceilings. Intake and exhaust flanges connect to ceiling ducts to cool computer rooms, telecom closets, offices, and healthcare facilities. Unit hardwires into an electrical circuit and has built-in mounting brackets for attaching to ceiling down rods.



36P688

Cooling Cap.	Average Coverage Area	Voltage	Sound Level	H	W	D	Mfr. Model	Item No.
10,500 BtuH	400 to 450 sq ft	115V AC	52 dB	15 1/2 in	32 in	20 in	CM12	36P688

Description	Mfr. Model	Item No.
Accessories		
Condenser Intake Air Plenum, For Use With Mfr. No. CM12	481769-0221	36P692
Exhaust Air Flange, For Use With CM25	481170-0191	36P694
Exhaust Air Flange, For Use With Mfr. No. CM12	481170-0440	36P691
Millivolt Thermostat, For Use With Classic 40, Classic 60, and CM12	LA484500-3430	36P693