

1-800-GRAINGER (472-4643)



USB Chargers

Ports	Brand	Item No.
12V/DC USB Charger		
(1) 2.4 Amp USB/(2) 12V/DC Ports	Mobilespec	55FC57
(1) 3.0 Amp USB/(1) 2.4 Amp USB/	Mobilespec	55FA10
(1) 2.4 Amps USB-C ports	Mobilespec	450X45
(4) 2.4 Amp USB ports	Mobilespec	450X45
Charge and Sync Cable		
(1) 2.4 Amp USB port/6 ft cable Micro Connector	Mobilespec	55FA15
USB Wall Outlet Charger		
(1) 2.5 Amp USB port	Tripp Lite	490X01
(2) 2.4 Amp USB ports	Mobilespec	55FA05



Power Banks and External Batteries

Capacity	Number of Output Connectors	Recharge Time	Input Connector	Output Connection Type	Item No.
Ability One					
12,000 mAh	2	3 hr	—	Female USB Type A	56LF39
Cat					
10,000 mAh	1	10 hr	Micro USB	Female USB Type A	420C73
Ego					
1.2 Ah	2	1 hr	Micro USB	Female USB Type A	55JG50
Milwaukee					
2,000 mAh	1	2 hr	Micro USB	Female USB Type A	55VT10
	1	2 hr	Micro USB	Female USB Type A	55VT11
Mobilespec					
2,600 mAh	1	4 hr	AC Prong	Female USB Type A	55FA12

*Kit includes a REDLITHIUM USB Battery, USB Rechargeable Power Source and Charger, 2 FT Heavy Duty Micro-USB Cord

USB Tester and Data Masker

Dual output for charging two USB devices off of one USB 3.0 port; One port is a specially designed masked port to charge your phone or tablet without any data being transferred. Built-in Smart Chip for Intelligent Charging that allows it to determine the safest maximum current your PD can accept.



Connector Type	Dim.	Item No.
USB 2.0 or 3.0	2.7 in L x 1 in W x 4.7 in H	55EP46



Charger/Sync Cables

Description	Cable Length	Color	Item No.
Cat			
Lightning® to USB	10 ft	Black	488H50
Micro to USB	10 ft	Black	488H51
USB-C to USB	10 ft	Black	783AH8
Mobilespec			
Lightning® to USB	3 ½ in	White	55FA28
Lightning® to USB	3 ft	Black	55FA43
Lightning® to USB	3 ft	White	55FA44
Lightning® to USB-C	6 ft	White	55FA58
Micro to USB	6 ft	Black	450X55
Mini, Micro, Samsung®, PSP® and Nintendo® to USB	3 ft	Black	450X71
USB-C to USB	6 ft	Black	55FA49



Device Charging Stations

Stations provide a hub for simultaneously recharging multiple cell phones or mobile devices. They're typically used in meeting rooms, waiting areas of airports and medical facilities, common areas of schools and multiunit residences, conference centers, and public libraries.

Charging Cord Configuration	Charges Up To	Item No.
Wall		
(2) 9 in Micro USB, (3) 9 in Lightning, (3) 9 in Type C cables	8 Devices	45UC03
Pedestal		
(2) 9 in Micro USB, (3) 9 in Lightning, (3) 9 in Type C cables	8 Devices	45UC06
Desktop		
(2) 9 in Micro USB, (3) 9 in Lightning, (3) 9 in Type C cables	8 Devices	45UC18
Charging Locker		
(4) 12 in Micro USB, (6) 12 in Lightning, (6) 12 in Type C cables	—	499F81
(4) 12 in Micro USB, (6) 12 in Lightning, (6) 12 in Type C cables	—	499F82

Sign in to **Grainger.com**® to see **YOUR Pricing** and **MORE**