



## Self-Righting Floor Lights



Self-righting floor lights won't tip over, so they withstand use in rugged, high-traffic settings. They wobble on their rounded, weighted base to deflect accidental blows and set themselves upright after impact.

Maximum Brightness	Operating Voltage	Power Cord Length	IP Rating	Maximum Height Adjustment	Frame Color	Mfr. Model	Item No.	
<b>Self-Righting Floor Lights</b>								
<b>LED</b>								
6,000 lm	120V AC	5 ft	Not Rated	25 in	Yellow	111208	787KG3	
10,000 lm	120V AC	5 ft	Not Rated	15 in	Yellow	111211	800WF3	
12,000 lm	120V AC	5 ft	IP54	33 in	Black/Yellow	111301LED	800WE8	
15,000 lm	120V AC	5 ft	IP55	32 in	Black/Yellow	111303LED	422V06	
<b>Metal Halide</b>								
40,000 lm	120V AC	—	IP54	36 in	Yellow	111104PS	12LTE9	
<b>Accessories &amp; Replacement Parts for 360-Degree Jobsite Lights</b>								
Item						Compatible with Manufacturer Model Number		Item No.
Reflector Shield						111203, 111204, 111205, 111206		1XFK8
						111102, 111104, 111301LED, 111302, 111303LED		2WA36
Replacement Bulb						111302		3KYN8
Replacement Sr Dome with Cap						111102, 111104, 111302		5GDZ8
Ballast Kit - 175						WL175MH-G		5GEA0
Ballast Kit - 400						WL400MH-G		5GEA2



## Balloon Lights

The oversized head of tripod balloon lights produces soft, diffuse illumination to reduce glare, minimize shadows, and create a more natural lighting effect than other jobsite lights.



Southwire®

Maximum Brightness	Operating Voltage	Power Cord Length	IP Rating	Maximum Height Adjustment	Frame Color	Brand	Item No.
<b>Tripod Balloon Lights</b>							
<b>LED</b>							
19,200 lm	120V AC	25 ft	IP54	11.33 ft	Black/Silver	Powermoon	444P65
24,000 lm	120V AC	15 ft	Not Rated	9 ft	White	Southwire	800W97
26,000 lm	110/230V AC	16 ft	IP65	9.8 ft	Blue/White	8:12 Illumination	443W24
40,000 lm	110/230V AC	25 ft	IP54	12.08 ft	Black/Orange	Powermoon	444P62
56,000 lm	110/230V AC	16 ft	IP65	9.8 ft	Blue/White	8:12 Illumination	443W25
75,000 lm	120V AC	23 ft	IP54	12 ft	Black/Orange	Powermoon	444P66
110,000 lm	110/230V AC	16 ft	IP65	9.8 ft	Blue/White	8:12 Illumination	443W26
	120V AC	25 ft	IP54	12 ft	Black/Orange	Powermoon	444P61
<b>Metal Halide</b>							
110,000 lm	120V AC	16 ft	IP65	24 in	Blue/White	8:12 Illumination	443W27
<b>Hanging Balloon Lights</b>							
<b>LED</b>							
75,000 lm	110V AC	25 ft	IP54	—	Black/Orange	Powermoon	444P63
110,000 lm	110V AC	25 ft	IP54	—	Black/Orange	Powermoon	444P64



## Jobsite Lights Cart Lights



Cart lights tip back to roll on their wheeled base for positioning and moving them between locations. They generate high-output light to illuminate large areas.

Maximum Brightness	No. of Brightness Levels	No. of Lamp Heads	Operating Voltage	Power Cord Length	IP Rating	Maximum Height Adjustment	Brand	Item No.
<b>Cart Lights</b>								
<b>LED</b>								
11,000 lm	1	2	120V AC	12 ft	IP65	10 ft	Southwire	61KH52
22,000 lm	1	1	120V AC	12 ft	Not Rated	10 ft	Southwire	785TU3
44,000 lm	1	4	120V AC	12 ft	Not Rated	33 in	Southwire	800WF2
44,000 lm	1	2	120V AC	12 ft	Not Rated	12 ft	Southwire	785TU4
<b>Metal Halide</b>								
110,000 lm	1	1	120V AC	8 ft	—	12 ft	Bulldog	9DPR0
220,000 lm	1	2	120V AC	8 ft	—	12 ft	Warner Tool Products	9UCE8



## LED Hazardous Location Work Lights



Lights illuminate areas where flammable, combustible, or ignitable materials are present. They keep arcs and sparks contained to reduce the risk of becoming a source of ignition for a fire or explosion.

Maximum Brightness	No. of Lamp Heads	Operating Voltage	Power Cord Length	IP Rating	Maximum Height Adjustment	Mount Type	Brand	Item No.
<b>Classification Class I Div. 1, Class I Div. 2, Class II Div. 1, Class II Div. 2</b>								
12,000 lm	1	120/277V AC	100 ft	IP67	66.58 in	J-Bracket	Larson Electronics Llc	31KZ69
<b>Classification Class I Div. 1, Class I Div. 2, Class II Div. 1, Class II Div. 2, Class III Div. 1, Class III Div. 2</b>								
12,000 lm	1	120/277V AC	250 ft	IP67	29 in	Cart	Larson Electronics Llc	31KZ64
<b>Classification Class I Div. 1, Class II Div. 1</b>								
5,600 lm	1	90 to 277V AC	50 ft	IP65	11 in	Yoke	Lind Equipment	785TX1
	1	90 to 277V AC	50 ft	IP65	11 in	Yoke	Lind Equipment	785TX2
24,000 lm	2	90 to 277V AC	50 ft	IP65	11 in	Tripod, Yoke	Lind Equipment	785TX3
	1	90 to 277V AC	50 ft	IP65	14 in	Yoke	Lind Equipment	785TX4
29,580 lm	1	90 to 277V AC	50 ft	IP65	14 in	Yoke	Lind Equipment	785TX5
	<b>Classification Class I Div. 2, Class II Div. 1, Class II Div. 2, Class III Div. 1, Class III Div. 2</b>							
29,580 lm	2	120/277V AC	100 ft	IP67	12.42 ft	Tripod	Larson Electronics Llc	31KZ68