FLUKE.

Removable Screen Digital Multimeters

Full size

• CAT III 1000V; CAT IV 600V rated Display can be detached from meter and mounted up to 33 ft. away for easy, hands-free viewing. The meter stays connected to the test point while the operator can maintain a safe distance. Ideal for hazardous situations such as moving machinery, automotive diagnostics, or applications that produce arc flash. Functions as a standard multimeter when screen is attached. Includes built-in thermometer, batteries, and test leads.



												CALIBRATION CERTIFICATE	
	Max.	Max.										Not Included	Included
AC Response	Current	Voltage	Instrument									Item	Item
Calculation	(AC/DC)	(AC/DC)	Counts	AC Current	AC Voltage	Capacitance	DC Current	DC Voltage	Frequency	Resistance	Temp. Type	No.	No.
TRMS	10 A	1000 V	6000	•	•	•	•	•	•	•	K	4GUE6	4GUE7



Analog Multimeters

Instruments use color-coded test leads to measure electrical currents and display readings on an analog scale. Can be used to monitor fluctuations and trends and will not freeze up in severe hot or cold environments. Include batteries and test leads.

Triplett—29FK30 to 29FK33 are specially designed for measurement tasks on railroad coding equipment. 29FK34 to 29FK36 are designed for use by telephone industry workers. Simpson—4CWP2 is specifically designed for railroad testing. 1770

designed for railroad testing. 1T779 and 1T848 feature a resettable relay overload protection circuit. 1TC61 and 1TC62 have high visibility cases that offer protection from drops and impact.



1A587



29FK30

Max. Voltage (AC/DC)	Max. AC Current	Max. DC Current	AC Current	AC Voltage	DC Current	DC Voltage	Multimeter Features	Brand	CALIBRATION Not Included Item No.	CERTIFICATE Included Item No.
300 V	—	600 mA		•	•	•	_	Triplett	29FK36	61NZ68
	30 A	30 A	•	•	•	•	60Hz and 100Hz Cab Filters	Triplett	29FK33	61NZ65
	30 A	30 A	•	•	•	•	100Hz and 200Hz Cab Filters	Triplett	29FK32	61NZ64
	30 A	30 A	•	•	•	•	100Hz and 250Hz Cab Filters	Triplett	29FK31	61NZ63
	30 A	30 A	•	•	•	•	_	Triplett	29FK30	61NZ62
600 V -	—	600 mA		•	•	•	_	Triplett	29FK35	61NZ67
	30 A	30 A	•	•	•	•	_	Simpson Electric	4CWP2	_
1000 V	—	10 A		•	•	•	Overload Protection	Simpson Electric	1T779	_
	—	10 A		•	•	•	_	Simpson Electric	1A587	_
	—	10 A		•	•	•	Roll Top Case; Overload Protection	Simpson Electric	1T848	_
	—	10 A		•	•	•	Bright Yellow Case; Overload Protection	Simpson Electric	1TC62	_
	_	10 A		•	•	•	Bright Yellow Case	Simpson Electric	1TC61	_
1200 V	_	600 mA		•	•	•	_	Triplett	29FK34	61NZ66

Sign in to Grainger.com[®] to see YOUR Pricing and MORE