



FLUKE

Holsters

Attach to belt loops to securely hold and protect compatible meters. Provide hands-free transport while keeping instruments easily accessible when needed.

4YE79 is a rigid plastic holster with a magnetic hanging strap. **4PD22 and 60YD83** are durable fabric holsters.

5PR86 is made from cowhide leather with a top flap that snaps shut to securely hold meter.

For Use With	Color	Wrist Strap	Belt Loop Included	Weather-Resistant Zipper	Overall Height	Overall Width	Overall Depth	Item No.
Synthetic Material								
787 Series, Mfr. No. 80/710 Series	Yellow	No	Yes	No	2 in	4 1/4 in	8 in	4YE79
Fluke T3 and T5 testers	Black/Yellow	No	Yes	No	13 1/4 in	1/4 in	3 in	4PD22
T6-600 and T6-1000 Electrical Testers	Black	No	Yes	No	7 1/2 in	3 1/2 in	1 1/2 in	60YD83
Leather Material								
Mfr. No. T3/T5	Brown	No	Yes	No	2 in	3 in	10 in	5PR86



29VM15



Energy Management Systems

- Color touchscreen
- 8 channels: 4 current and 4 voltage

Systems interface with electrical equipment and devices for continuous monitoring and diagnostics. Users can select length and mode of data collection including troubleshooting, data logging, power quality surveys, energy and load balancing. Automated setups ensure the instrument is ready to collect data. Include Dran-View software for data review and analysis. Systems pinpoint harmonic irregularities, swells, unbalance, and dips in energy. Allow electricians, operators, and facility maintenance personnel to view data in real time and proactively troubleshoot to streamline production, maximize efficiency, and reduce energy costs.

29VM12 to 29VM14 include clamp-on current probes. **29VM15 and 29VM16** include flexible current probes, ideal for use in tight spaces.

Current Range	For Phase	Includes	Item No.
1 to 10A	Three	AC Adapter, Alligator Clips, Carry Case, Current Probes, Voltage Cable Set	29VM12
1 to 100A	Three	AC Adapter, Alligator Clips, Carry Case, Current Probes, Voltage Cable Set	29VM14
10 to 500A	Three	AC Adapter, Alligator Clips, Carry Case, Current Probes, Voltage Cable Set	29VM13
30 to 3000A	Four	Carry Case, Current Probes, Voltage Cable Set	29VM15
60 to 6000A	Three	AC Adapter, Alligator Clips, Carry Case, Current Probes, Voltage Cable Set	29VM16



Appliance Tester 29JA21

Continuity/Ground Bond Lead 11N131

Barcode Scanner 29JA22

Megger

Tool and Appliance Testers

- Full color display

Portable units perform insulation resistance, leakage current, and ground bond tests to ensure safe operation of electrical equipment. Digital display indicates if the tool has passed or failed specified test parameters with user selectable pass/fail limits. Use for testing handheld power tools, equipment, and appliances in commercial and industrial facilities.

11N130—Features automatic or manual mode with selectable test time duration.

29JA21—Features memory capacity for storing up to 10,000 test results, and performs 1.5 kV and 3 kV flash testing. USB communication for data download.

Testing Functions	Current Range	Leakage Current Measured	High Voltage Test	Insulation Resistance Test Voltage	Item No.
General Purpose Tool & Appliance Testers					
Ground Bond Integrity, Ground Leakage, Insulation Resistance	10, 25 and 200mA	0 to 19.99 mA	—	250V DC, 500V DC	11N130
Earth Bond, Insulation Resistance	10 to 25A	0 to 19.99 mA	3,000 kV AC	250V DC, 500V DC	29JA21
Compatible with Grainger Part Number					Item No.
Accessories for Tool & Appliance Testers					
Continuity/Ground Bond Lead				11N130	11N131
Barcode Scanner				11N130	29JA22



53RU31



GOSSEN METRAWATT

Medical Device Testers

- Meet EN 60601 and IEC 62353 safety standards

Portable instruments analyze electrical functions of medical equipment such as nebulizers, infusion pumps, ventilators, incubators, and other laboratory equipment to ensure safe and proper operation.

53RU31—Color-coded user interface for easy selection of required tests with one key press.

30PR89—Automatic test sequences comply with safety standards for testing of electrical medical devices. Convenient memory and report generating functions.

30PR91—Designed to test medical devices operated with 3-phase electrical current. Internal memory for up to 125 tests.



30PR91

Testing Functions	Current Range	Leakage Current Measured	High Voltage Test	Insulation Resistance Test Voltage	Brand	Item No.
Equipment Leakage, Ground Bond Integrity, Ground Leakage, Line Frequency, Line Voltage, Load Current, Point-to-Pointing, Touch Leakage, Touch Voltage	0 to 20A	0.1 to 9,999 uA	—	—	Seaward	53RU31
Insulation Resistance, Leakage Current	0 to 10A	0 to 120 mA	6 kV DC	3.7kV DC	Gossen Metrawatt	30PR89
Insulation Resistance, Leakage Current	0 to 16A	0 to 310 uA	5 kV DC	3.7kV DC	Gossen Metrawatt	30PR91