

## Megger.

# **Cable Height Meters**

- Measures up to 6 cables or wires simultaneously
- Selectable display in feet and inches or meters

Compact instruments use sound waves that reflect off overhead telephone, cable, distribution, and transmission lines to quickly and safely determine their distance from the ground as well as spacing from each other. No physical connection to cables is required. Built-in temperature sensor ensures accurate readings. Batteries are included.



3GZX7

Measurement Range for ½ in Cable	Measurement Range for 1 in Cable	Item No.
7 to 35 ft	7 to 35 ft	3GZX7
10 to 50 ft	10 to 50 ft	3GZX8
10 to 50 ft	10 to 75 ft	3GZX9









### **AC Current Line Splitters**

- Max. current measured: 15 A
- Current multiplier loop: X1, X10

Plug into outlets to measure the amount of voltage used by electrical tools, devices, and household appliances. Include a receptacle for connecting devices to be measured; once device is connected, a clamp meter is fastened around the splitter to read electrical current. Provide quick readings without manually splicing individual wires to separate hot from ground and neutral wires in electrical outlets.



Max. Voltage	CAT Safety Rating	Tool Height	Tool Length	Tool Width	Brand	ltem No.
120V AC	CAT II 300V	9.5 in	3.6 in	1.1 in	Triplett	347FD2
120V AC	CAT II 600V	5.3 in	1 in	2 in	Extech	3ZH94
120V AC	CAT II 600V	5.3 in	1 in	2 in	FLIR	35KP95
250V AC	CAT II 600V	6.3 in	1.3 in	2.3 in	Supco	55AC67

# KeepStock\* Inventory Management

#### TAKE CONTROL OF YOUR STUFF

What if there were an easier way to ensure you have the right parts in the right place at the right time? Put Grainger's expertise to work for you. It's almost like managing your inventory on autopilot.

Inventory managed. Space organized. Time and money saved.


Grainger KeepStock solutions are subject to customer eligibility and agreements.

Learn more at grainger.com/keepstock






Portable, Straight Cord w/ Small Drum Clamps 33UC50



Wall-Mount, Straight Cord w/ **Lugs & Large Truck Clamp** 33UC47



Small Clamp Assembly w/Coiled Cable 33UC54



Lug Cable Assembly 33UC52



## **Static Monitoring Systems**

- Safety rating: cULus for Class 1, Div 1 and 2, Groups ABCD; Class 2, Div 1 and 2, Groups FG
- Resistance setting: 5 ohms

Intrinsically safe StaticSure device ensures proper grounding when transferring flammable materials. Static discharge generated when handling flammables can cause explosions or fires, and bonding or grounding must be confirmed to dissipate static charge and ensure safe work environments. StaticSure unit continuously measures resistance between the end points of the unit to verify proper bonding. A red light flashes to indicate a danger of static discharge and alert that there is an improper static bond or ground connection. Helps comply with safety regulations for applications with drums, fuel transfer, chemical mixing, and truck or railcar loading and unloading.

Combo units are assemblies composed of the StaticSure unit between two cords with clamps or lugs at the ends. Portable units can be carried to needed location and have clamps at both cord ends. Wall-mount units are for permanent installation and have lugs on one cord end for easy attachment to known grounding point.

Includes	L	item No.
StaticSure Unit		
Pair of U-Clamps is provided in the package, for mounting of the StaticSure Unit.	6 in	33UC51
StaticSure Combo Units		
Portable		
2 ft Straight Cord with Small Drum Clamp, 20 ft Coiled Cord with Small Drum Clamp	22 ft	33UC50
2 ft Straight Cord with Large Truck Clamp, 20 ft Coiled Cord with Large Truck Clamp	22 ft	33UC49
Wall Mount		
2 ft Straight Cord with Lugs, 20 ft Coiled Cord with Small Drum Clamp	22 ft	33UC48
2 ft Straight Cord with Lugs, 20 ft Coiled Cord with Large Truck Clamp	22 ft	33UC47
Accessories For Use with 33UC51		
Small Clamp Assembly		
2 ft Straight Cable with Small Drum Clamp and Quick Connect	_	33UC55
20 ft Coiled Cable with Small Drum Clamp and Quick Connect	_	33UC54
Large Clamp Assembly		
2 ft Straight Cable with Large Truck Clamp and Quick Connect	_	33UC56
20 ft Coiled Cable with Large Truck Clamp and Quick Connect	_	33UC53
Lug Cable Assembly		
2 ft Straight Cable, Lugs and Quick Connect		33UC52

534