1PX61

### **Combination Tachometers**

### **EXTECH**

#### MONARCH INSTRUMENT **AMPROBE**



SHIMPO



surface and noncontact measurement choices. Each includes batteries. NIST models include certificate and calibration documents.

#### **EXTECH**

**Tachometers and Laser Tachometers**—Laser light source, except 8PMK7 and 22DC94 have visible light source. Each includes tip(s) and wheel for contact readings and reflective tape for noncontact.

41D940 and 41D941 also measure length

Handheld instruments offer 
Tachometers with Infrared Thermometer—Make contact/noncontact speed measurements and noncontact surface temperature measurements.

■ IR temp. range -4° to 600°F

#### **AMPROBE**

Tachometer 6NZG4—Makes contact/noncontact speed measurements with noncontact rpm. Infrared light source. Features selectable units in contact mode and data hold. Includes cone and funnel contact tips and reflective tape.

Tachometer 4FKR9—Measures sensor 3WB47, sold separately on rotational and surface speed, with page 542. Tripod mountable. selectable rpm/length units using the infrared beam or adapter. Includes 6 adapters, reflective tape, and carrying case.

 Meter/foot/inch length measurements

#### MONARCH INSTRUMENT

### **Laser Tachometer and**

Kit-Pocket Laser Tach 200 is a 32-function tachometer/ratemeter, totalizer/counter, and timer (stopwatch). Fixed decimal points. TTL compatible pulse output can trigger data collectors or stroboscopes. Accepts remote optical

Instrument 4YE86 includes 12" reflective tape. Kit 4YE87 adds remote contact assembly with concave and convex tips, 10cm linear scope wheel, 5-ft. reflective tape, and carrying case.

#### SHIMPO

Tachometers—Measure rotational, linear, and surface speed plus total length. 10-measurement memory. Complete with 2 cone tips, funnel tip, extension shaft, and carrying case. Speed wheel included: 6" with 21YD75 and 21YD76, 12" with 21VD77 and 21VD78



measure lengur.				211	DII aliu ZITDIO.					
Description	Speed (FPM)	Noncontact RPM Range	Contact RPM Range	RPM Accuracy	Memory	Display	Calibration Certificate		Mfr. Model	Item No.
Extech										
	0 to 6560	2 to 99,999	2 to 20,000	+/-0.05% +1 Digit	10 Data Sets	Backlit LCD	No	1.6 ft	RPM33	41D940
Laser	0 to 6560	2 to 99,999	2 to 20,000	+/-0.05% +1 Digit	10 Data Sets	Backlit LCD	Yes	1.6 ft	RPM33-NIST	41D941
Tachometers	0.20 to 6560	10 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Digit LCD	No	6.5 ft	461995	1PX61
		10 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Digit LCD	Yes		461995-NIST	2HZB9
Tachometers	0.20 to 6560	5 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Diğit LCD	No	0.5 ft	461895	8PMK7
	0.20 to 6560	5 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Digit LCD	Yes		461895-NIST	22DC94
Tachometer	0.20 to 6560	10 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Digit LCD	No	6.5 ft	RPM10	4GE84
with Infrared Thermometer	0.20 to 6560	10 to 99,999	0.5 to 20,000	0.05% of Reading +1 Digit	Last/Min/Max	5 Digit LCD	Yes	6.5 ft	RPM10-NIST	2HZC1
Amprobe										
Tachometers	3 to 30,000	10 to 99,999	10 to 19,999	+/-1% of Reading +/-2 Digits	No	LCD	No	1 ft	TACH-10	6NZG4
	0.40 to 6550	1 to 99,999	1 to 19,999	+/-0.02% +/-1 Digit	Built in	LCD	No	2 ft	TACH-20	4FKR9
Monarch										
Laser	0.16 to 6562		0.5 to 20,000	+/-0.01% of Reading	Last/Min/Max	5 Digit +5 Alpha Numeric LCD	Yes	25 ft	PLT200	4YE86
Tachometers	0.16 to 6562	5 to 200,000	0.5 to 20,000	+/-0.01% of Reading	Last/Min/Max	5 Digit +5 Alpha Numeric LCD	Yes	25 ft	PLT200 KIT	4YE87
Shimpo										
	0.40 to 12,500		0.8 to 25,000	+/-0.006% of Reading +/- 1 Digit		5 Digit LCD	Yes	20 ft	DT-205LR	21YD75
	0.40 to 12,500	6 to 99,999	0.8 to 25,000	+/-0.006% of Reading +/- 1 Digit	Last/Min/Max	5 Digit LED	Yes	20 ft	DT-207LR	21YD76
	0.80 to 25,000	6 to 99,999	0.8 to 25,000	+/-0.006% of Reading +/- 1 Digit	Last/Min/Max	5 Digit LCD	Yes	20 ft	DT- 205LR-S12	21YD77
Tachometers	0.80 to 25,000	6 to 99,999	0.8 to 25,000	+/-0.006% of Reading +/- 1 Digit	Last/Min/Max	5 Digit LED	Yes	20 ft	DT- 207LR-S12	21YD78
	0 to 6560	6 to 99,999	6 to 25,000	_	Last/Min/Max/10 user logged measurements, retained for 5 minutes	Digital LCD	Yes	6 ft	MT-200	45AE68
	0.40 to 12,500	6 to 99,999	1 to 25,000	_	1000 Readings	_	Available Separately	_	DT-2100	49VY90

# **Digital Contact Tachometers**

Extech-Each includes interchangeable cone, flat tips, surface speed wheel, carrying case, and AA batteries.

- Digital
- Max./min. values

Shimpo—Measure rotational, linear, and surface speed plus total length. 10-measurement memory. Each includes 2 cone tips, funnel tip, extension shaft, speed wheel, carrying case, and AA batteries. 21YD66 and 21YD67 have a standard 6" speed wheel.

## **EXTECH**



Video

- high-speed readings. Digital
- Last/max./min. recall
- 16 selectable units

Speed (FPM)	Contact RPM Range	RPM Accuracy	Display	Calibration Certificate	Mfr. Model	ltem No.
0.20 to 6560	0.5 to 20,000	+/-0.05%	5 Digit LCD	No	461891	1PX59
3 to 6560	10 to 20,000	+/-0.1% of Reading +2 Digits	_	No	461750	8PPJ5
0.05 to 12,500	0.10 to 25,000	+/-0.006% of Reading +/- 1 Digit	5 Digit LCD	Yes	DT-105A	21YD66
0.05 to 12,500	0.10 to 25,000	+/-0.006% of Reading +/- 1 Digit	5 Digit LED	Yes	DT-107A	21YD67
0.10 to 25,000	0.10 to 25,000	+/-0.006% of Reading +/- 1 Digit	5 Digit LCD	Yes	DT-105A-S12	21YD68
0.10 to 25,000	0.10 to 25,000	+/-0.006% of Reading +/- 1 Digit	5 Digit LED	Yes	DT-107A-S12	21YD69
	0.20 to 6560 3 to 6560 0.05 to 12,500 0.05 to 12,500 0.10 to 25,000	Speed (FPM)         RPM Range           0.20 to 6560         0.5 to 20,000           3 to 6560         10 to 20,000           0.05 to 12,500         0.10 to 25,000           0.05 to 12,500         0.10 to 25,000           0.10 to 25,000         0.10 to 25,000	Speed (FPM)         RPM Range         RPM Accuracy           0.20 to 6560         0.5 to 20,000         +/-0.05%           3 to 6560         10 to 20,000         +/-0.1% of Reading +2 Digits           0.05 to 12,500         0.10 to 25,000         +/-0.006% of Reading +/- 1 Digit           0.05 to 12,500         0.10 to 25,000         +/-0.006% of Reading +/- 1 Digit           0.10 to 25,000         0.10 to 25,000         +/-0.008% of Reading +/- 1 Digit	Speed (FPM)         RPM Range         RPM Accuracy         Display           0.20 to 6560 3 to 6560         0.5 to 20,000 10 to 20,000         +/-0.05% +/-0.1% of Reading +2 Digits         5 Digit LCD           0.05 to 12,500         0.10 to 25,000         +/-0.006% of Reading +/- 1 Digit         5 Digit LCD           0.05 to 12,500         0.10 to 25,000         +/-0.006% of Reading +/- 1 Digit         5 Digit LCD           0.10 to 25,000         0.10 to 25,000         +/-0.006% of Reading +/- 1 Digit         5 Digit LCD	Speed (FPM)         RPM Range         RPM Accuracy         Display         Certificate           0.20 to 6560 3 to 6560         0.5 to 20,000 10 to 20,000         +/-0.05% +/-0.1% of Reading +2 Digits         5 Digit LCD No         No           0.05 to 12,500 0.05 to 12,500         0.10 to 25,000 0.10 to 25,000         +/-0.006% of Reading +/-0.006% of Reading 0.10 to 25,000         5 Digit LCD 10 to 25,000 0.10 to 25,000         Yes 10 to 25,000 0.10 to 25,000           0.05 to 12,500 0.10 to 25,000         0.10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.10 to 25,000         -/-0.006% of Reading 0.20 to 10 to 25,000 0.20 to 25,000 0.	Speed (FPM)         RPM Range         RPM Accuracy         Display         Certificate         Model           0.20 to 6560 3 to 6560         0.5 to 20,000 10 to 20,000         +/-0.05% +/-0.1% of Reading +2 Digits         5 Digit LCD No         No         461891 461750           0.05 to 12,500         0.10 to 25,000 0.05 to 12,500         10 to 25,000 10 to 25,000         +/-0.006% of Reading +/-1 Digit 0.05 to 12,500 10 to 25,000         5 Digit LCD 10 to 25,000 10 to 25,00





21YD68

# **Noncontact Tachometers**

Each includes reflective tape for targeting. 5URHO also includes USB cable.

**Extech**—Employ a laser light source for noncontact rpm measurements from long distances. On-target indicator. Include 9V battery.

Max./min. values

Item	Noncontact RPM Range	RPM Accuracy	Display	Calibration Certificate	Working Distance	Mfr. Model	Item No.
Extech							
Laser Tachometer	2 to 99,999	+/-0.05%	5 Digit LCD	No	1.6 ft	461920	1TZP5
Tachometer with Counter	2 to 99,999	+/-0.05%	5 Digit LCD	Yes	1.6 ft	461920-NIST	6RGL0
Monarch	,						
Tachometer	5 to 99,999	+/-0.01% +/-1 Digit	5 Digit +5 Alpha Numeric LCD	No	3 ft	PT99	4YE85
Westward							
Tachometer	10 to 99.999	+/-0.04% +/-2 Digits	LCD	No	0.65 ft	5URH0	5URH0





WESTWARD

Monarch Instrument—Pocket Tach 99 accepts tripod mount. Includes AA batteries.

- Autoranging
- Selectable max./min./last reading
- Fixed decimal points
- LED light source



