







SDS-Max Concrete and Masonry Drill Bits

4 Cutter heads

Have variable-helix flutes that efficiently remove dust from the hole to minimize heat during drilling.

Drill Bit Size	Maximum Drilling Depth	Overall Length	Shank Diameter	Brand	Item No.
5/32 in	4 in	6 in	13/32 in	Milwaukee	785XZ1
3∕16 in	2 in	4 in	13/32 in	Milwaukee	785XZ2
5/16 in	4 in	6 in	13/32 in	Milwaukee	785XZ3
3∕8 in	7 in	13 in	45/64 in	Milwaukee	785XW5
7/16 in	10 in	12 in	13/ ₃₂ in	Milwaukee	785XZ5
	8 in	13 in	½ in	Bosch	490R46
1/2 in	23 in	28 in	45/64 in	Milwaukee	785XW7
	54 in	60 in	45/64 in	Milwaukee	785XW9
9/16 in	16 in	21 in	9/16 in	Bosch	490R67
916 III	16 in	21 in	45/64 in	Bosch	40ZJ35
5/8 in	31 in	36 in	5⁄8 in	Bosch	490R51
98 III	54 in	60 in	45/64 in	Milwaukee	785XX1
3/4 in	8 in	10 in	13/32 in	Milwaukee	785XY9
	12 in	17 in	45/64 in	Milwaukee	785XX2
	31 in	36 in	45/64 in	Bosch	40ZJ67
13/16 in		21 in	45/64 in	Milwaukee	785XX4
74 in	8 in	10 in	13/32 in	Milwaukee	785XZ0
⅓ in	24 in	29 in	⅓ in	Bosch	490R65

Drill Bit Size	Maximum Drilling Depth	Overall Length	Shank Diameter	Brand	Item No.
1 in	31 in	36 in	45/64 in	DeWalt	5MP67
	31 in	36 in	⁴⁵ / ₆₄ in	Milwaukee	45L355
11/16 in	18 in	23 in	45/64 in	Milwaukee	45L356
11/8 in	24 in	29 in	45/64 in	Bosch	40ZJ55
1 78 111	31 in	36 in	45/64 in	Milwaukee	785XY2
11/4 in	31 in	36 in	45/64 in	Bosch	40ZJ59
	31 in	36 in	45/64 in	DeWalt	5MP69
1% in	18 in	23 in	45/64 in	Milwaukee	45L363
17/16 in	18 in	23 in	45/64 in	Milwaukee	785XY6
	12 in	17 in	45/64 in	Milwaukee	785XY7
1½ in	16 in	21 in	45/64 in	Bosch	40ZJ32
1 72 111	18 in	23 in	45/64 in	Milwaukee	45L365
	20 in	22 in	45/64 in	Milwaukee	785Y23
19/16 in		23 in	45/64 in	Milwaukee	785XY8
13/4 in	18 in	23 in	45/64 in	Milwaukee	45L368
2 in	18 in	23 in	45/64 in	Milwaukee	45L369
31/8 in	20 in	22 in	45/64 in	Milwaukee	785Y24













Suitable for breaking up concrete and masonry in high-torque construction and demolition applications.

	Overall Length	Shank Diameter	Cutting Application	Brand	Item No.
	It Cutter		<u> </u>		
5 in	16 ½ in	45/64 in	Asphalt, Hard Ground	Milwaukee	45L245
	16 in	45/64 in	Tile Chiseling	DeWalt	1EC37
Bull P	oint Chis				
1/4 in	12 in	45/64 in	Chiseling Concrete/Block/Brick	Bosch	44H337
	18 in	45/64 in	Chiseling Concrete/Block/Brick	Bosch	20PK78
3/4 in	18 in	⁴⁵ / ₆₄ in	Concrete Chipping and Breaking	Milwaukee	45L249
Bushi	ng Tool				
1½ in	9 ½ in	45/64 in	Finishing, Roughing	Milwaukee	45L226
1 72 111	10 in	45/64 in	Roughing	DeWalt	19TF54
13/4 in	9 1/4 in	45/64 in	Finishing	Bosch	1UL89
174 111	9 ½ in 10 ½ in	45/64 in	Concrete Removal	Milwaukee	45L244
Clay S	pade				
41/4 in	16 in	45/64 in	Dirt, Hard Packed Gravel	Milwaukee	451N61
Concr					
13/4 in	12 in	0 in	Holemaking	Bosch	61HW77
Flat C	hisel		<u>-</u>		
	12 in	45/64 in	Breaking, Concrete Removal	DeWalt	34D579
	12 in	45/64 in	Chiseling Concrete/Block/Brick	Bosch	20PK74
1 in	12 in	45/64 in	Concrete Chipping and Breaking	Milwaukee	45L250
I In	16 in	45/64 in	Concrete Breaking	DeWalt	4LD52
	18 in	45/64 in	Chiseling Concrete/Block/Brick	Bosch	20PK75
	18 in	45/64 in	Concrete Chipping and Breaking	Milwaukee	45L252
0:	12 in	45/64 in	Surface Material Removal	DeWalt	4LD54
2 in	16 in	45/64 in	Concrete Splatter, Tile Removal	DeWalt	34D581
٥.	12 in	45/64 in	Surface Material Removal	DeWalt	5MP70
3 in	16 in	45/64 in	Concrete Splatter, Tile Removal	DeWalt	34D582
6 in	25 in	45/64 in	Composite Removal	Bosch	1UL95
	Scraper				
6 in	25 in	23/32 in	Finishing	Westward	22UV21
	d Rod Dr	iver			
5/8 in,- 3/4 in	10 in	⁴⁵ / ₆₄ in	Driving Ground Rods	Bosch	1UL97
5/8 in	10 in	45/64 in	Rod Drivina	Milwaukee	783WN3
	10 in	45/64 in	Driving Ground Rods	Milwaukee	45L257
¾ in		45/64 in	Driving Ground Rods	DeWalt	4LD57
Pointe	ed Spade	701 111		20114.1	
1/4 in	12 in	45/64 in	Chiseling Concrete/Block/Brick	Bosch	6MR15
1 in	16 in	45/64 in	Chipping	DeWalt	4LD50
	a Chisel		omppmg	Borrant	12200
3 in	12 in	23/32 in	Roughing	Westward	22UV18
	Chisel	732 111	riougining	Wootwara	LLOVIO
4 in	4 in	45/64 in	Tile Chiselina	DeWalt	1EC34
4½ in	17 in	45/64 in	Digging	Bosch	1UL96
5 in	15 in	45/64 in	Asphalt	Bosch	1UL88
53/8 in	16 in	45/64 in	Digging	Bosch	2LDP7
Tile C		707 111	Digging	Doddii	LLD! !
2 in	12 in	45/64 in	Tile Removal	Bosch	2LDP4
3 in	12 in	45/64 in	Surface Material Removal	Bosch	1UL90
0 111		, , , , , , , , , , , ,	ouriago matorial momoval	200011	.0200





Centering bit reduces bit walking and increases precision when drilling. Bits are ideal for creating large, shallow holes in concrete, masonry, and limestone.

Core Dia.	Drilling Depth	Overall Length	Shank Diameter	Brand	Item No.
13/4 in	17 in	22 in	1 3/4 in	Bosch	2LDE9
2 in	17 in	22 in	2 in	Bosch	2LDF2
21/4 in	17 in	22 in	2 1/4 in	Bosch	20PK60
25% in -	7 in	12 in		Bosch	2LDF3
298 III ·	17 in	22 in	2 5/8 in	Bosch	20PK61
31/4 in	17 in	22 in	3 1/4 in	Bosch	2LDF6
39/16 in	17 in	22 in	3 %16 in	Bosch	2LDF8
	7 in	12 in	4 in	Bosch	2LDF9
4 in	12 in	17 in	4 in	Bosch	2LDG1
	17 in	22 in	4 in	DeWalt	3AB28
5 in	7 in	12 in	5 in	Bosch	20PK62
	17 in	22 in	5 in	Bosch	2LDG2
C in	47 in	00 in	Cin	Doooh	OI DCO

Maximum









SDS-Max Deep-Hole Drill Bits

■ Shank size: 45/64" dia.

Feature a fluted head that grinds through concrete and masonry without creating a plug of material that needs to be cleared from the drill bit.

Drill Bit Size	Maximum Drilling Depth	Overall Length	Brand	Item No.
13/4 in -	18 in	24 in	Bosch	2LDG5
194 111 -	20 in	22 in	Milwaukee	22UP97
21/8 in -	18 in	24 in	Bosch	2LDG6
2 78 III -	20 in	22 in	Milwaukee	22UP98
2½ in -	18 in	24 in	Bosch	2LDG7
∠ /2 111 -	20 in	22 in	Milwaukee	22UP99
31/8 in	18 in	24 in	Bosch	2LDG8



45L255











Scaling

Self-Sharpening Chisel Bits for SDS-Max Hammer Drills

■ Shank size: 45/64" dia.

Design allows bits to wear evenly and retain their sharpness longer than standard chisel bits.

	Length	Cutting Application	Brand	Item No.					
Bull P	Bull Point Chisel								
½ in	16 in	Concrete Chipping and Breaking	Milwaukee	451N62					
1 in	12 in	Chipping	DeWalt	490U06					
Flat C	hisel								
1 in	16 in	Concrete Chipping and Breaking	Milwaukee	451N63					
1 111	16 in	Chiseling Concrete/Block/Brick	Bosch	6LFH7					
Pointe	ed Spad	9							
1/4 in	16 in	Chiseling Concrete/Block/Brick	Bosch	44H732					
94 III	16 in	Chiseling Concrete/Block/Brick	Bosch	48XX80					
1 in	16 in	Chiseling Concrete/Block/Brick	Bosch	6LFH6					
Scalir	g Chise	l							
3 in	12 in	Asphalt, Cutting Troughs, Mortar, Rust	Milwaukee	45L255					
Scrap	ing Chis								
2 in	12 in	Surface Material Removal	Milwaukee	45L256					
Tile C	hisel								
2 in	14 in	Surface Material Removal	Bosch	1UL94					
۱۱۱ ک	15 in	Tile Removal, Laminate, Mortar	Milwaukee	451N64					



Hollow Core Bits

■ Shank size: 45/64" dia.

Have a hollow shaft and dust-extraction holes that allow dust to be removed with a dust extractor during drilling. These 4-cutter bits have long life compared to 2-cutter bits and are less likely to bind up if they hit embedded rebar when drilling into concrete.

Drill Bit Size	Maximum Drilling Depth	Overall Length	Brand	Item No.
	8 in	17 in	Bosch	55JE11
5/8 in	15¾ in	23 ¾ in	DeWalt	54FH81
	16 in	25 in	Bosch	55JE12
3/4 in	12½ in	21 in	Bosch	48UR95
94 III	15¾ in	23 ¾ in	DeWalt	54FH80
7/8 in	15 in	25 in	Bosch	48UR97
78 III	15¾ in	23 ¾ in	DeWalt	54FH82
1 in	15¾ in	23 ¾ in	DeWalt	54FH79
	17½ in	27 in	Bosch	48UR98
11/4 in	16 in	21 in	Rosch	55 ID05