



**Flexon TUFF-GUARD**  
watering done right since 1956

## Cold Water Hoses

- Premium-Duty: 6 ply
- Heavy-Duty: 5 ply
- Standard-Duty: 4 ply
- Light-Duty: 2 and 3 ply
- Super Light-Duty: 1 ply

All have GHT connections. Hoses with aluminum couplings are certified for use in potable water applications. PVC Premium- and Heavy-Duty Hoses are

kink-resistant and have crushproof couplings. Standard-Duty polypropylene hoses feature a helix wrap, providing flexibility. They resist abrasion, crushing, and kinks. Polypropylene material is up to 35% lighter than standard hoses. Collapsible Hose 423J02 is a fabric hose. Super Light-Duty Soaker Hose 423H99 can be used above ground or buried for direct underground soaking.

Operating Temp.	Number of Ply	Hose Inside Dia.	Hose L	Hose Color	Coupling Material	Max. Pressure	Brand	Item No.
<b>Premium-Duty Hoses</b>								
<b>PVC</b>								
130°F Max. Temp.	6	3/4 in	50 ft	Black	Aluminum	500 psi	Tough Guy	423H80
	6	3/4 in	100 ft	Black	Aluminum	500 psi	Tough Guy	423H81
<b>Heavy-Duty Hoses</b>								
<b>PVC</b>								
	5	3/4 in	50 ft	Black	Aluminum	500 psi	Tough Guy	423H86
	5	3/4 in	50 ft	Green	Aluminum	500 psi	Tough Guy	423H87
	5	3/4 in	100 ft	Green	Aluminum	500 psi	Tough Guy	423H88
130°F Max. Temp.	5	3/4 in	50 ft	Black	Aluminum	500 psi	Tough Guy	423H89
	5	3/4 in	50 ft	Green	Aluminum	500 psi	Tough Guy	423H90
	5	3/4 in	75 ft	Black	Brass	500 psi	Tough Guy	423H91
	5	3/4 in	75 ft	Green	Brass	500 psi	Tough Guy	423H92
<b>Standard-Duty Hoses</b>								
<b>PVC</b>								
	4	3/4 in	50 ft	Green	Brass	250 psi	Tough Guy	423H93
	4	3/4 in	100 ft	Green	Brass	250 psi	Tough Guy	423H94
90°F Max. Temp.	4	1/2 in	50 ft	White	Aluminum	100 psi	Tough Guy	423H97
	4	3/4 in	50 ft	White	Aluminum	100 psi	Tough Guy	423H98
	4	1/2 in	100 ft	White	Aluminum	100 psi	Tough Guy	423H96
130°F Max. Temp.	4	3/4 in	100 ft	Yellow	Aluminum	250 psi	Tough Guy	491G54
<b>Collapsible Nylon/PVC</b>								
90°F Max. Temp.	0	1/2 in	50 ft	Green	Aluminum	400 psi	Flexon	423J02
<b>Light-Duty Hoses</b>								
<b>PVC</b>								
90°F Max. Temp.	3	3/4 in	50 ft	Green	Plastic/Brass	175 psi	Tough Guy	423H95
	3	3/4 in	15 ft	Green	Brass	175 psi	—	423J01
<b>Polypropylene</b>								
	2	3/4 in	25 ft	Blue	Brass	100 psi	Tuff-Guard	29FX94
	2	3/4 in	50 ft	Green	Brass	100 psi	Tuff-Guard	29FX92
	2	3/4 in	50 ft	Red	Brass	100 psi	Tuff-Guard	29FX93
158°F Max. Temp.	2	3/4 in	50 ft	Blue	Brass	100 psi	Tuff-Guard	12F251
	2	3/4 in	100 ft	Green	Brass	100 psi	Tuff-Guard	34FW19
	2	3/4 in	100 ft	Blue	Brass	100 psi	Tuff-Guard	12F253
<b>Super Light-Duty Soaker Hoses</b>								
<b>Rubber/PVC</b>								
90°F Max. Temp.	1	1/2 in	50 ft	Black	Plastic	100 psi	Tough Guy	423H99



423H80



423H87



423H94



423J02



423H95



12F252



423H99



442F17



423H82

## Heavy-Duty Hot/Cold Water Hoses

- GHT connections

Kink-resistant SEBS (Styrene Ethylene Butylene Styrene) hoses, 442F17 and 442F18 are certified for use in potable water applications and NSF 61 Listed. Rubber hoses have crushproof couplings and high-burst pressure.

Operating Temp.	Number of Ply	Hose Inside Dia.	Hose Length	Hose Color	Coupling Material	Max. Pressure	Item No.
<b>Kink-Resistant Rubber Compound Hoses</b>							
-40° to 165°F Max. Temp.	4	3/4 in	50 ft	Red	Aluminum	400 psi	442F17
-40° to 160°F Max. Temp.	4	3/4 in	50 ft	Red	Aluminum	400 psi	442F18
<b>Rubber Hoses</b>							
	3	3/4 in	25 ft	Red	Aluminum	400 psi	423H82
	3	3/4 in	50 ft	Red	Aluminum	401 psi	423H83
180°F Max. Temp.	3	3/4 in	75 ft	Red	Aluminum	402 psi	423H84
	3	3/4 in	50 ft	Red	Aluminum	403 psi	423H85



55AW95



55AX13

## EPDM Garden Hoses

- Temp. range: -40° to 190°F
- Safety factor: 4:1

EPDM (ethylene propylene diene monomer) garden hoses provide excellent resistance to UV rays and ozone and are used in landscaping and grounds-maintenance applications. Hoses with coupled assembly feature fittings on both ends for attaching to equipment. Bulk hoses do not come with fittings.

Hose I.D.	Max. Working Pressure @ 70°F	25 ft Item No.	50 ft Item No.	75 ft Item No.	100 ft Item No.
<b>Bulk Hose</b>					
1/2 in	150 psi	55AW94	55AW98	55AX03	55AX07
3/8 in	150 psi	55AW95	55AW99	55AX04	55AX08
3/4 in	150 psi	55AW96	55AX01	55AX05	55AX09
1 in	150 psi	55AW97	55AX02	55AX06	55AX10
<b>Coupled Assembly</b>					
1/2 in	150 psi	55AX11	55AX15	55AX19	55AX23
3/8 in	130 psi	55CN83	55CN84	55CN85	55CN86
3/4 in	150 psi	55AX12	55AX16	55AX20	55AX24
3/4 in	150 psi	55AX13	55AX17	55AX21	55AX25
1 in	150 psi	55AX14	55AX18	55AX22	55AX26