

1-800-GRAINGER (472-4643)

Choose the Right Ladder for the Job

STEP 1: WHAT MATERIAL DO YOU NEED?

Fiberglass or Aluminum?

Fiberglass

Rugged and durable, ideal when working around electricity. Feature nonconductive side rails.



Aluminum

Lightweight and easy to carry. Not for use around electricity.



STEP 2: CHOOSE LOAD CAPACITY/DUTY RATINGS

Load capacity is the combined weight of user and materials.



STEP 3: CHOOSE THE SIZE/HEIGHT

STEPLADDERS		EXTENSION LADDERS	
Max. Ht. of Desired Reach (ft.)*	Choose This Size (ft.)	Height to Top Support Point (ft.)	Choose This Size (ft.) †
7	3	9 Maximum	16
8	4	9 to 13	20
9	5	13 to 17	24
10	6	17 to 21	28
11	7	21 to 25	32
12	8	25 to 28	36
14	10	28 to 31	40
16	12		
18	14		
20	16		

* Assumes a 5-ft. 6" person with a vertical 12" reach.

† Reflects section overlap, ladder angle and 3-ft. extension above roof line.

L7300 SERIES

- Safely lean against wall
- Rail latch holds rear rail to front rail in leaning mode

Fiberglass, Type 1AA, 375-lb. Duty Rating



6300 SERIES

- Red side rails
- Molded versatile LockTop securely holds drills and tools
- Top accommodates Lock-In accessories
- Molded large boots with EDGE Bracing
- Steel Internal spreader bars

Fiberglass, Type 1AA, 375-lb. Duty Rating



7300 SERIES

- Molded external rail shields and EDGE Bracing
- Aluminum Tool-Tra-Top securely holds tools
- Extra-large knee braces—front and back
- Extra-wide base width
- Steel internal spreader bars

Fiberglass, Type 1AA, 375-lb. Duty Rating



7400 SERIES

- Aluminum external rail shields and EDGE Bracing
- Aluminum Tool-Tra-Top securely holds tools
- Extra-large knee braces—front and back
- Extra-wide base width—widest ladder in industry
- Larger spread than 7300 Series
- Aluminum internal spreader bars

Fiberglass, Type 1AA, 375-lb. Duty Rating



400 SERIES

- Aluminum Tool-Tra-Top
- Fully knee braced—front and back
- Slip-resistant foot pads
- Internal spreader bars except on 4-ft. and 6-ft. sizes

Aluminum, Type 1AA, 375-lb. Duty Rating



6100 SERIES

- Molded Proguard Boot provide firm slip-resistant footing
- Versatile HolsterTop securely hold drills and tools
- Top accommodates Lock-In accessories
- Metal bottom step knee braces
- Internal spreader bars

Fiberglass, Type 1A, 300-lb. Duty Rating



6200 SERIES

- Orange side rails
- Molded versatile LockTop securely hold drills and tools
- Top accommodates Lock-In accessories
- Molded large boots with EDGE Bracing
- Steel internal spreader bars

Fiberglass, Type 1A, 300-lb. Duty Rating



370 SERIES

- Molded Tool-Tra-Top securely holds tools
- Internal "H" spreader on 4-ft., 5-ft., and 6-ft. sizes
- Auto-closing molded pail shelf
- Aluminum foot bracket with slip-resistant pad

Aluminum, Type 1A, 300-lb. Duty Rating



6000 SERIES

- Molded HolsterTop
- Top accommodates Lock-In accessories
- EDGE bracing at bottom
- External spreader bars

Fiberglass, Type 1, 250-lb. Duty Rating



360 SERIES

- Molded Tool-Tra-Top
- Auto-closing molded pail shelf
- External spreaders
- Slip-resistant foot pads
- Ideal for painting

Aluminum, Type 1, 250-lb. Duty Rating



5900 SERIES

- Molded HolsterTop
- Top accommodates Lock-In accessories
- EDGE bracing at bottom
- External spreader bars
- Ideal for light-duty or homeowner use

Fiberglass, Type II, 225-lb. Duty Rating



Stepladders

- The most popular ladder style used for low and medium heights

Series	Ladder Height	Material	Item No.
L7300	4 ft	Fiberglass	458R92
	6 ft	Fiberglass	458R93
	8 ft	Fiberglass	458R94
	10 ft	Fiberglass	458R95
	12 ft	Fiberglass	458R96
6300	4 ft	Fiberglass	29JV18
	5 ft	Fiberglass	29JV20
	6 ft	Fiberglass	29JV21
	8 ft	Fiberglass	29JV23
	10 ft	Fiberglass	29JV25
7300	12 ft	Fiberglass	29JV27
	3 ft	Fiberglass	41D244
	4 ft	Fiberglass	6JJ81
	5 ft	Fiberglass	3AZX3
	6 ft	Fiberglass	6JJ82
7400	8 ft	Fiberglass	6JJ83
	10 ft	Fiberglass	6JJ84
	12 ft	Fiberglass	6JJ85
	3 ft	Fiberglass	41D241
	4 ft	Fiberglass	4XN71
400	5 ft	Fiberglass	3AZX4
	6 ft	Fiberglass	4XN72
	7 ft	Fiberglass	3AZX5
	8 ft	Fiberglass	4XN73
	10 ft	Fiberglass	4XN74
6100	12 ft	Fiberglass	4XN75
	4 ft	Aluminum	4XN58
	6 ft	Aluminum	4XN59
	8 ft	Aluminum	4XN60
	10 ft	Aluminum	4XN61
6200	12 ft	Aluminum	4XN63
	4 ft	Fiberglass	29JV19
	6 ft	Fiberglass	29JV22
	8 ft	Fiberglass	29JV24
	10 ft	Fiberglass	29JV26
370	12 ft	Fiberglass	29JV28
	3 ft	Fiberglass	41D245
	4 ft	Fiberglass	3W421
	5 ft	Fiberglass	3AZX1
	6 ft	Fiberglass	3W141
400	7 ft	Fiberglass	3AZX2
	8 ft	Fiberglass	3W142
	10 ft	Fiberglass	3W183
	12 ft	Fiberglass	3W422
	3 ft	Aluminum	2EJG8
6000	4 ft	Aluminum	4W074
	5 ft	Aluminum	3AZX9
	6 ft	Aluminum	3W423
	8 ft	Aluminum	3W424
	10 ft	Aluminum	4W172
360	14 ft	Aluminum	4XN64
	16 ft	Aluminum	4XN67
	4 ft	Fiberglass	4W077
5900	5 ft	Fiberglass	3AZW9
	6 ft	Fiberglass	4W078
	8 ft	Fiberglass	4W079
	4 ft	Aluminum	41D304
Type II, 225 lb Duty Rating	5 ft	Aluminum	41D305
	6 ft	Aluminum	41D306
	8 ft	Aluminum	4GNK8
Type I, 250 lb Duty Rating	4 ft	Fiberglass	41D251
	6 ft	Fiberglass	41D252
	8 ft	Fiberglass	41D253