

## **Specialty Ladders**

#### **OBEL SERIES**

- Custom molded top designed for electrical contractors
- Integrated retractable conduit holder for cutting pipe
- Wire spool holders and a multiuse hook
- EDGE bracing at bottom
- Internal spreader bars Fiberglass Electricians Job Station

## Stepladders, Type 1AA, 375-lb. Duty Rating

## **E7400 SERIES**

- Convenient for versatile applications
- Ideal for two-person jobs and working at various heights
- Duty rating applies to each stepladder side

- Double riveted, fully knee braced steps
- Aluminum external rail shields and EDGE bracing

Fiberglass Extension Trestle Ladder, Type 1A, 300-lb. Duty Rating

### FTP6200 SERIES

- Back rail fits through studs, tight areas, around corners and uneven surfaces
- Spreader handle designed for convenient setup and transport
- Fully based front section
- Extra-wide stance for stability
- Available up to 12 ft.

Fiberglass Tripod Ladder, Type 1A, 300-lb. Duty Rating

Series	Ladder Height	Material	Item No.
Type IAA, 375 lb Duty Rati	ng		
OBEL00	4 ft		1FCF1
	6 ft	_	1FCF2
	8 ft	Fiberglass	1FCF3
	10 ft	_	1FCF4
	12 ft		1FCF5
Type IA, 300 lb Duty Ratin	g		
E7400	8 ft	_	4XP05
	10 ft		4XP06
	12 ft		4XP07
	14 ft	_	4XP08
	16 ft	Fiberglass -	4XP09
FTP6200	4 ft		4ZY19
	6 ft		4EB99
	8 ft		4ZY20
	10 ft	-	41D249
	12 ft	-	41D250



WERNER.

# **Adjustable Enclosed Safety Cages**

- Nonconductive, high-strength, fiberglass-resin composite
- Fully adjustable 1-ft. increments

Offer versatile, safe alternative to tie-off, allowing access to constricted areas and drop ceilings while complying with tie-off rules. Help protect operators in a fully enclosed working platform, allowing them to work safely and quickly with 2 hands. Each side adjusts independently to multiple heights; adjusts to work safely on uneven surface and stairs. Models with Wheel Lift casters allow cage to move from place to place fully deployed. Built-in Tip & Glide wheels make it quick-and-easy to roll anywhere.

Series Type IAA, 375 lb Duty Rating	Platform Height	Includes	Item No.
Compact Safety Cage	4 to 6 ft	Tip and Glide Wheels	48RR82
	6 to 10 ft	Net, Outriggers, Side Tip Wheels, Wheel Lift	48RR88
		Outriggers, Ratchet Levelers, Side Tip Wheels, Wheel Lift	48RR89
Adjustable Safety Cage	3 to 5 ft	Net, Wheel Lift	36GL22
	5 to 9 ft	- Net, Outriggers, Wheel Lift	36GL23
	8 to 14 ft	- ivet, Outriggers, Writer Lift	36GL24



# **Ladder Jacks, Planks and Leveler**

**Aluminum Extension Planks - PA200** Series-Made of 2" deep box section extrusions for outstanding rigidity in ladder jack, trestle ladder, and step stool applications. Locking mechanism sets plank in 12" incre-

ments; positive stops prevent overextending. WARNING: When assembled as a scaffold or staging, planks must be used in conjunction with suitable guardrail protection in compliance with applicable governmental codes, ordinances, regulations, and safe practices.

Ladder Jack Clamping System—Ladder jacks mount to either side of extension ladder and clamps securely hold stage platform to ladder jacks. OSHA and ANSI Standards require ladder jacks only be used on Type 1, Type 1A, or Type 1AA ladders.

Accommodates up to 20"W stage planks

	Description	Series	Overall Length	Load Capacity	Material	Item No.
Extensio	n Plank	PA200	6 to 9 ft	250 lb	Aluminum	4XP30
Extensio	n Plank	PA200	8 to 13 ft	250 lb	Aluminum	4XP31
Extensio	n Plank	PA200	10 to 17 ft	250 lb	Aluminum	4XP32
Ladder J	ack Clamping System	_		300 lb		4XN82
Ladder L	.eveler	_	_	_	Aluminum	4XP35

